



SPECIFICATIONS:

- ① **BASE: 319 CAST ALUMINUM**
- ② **ABRASIVE: SILICON CARBIDE ABRASIVE , CROSSHATCH PATTERN 1/8" DEEP**
3. **FINISH: SAND CAST**
4. **POURED CONCRETE STAIRS: NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS**
5. **LENGTH: 6" MINIMUM 6'-0" MAXIMUM**
6. **WING ANCHORS: STANDARD FOR POURED CONCRETE APPLICATIONS; STEEL ANCHORS AND STAINLESS STEEL HARDWARE**

LENGTH ±1/8	QTY

PROJECT:				
ARCHITECT:				
CONTRACTOR:				
QTY:				
PART#:		STCA-L4W		
NYSTROM <small>Right to site.</small> 9300 73rd Avenue North Brooklyn Park, MN 55428		TITLE:		
		Stair Tread, Cast Series 4", Cast Aluminum Crosshatch Long Nosing for Pan, Wing Anchor		
	NAME	DATE	SIZE	DWG. NO.
DRAWN	SJB	3/31/11	A	STCA-L4W
RELEASED	DWO	3/31/11	WEIGHT: 1.59 LB/FT	SHEET 1 OF 1