







SPECIFICATIONS:

В

- $\langle 1 \rangle$ **BASE**: GRAY CAST IRON
- $\langle 2 \rangle$ **ABRASIVE**: SILICON CARBIDE ABRASIVE ,CROSSHATCH PATTERN 1/32" THICK
- 3. FINISH: BLACK PAINT
 4. POURED CONCRETE STAIRS: NOSING SHALL
 TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. **LENGTH:** 5'6" MAXIMUM
- 6. WING ANCHORS: STANDARD FOR POURED CONCRETE **APPLICATIONS**

LENGTH	QTY

PROJECT:						
ARCHITECT:						
CONTRACTOR:						
	QTY:					
PART#:				STCI-C3W		
Right to site. 9300 73rd Avenue North Brooklyn Park, MN 55428				TITLE: Stair Tread, Cast Series 3", Cast Iron Crosshatch Short Nosing for Concrete, Wing Anchor		
	NAME	DATE	SIZE	DWG. NO.		REV
DRAWN	TVANG	3/14/11	Α	STCI-C3W		Α
RELEASED	PE	3/14/11	WE	IGHT: 3.25 LB/FT SHEET 1 C		OF 1

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.