

NOTES:

В

- PROFILE: HIGH IMPACT VINYL ACRYLIC EXTRUSION LOCKED IN PLACE, NOMINAL 0.078" (1.98mm) THICK 1.
- 2. CLASS A FIRE RATING, TESTED TO ASTM E84
- 3. RETAINER: CONTINUOUS 6063 T-5 ALUMINUM RETAINER, NOMINAL 0.062" (1.57mm) THICK
- EXTRUSION: PEBBLE GRAIN FINISH WHICH CONTAINS EPA REGISTERED MICRO-CHEK ANTIMICROBIAL 4. **AGENT**
- 5. VINYL CRASH RAIL LENGTH: PROVIDED IN 20' CONTINUOUS SECTIONS
- END CAP: #CRVS4C-EC, OUTSIDE CORNER: #CRVS4C-OC, 135 DEG OUTSIDE CORNER: #CRVS4C-OC135, INSIDE CORNER: #CRVS4C-IC, SPLICE KIT: #CRVS4C-SK 6.
- FASTENERS AND PARTITION COMPONENTS PROVIDED BY OTHERS. 7.

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.

	PROJECT:							
	ARCHITECT:							
	CONTRACTOR:							
	NYSTROM Right to site. 9300 73rd Avenue North Brooklyn Park, MN 55428				TITLE: 4" VINYL CRASH RAIL SURFACE MOUNT CONTINUOUS RETAINER			
		NAME	DATE	SIZE	DWG. NO.			REV
	DRAWN	MDS	23APR13	Α		CRVS4C		A
1	RELEASED	PGE	01MAY13	WE	IGHT: 1.03 lbs/ft		SHEET 1	OF 1

QUANTITY

COLOR