

COLOR

QUANTITY

NOTES:

В

- 1. PROFILE: HIGH IMPACT VINYL ACRYLIC EXTRUSION LOCKED IN PLACE, NOMINAL 0.078" (1.98mm) THICK
- 2. CLASS A FIRE RATING, TESTED TO ASTM E84
- 3. RETAINER: CONTINUOUS 6063 T-5 ALUMINUM RETAINER, NOMINAL 0.062" (1.57mm) THICK
- 4. **EXTRUSION**: PEBBLE GRAIN FINISH WHICH CONTAINS EPA REGISTERED MICRO-CHEK ANTIMICROBIAL AGENT
- 5. VINYL CRASH RAIL LENGTH: PROVIDED IN 20' CONTINUOUS SECTIONS
- 6. END CAP: #CRVS6C-EC, OUTSIDE CORNER: #CRVS6C-OC, 135 DEG OUTSIDE CORNER: #CRVS6C-OC135, SPLICE KIT: #CRVS6C-SK
- FASTENERS AND PARTITION COMPONENTS PROVIDED BY OTHERS.

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.

	PROJECT: ARCHITECT:						
	CONTRACTOR:						
	Right to site. 9300 73rd Avenue North Brooklyn Park, MN 55428				TITLE: 6" VINYL CRASH RAIL SURFACE MOUNT CONTINUOUS RETAINER		
		NAME	DATE	SIZE	DWG. NO.		REV A
	DRAWN	MDS	24APR13	Α	CRVS6C		
	RELEASED PGE 01MAY13 WEI				IGHT: 1.13 lbs/ft	SHEET 1	OF 1

2

1