

NOTES:

В

- 1. PROFILE: HIGH IMPACT VINYL ACRYLIC EXTRUSION LOCKED IN PLACE, NOMINAL 0.078" (1.98mm) THICK
- 2. CLASS A FIRE RATING, TESTED TO ASTM E84
- 3. RETAINER: CONTINUOUS 6063 T-5 ALUMINUM RETAINER, NOMINAL 0.060" (1.52mm) THICK
- 4. **EXTRUSION**: PEBBLE GRAIN FINISH WHICH CONTAINS EPA REGISTERED MICRO-CHEK ANTIMICROBIAL AGENT
- 5. VINYL CRASH RAIL LENGTH: PROVIDED IN 20' CONTINUOUS SECTIONS
- 6. END CAP: #CRVE7C-ECT, OUTSIDE CORNER: #CRVE7C-OCT, 135 DEG OUTSIDE CORNER: #CRVE7C-OC135, SPLICE KIT: #CRVE7C-SK
- FASTENERS AND PARTITION COMPONENTS PROVIDED BY OTHERS.

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.

PROJECT:				
ARCHITECT:				
CONTRACTOR:				
Right to site. 9300 73rd Avenue North Brooklyn Park, MN 55428		CRESCENT SHAPE, EXTENDI	" VINYL CRASH RAIL IT SHAPE, EXTENDED MOUNT CKET, CONTINUOUS RETAINER	
NAME DATE	SIZE	DWG. NO.	REV	
DRAWN MDS 30MAY13	Α	CRVE7C-B15	A	
RELEASED PGE 30MAY13	WE	IGHT: 1.50 lbs/ft	SHEET 1 OF 1	

QUANTITY

COLOR

В