Partition Breakdown

PARTITION STYLE **APPLICATION AVAILABLE MATERIALS** Overhead Brace (Series 400) This style provides the most Fusion™ Granite Sentinel" Floor-Mounted, economical solution for heavy • Baked Enamel traffic and vandalism-prone areas. Because it requires • Bradmar® Solid Plastic no special floor or ceiling • Solid Phenolic Core construction, installation is easy in new construction or existing • Plastic Laminate buildings. The anti-grip headrail Stainless Steel provides outstanding rigidity. This style complements design • Baked Enamel Floor-Braced (Series 500) with functional performance. • Solid Phenolic Core Recommended for buildings with high ceilings, it enhances the • Plastic Laminate effect of spaciousness. • Stainless Steel A minimum three inch concrete floor for anchoring is required. This style is ideal for areas with • Baked Enamel Ceiling-Hung (Series 600) low ceilings. Offering an area • Solid Phenolic Core free from obstruction to allow for fast and easy maintenance, Plastic Laminate the system requires structural Stainless Steel supports in the ceiling for maximum rigidity. Not recommended for ceiling heights over eight feet. This style works well where Baked Enamel Floor-to-Ceiling (Series 700) additional support is required. Bradmar® Solid Plastic Anchored at the floor and ceiling. • Solid Phenolic Core Plastic Laminate Stainless Steel

See bradleycorp.com for more information about Mills Partition materials and styles, and technical specifications.

