



WHS SYSTEMS

DESCRIPTION

WHS systems are made up of frames, and faced panel with two elastomeric joint fillers (PVC).

BASIC USE

WHS systems are used for covering wall expansion joint openings and providing a clean and aesthetically pleasing sightline where the joints occur.

FEATURES

- Installation is easy
- During seismic movement, the "Seismic Sentry" engages to lift the center plate to avoid being crushed by the side frames.
- Seal can be installed later on most systems if necessary.
- The seal is available in many colors
- Floor and wall systems may be fire rated.

COLOR OPTIONS

Standard:

Lunar White, Prairie, Fog, Carbon

Non-Standard:

Heather, Madrid, Slate, Statuette

FINISH

Aluminum frames and faced panel are mill finish.

STORAGE

All materials should be stored in a cool, dry location prior to use.

INSTALLATION

Apply to clean, dry, sound substrate. Any blockouts must be level before installation can begin. See manufacturer's standard installation guide.

LIMITED WARRANTY

MM Systems Corporation warrants materials furnished to be free of defects in materials and workmanship for a period of one year from date of shipment. Materials must be installed in strict accordance with approved MMSC shop drawings and/or installation instructions. MMSC shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use of the product.

TECHNICAL DATA

- Aluminum conforms to ASTM B221 for extrusion alloys 6063-T5 and 6061-T6.
- Extruded Preformed Seals PVC Profiles conform to ASTM C920.
- Conforms to ASTM E1399 for cycling joint.