

## Product Data Sheet



### Description and Uses

Owens Corning Metal Building Utility Blanket is an unfaced light density fibrous glass blanket. The product is designed to be laminated with a variety of facings and is used for condensation and noise control in metal buildings. The product is available in rolls with widths of 36", 48" and 72" at a nominal product thickness of 2".

### PureFiber<sup>®</sup> Technology Advances

- Made with natural<sup>1</sup> materials, formaldehyde-free<sup>2</sup> and soft to the touch
- Uses a minimum of 50% recycled content—30% being post-consumer
- GREENGUARD Children and Schools Certified<sup>SM</sup> and GREENGUARD Indoor Air Quality Certified<sup>®</sup>
- Thickness recovery provides outstanding thermal and acoustical performance

### Application

After the product is laminated with an appropriate facing, the insulation is typically installed in a single layer between the structural members (purlins for

### Physical Properties

Property	Test Method	Value
Noncombustible	CAN/ULC S114	Meets Max temp rise, no flaming and max mass loss criteria
Nominal Density	ASTM C 167	0.8 PCF
Fire Hazard Classification	ASTM E 84, UL 723, CAN/ULC S102	FHC 25/50
Moisture Absorption	ASTM C 1104	<2% by weight
Fungi Resistance	ASTM C 1338	No growth greater than comparative item

<sup>1</sup>The surface burning characteristics of these products have been determined in accordance with ASTM E 84, UL 723, or CAN/ULC S102. These standards should be used to measure and describe the properties of materials, products or assemblies in response to heat and flame under controlled laboratory conditions and should not be used to describe or appraise the fire hazard or fire risk of materials, products or assemblies under actual fire conditions. However, results of this test may be used as elements of a fire risk assessment which takes into account all of the factors which are pertinent to an assessment of the fire hazard of a particular end use. Values are reported to the nearest 5 rating.

### Thermal Resistance

Thickness		R-Value	RSI Value <sup>e</sup>
Inches	mm		
2	51	7.0 <sup>f</sup>	1.23 <sup>f</sup>

<sup>f</sup>Pre-lamination values

roofs and girts for walls) and the exterior panels. In most cases, the product is installed over and perpendicular to the structural members with the facing towards the interior of the structure. Care should be taken not to overstretch the insulation material as excess compression can reduce the insulation's thermal performance. All seams should be sealed to help maintain a continuous vapor retarder.

Metal Building Utility Blanket can also be used over the purlins in roof systems that utilize a primary layer of insulation between the purlins.

### Availability

Owens Corning Metal Building Utility Blanket is fabricated and distributed by a nationwide network of independent laminators assuring prompt service and delivery. Contact your Owens Corning sales

representative for the names of insulation laminators servicing your area.

### Specification Compliance

CAN/ULC - S702 - Standard for Mineral Fiber Thermal Insulation for Buildings-Type I.

### Notes

1. Unfaced insulation made with a minimum of 99% by weight natural materials consisting of minerals and plant-based compounds (not including packaging).
2. Applies to the insulation component only.



INNOVATIONS FOR LIVING®

# Metal Building Utility Blanket Insulation

## Product Data Sheet

### Disclaimer of Liability

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Owens Corning makes no representation about, and is not responsible or liable for the accuracy or reliability of data associated with particular uses of any product described herein. Nothing contained in this bulletin shall be considered a recommendation.

Scientific Certification Systems (SCS) provides independent verification of recycled content in building materials and verifies recycled content claims made by manufacturers. For more information, visit [www.scs-certified.com](http://www.scs-certified.com).

The GREENGUARD INDOOR AIR QUALITY CERTIFIED Mark is a registered certification mark used under license through the GREENGUARD Environmental Institute.



INNOVATIONS FOR LIVING®

**OWENS CORNING INSULATING SYSTEMS, LLC**  
ONE OWENS CORNING PARKWAY  
TOLEDO, OHIO 43659

**1-800-GET-PINK®**  
[www.owenscorning.com](http://www.owenscorning.com)

Pub. No. 45109-E. Printed in U.S.A. June 2011. THE PINK PANTHER™ & ©1964-2011 Metro-Goldwyn-Mayer Studios Inc. All Rights Reserved. The color PINK is a registered trademark of Owens Corning. ©2011 Owens Corning.

