

PRE-MIXED FLOOR LEVELER

PRICE

- **Lightweight formula – Ready to use**
- **Levels uneven floors in minutes**
- **Pour on or skim coat**
- **Use over concrete, plywood and vinyl**



PRODUCT DESCRIPTION

Easily smooths and levels interior floors prior to installing tile or vinyl flooring. Floor Leveler's unique lightweight formula mixes easily. Just pour it on your floor. Seeks its own level in minutes. Can be applied from featheredge to 1/2" (13 mm) thick in one pour. Protected with MoldGard® Technology to resist mold and mildew growth.

AREAS OF USE

- For interior use only
- Concrete
- Cement backerboards
- Ceramic tile
- Exterior grade plywood
- Vinyl flooring

LIMITATIONS

- Do not apply when temperature is below 50° F (10° C) or on sloped surfaces that require drainage.
- Do not use as a wear surface.

SURFACE PREPARATION

General Surface Preparation:

All surfaces must be structurally sound, clean, dry and free from contaminants that would prevent a good bond. Concrete must be fully cured and not subject to hydrostatic pressure. Concrete surfaces should accept water penetration. Smooth concrete surfaces, existing glazed tile, terrazzo, or polished stone should be roughened or scarified. Sheet vinyl must be well bonded and stripped of old finish. Surfaces and materials should be maintained at a temperature above 50° F (10° C) or below 100° F (38° C) for 72 hours.

Plywood Substrates:

Plywood flooring, including those under resilient flooring must be structurally sound and meet all ANSI and deflection requirements (no flex or movement). For questions about proper subfloor installation, call Technical Services at 800-282-8786.

APPLICATION

Some liquid may settle to the bottom of the container. Stir thoroughly until it reaches a fluid, pourable consistency. As a Self Leveler — Pour directly from pail onto the lowest spot on the floor. Apply to a 6 - 8 sq. ft. (.5 - .75 m²) area at a time. The material will seek its own level during the first 10 minutes. Side by side pours must be applied no more than 5 - 10 minutes apart to ensure a seamless, smooth surface. Overlap side by side pours by 1" - 3" (2.5 - 7.6 cm). For featheredging and smoothing, use a finish trowel. Single pour should not exceed 1/2" (13 mm). A second layer can be applied after the first layer has thoroughly dried. As a Skim Coat — Pour directly from pail onto the floor in an area no larger than 5 - 10 sq. ft. (.46 - .9 m²) at a time. Holding a finish trowel at a 30° angle, spread product approximately 1/8" (3 mm) thick.

DRYING TIME

When Used as a Self Leveler — 12 to 24 hours drying time depending on application thickness, floor surface and humidity. When Used as a Skim Coat — 2 to 4 hours. If installing vinyl flooring over Floor Leveler, the floor must be completely dry with no moisture present. Test for moisture content first.



CUSTOM[®]
BUILDING PRODUCTS

COVERAGE

Approximately 6 - 8 sq. ft. per 6 lbs. (.55 - .65 M²/2.72 kg) at 1/4" (6 mm) thickness.

CLEAN-UP

Clean tools with water before material dries.

CAUTION

Contains Petroleum Distillates. If ingested, do not induce vomiting. Call a physician immediately. Use with adequate ventilation. Non-flammable.

KEEP OUT OF REACH OF CHILDREN.

DO NOT TAKE INTERNALLY. KEEP FROM FREEZING.

ORDERING INFORMATION

ITEM CODE	SIZE	COLOR	PACKAGE
FL1	6 lbs. (2.72 kg)	Gray	Pail

WARRANTY

Custom's Standard Warranty applies. For complete information call 800-272-8786 or visit www.custombuildingproducts.com.



CUSTOM[®]
BUILDING PRODUCTS