

T1-60™ WALL & FLOOR TILE ADHESIVE

- High tack, quick grab
- Easy to cleanup
- Fast drying

PRICE



PRODUCT DESCRIPTION

Commercial grade T1-60 Wall & Floor Tile Adhesive offers economical and durable bonds for most wall, floor and countertop installations of ceramic tile. Meets ANSI A136.1 Type I requirements for organic adhesives.

USES — TILE TYPES

Ceramic, mosaic, quarry, pavers, gauged slate and porcelain tile. Maximum ceramic tile size for floor applications is 8" x 8" (20 x 20 cm).

AREAS OF USE

- For interior use on floors, walls and countertops
- Interior wet areas with prolonged water exposure such as gang showers, tub surrounds and shower walls as defined by ANSI A136.1, Type I requirements
- Concrete, masonry, plaster
- Gypsum wallboard (dry areas)
- Water-resistant wallboard
- WonderBoard,® cement backerboards
- Exterior grade plywood (interior dry areas)
- Existing ceramic tile (walls and countertops)
- Plastic laminates

LIMITATIONS

- Do not bond directly to hardwood, Luan plywood, particle board, parquet, cushion or sponge-back vinyl flooring or their adhesive residue, resilient flooring, metal, fiberglass, plastic and OSB panels.
- Do not use in steamrooms, shower floors, underwater or areas exposed to hydrostatic pressure.

- Do not use over wood surfaces in wet areas.
- Do not use outdoors; use an appropriate Custom® thin-set mortar.
- Do not use to install fixtures, ungauged natural stone, gauged slate thicker than 3/8" (9.5 mm), marble or granite tile, transparent glass tile, Saltillo pavers or tile with lugs on floors.

SURFACE PREPARATION

General Surface Preparation:

Surfaces must be structurally sound, clean, dry and free from grease, oil, dirt, curing compounds, sealers, adhesives or any other contaminant that would prevent a good bond. Glossy or painted surfaces must be sanded, stripped and cleaned of waxes, dirt or any contaminants. Surfaces and materials should be maintained at a temperature above 50° F (10° C) or below 100° F (38° C) until adhesive cures.

Cementitious Substrates:

Concrete must be porous, fully cured and free of any surface contaminants and efflorescence and not subject to hydrostatic pressure. Surface should accept water penetration to form a good bond. Test by sprinkling water on various areas of the substrate. If water penetrates, then a good bond can be achieved. If water beads, surface contaminants are present and loss of adhesion may occur. The contaminants should be removed before installation. Concrete slabs should be finished with a steel trowel and fine broom finish to enhance the bond. Smooth concrete slabs must be roughened to ensure a good bond.



CUSTOM®
BUILDING PRODUCTS

Plywood Substrates:

Plywood floors, including those under resilient flooring, must be built to industry standards. Deflection not to exceed L/360. For questions about proper subfloor installation, call Technical Services.

WonderBoard® Backerboard:

As a superior alternative to an additional layer of plywood, WonderBoard Backerboard may be installed over plywood subfloors. Refer to WonderBoard data sheets for installation information.

Existing Ceramic Tile or Plastic Laminates:

Plywood flooring must be structurally sound and meet all ANSI and deflection requirements. Plastic laminates must be well bonded, clean and free of all contaminants. Roughen the surface by sanding or scarifying, rinse and allow to dry. For existing well-bonded ceramic tile, mechanically abrade with carborundum stone. Rinse and allow to dry. When sanding we recommend the use of an approved respirator.

APPLICATION**INSTALLATION TO CONFORM TO ANSI A108.4.**

Using flat side of trowel, apply skim coat of adhesive with appropriate size trowel. Apply additional adhesive with notch side of trowel held at a 45° angle to the surface, combing in one direction. Press tile firmly into place in a perpendicular motion across ridges, moving back and forth about 1/8" - 1/4" (3 - 6 mm). Perpendicular pressing flattens ridges and closes valleys allowing maximum coverage. With some tile, back buttering is advisable. Adjust tile promptly and beat in with block and rubber mallet. Periodically pull up a tile and check the back to ensure complete coverage with the adhesive. Do not apply more adhesive than can be covered with tile in 30 minutes. If adhesive starts to skin over (not sticky), re-trowel before setting tile.

DRYING TIME

Allow a minimum of 24 hours drying time before applying grout. Cure time can be greatly extended when setting dense tile, tile larger than 6" x 6" (15 x 15 cm), bonding tile to dense surfaces, in high humidity or when temperature is below 60° F (16° C).

COVERAGE

Approximately 40 - 60 ft² per gallon (3.7 - 5.6 m²) using a 3/16" x 5/32" (5 x 4 mm) V-notch trowel.

RECOMMENDED TROWEL SIZE

3/16" x 5/32" (5 x 4 mm) V-notch for tile up to 6" x 6" (15.2 x 15.2 cm)

1/4" x 1/4" x 1/4" (6 x 6 x 6 mm) square-notch for tile over 6" x 6" (15 x 15 cm)

CLEAN-UP

Remove fresh adhesive from tile surfaces with a damp cloth. Clean tools in warm soapy water.

STORAGE

Although this product is freeze-thaw stable, it is best if stored indoors at moderate temperatures.

SAFETY

Contains petroleum distillates. If ingested, do not induce vomiting. Call a physician immediately. Use with adequate ventilation. Non-flammable.

ORDERING INFORMATION

ITEM CODE	SIZE	COLOR	PACKAGE
T1603	3-1/2 gal. (13.25 L)	White	Pail

TECHNICAL DATA

Meets ANSI A136.1 Type I specifications.

	T1-60™ CERAMIC TILE ADHESIVE
Applicable ANSI Standards	A136.1 Type I
Adjustment Time	40 min.
Open Time	50 min.
Shear Strength:	
Type I Water Immersion	50 psi
Freeze/Thaw	Stable
Stain Test	Passes
Impact Test	Passes
Heat Resistance	Passes

WARRANTY

Custom's Standard Warranty applies. For complete information call 800-272-8786 or visit www.custombuildingproducts.com.

