



**Low-VOC Product Portfolio
Adhesives/Sealants/Coatings**



Durabond® Hardwood Products	VOC Weight%	NAHB Model Green Home Guideline (based upon CARB VOC levels)	VOC g/L	USGBC LEED- NC/ LEED-H Standard (SCAQMD VOC levels)
Weight %			g/L	
Moisture Vapor Protection				
D-288™ Moisture Vapor Retarder	8.3	N/A	126	250
Hardwood Adhesives				
D-332™ Premium Wood Flooring Adhesive	5.8	15	86	100
D-321™ Moisture Cure Urethane Adhesive	5.4	15	86	100
D-317™ Engineered Wood Flooring Adhesive	8.0	15	88	100
Durabond® Ceramic Products	VOC Weight%	NAHB Model Green Home Guideline (based upon CARB VOC levels)	VOC g/L	USGBC LEED- NC/ LEED-H Standard (SCAQMD VOC levels)
Weight %			g/L	
Waterproofing & Antifracture Membrane				
D-222 DuraGuard™ Waterproofing Membrane	1.1	N/A	12.5	250
Grouts/Epoxies				
D-190 DuraPoxy™ Epoxy-Modified Grout and Mortar Admixture	0	N/A	0	65
EzPoxy™ 100% Solids Epoxy Grout & Mortar	0	N/A	0	65
Fortified Tile Grout Sanded	0	N/A	0	N/A
Fortified Tile Grout (Unsanded)	0	N/A	0	N/A
Liquid Admixtures				
D-L16™ High Strength Mortar and Grout Additive	0	N/A	0	65
Thin Set Mortars				
D-70™ ProFlex	0	N/A	0	N/A
D-65™ High Performance & Non Sag Mortar	0	N/A	0	N/A
D-60™ Medium Set	0	N/A	0	NA
D-55™ Fast Set	0	N/A	0	N/A
D-50™ Flexible	0	N/A	0	N/A
D-40™ DuraFlex	0	N/A	0	N/A
D-25™ DitraSet	0	N/A	0	N/A
D-20™ Porcelain Set	0	N/A	0	N/A
D-5™ Premium	0	N/A	0	N/A
D-2™ Floor Grade	0	N/A	0	N/A



Durabond® Floor Covering Products	VOC Weight%	NAHB Model Green Home Guideline (based upon CARB VOC levels)	VOC g/L	USGBC LEED- NC/ LEED-H Standard (SCAQMD VOC levels)
Weight %			g/L	
Moisture Vapor Barrier Coatings				
D-261™ Extreme Moisture Vapor Barrier Coating	4.0	N/A	59	250
D-250™ Moisture Vapor Barrier Coating	5.0	N/A	67	250
Specialty Adhesives				
D-1500™ Universal Adhesive	4.5	15	57	60
D-1400™ Epoxy Adhesive	0	15	0	50
Multipurpose Adhesive				
D-990™ Multipurpose Adhesive	0	15	0	50
D-920™ Multipurpose Adhesive	0	15	0	50
D-910™ Multipurpose Adhesive	0	15	0	50
D-905™ Multipurpose Adhesive	0	15	0	50
Carpet Adhesives				
D-870™ Carpet Tile & Pad Adhesive	0	15	0	50
D-860™ Double Stick Adhesive	0	15	0	50
D-850™ Carpet Adhesive	0	N/A	0	50
D-818™ Tack Strip & Multipurpose Adhesive	3.9	15	48	50
D-817™ Carpet Pad Adhesive	1.0	15	17	50
D-808™ Exterior Carpet Adhesive	0	15	0	50
D-807™ Sprayable Adhesive	0	15	0	50
Wall Surface				
D-745™ Fire Retardant Wall Adhesive	0.9	15	15	50
D-740™ Multipurpose Wall Adhesive	1.7	15	39	50
Hard Surface				
D-670™ Firm Set Goods and Carpet Adhesive	0	15	0	50
D-650™ Clear VCT Adhesive	0	15	0	50
D-640™ Pure Vinyl Adhesive	0	15	0	50
Primers				
Durabond Extreme Primer	<1	N/A	7.7	250
Durabond® Patches and Underlayments	VOC Weight %	NAHB Model Green Home Guideline (based upon CARB VOC levels)	VOC g/L	USGBC LEED- NC/ LEED-H Standard (SCAQMD VOC levels)
Weight %			g/L	
Self Leveling Underlayments				
83P™ Self Leveling Underlayment	0	N/A	0	N/A
Patches				
Webcrete® Ultra Finish	0	N/A	0	N/A
Webcrete® 95	0	N/A	0	N/A
Webcrete® 98	0	N/A	0	N/A
Webpatch 90	0	N/A	0	N/A
D-9001 Webpatch	0	N/A	0	N/A



Hydroment® Ceramic Products	VOC Weight%	NAHB Model Green Home Guideline (based upon CARB VOC levels)	VOC g/L	USGBC LEED- NC/ LEED-H Standard (SCAQMD VOC levels)
		Weight %	g/L	
Waterproofing & Antifracture Membranes				
Gold™ Waterproofing Membrane	1.1	N/A	12.5	250
UltraSet® Advanced Antifracture Waterproofing, Crack Isolation and Sound Reducing Membrane	5.0	N/A	67	250
Grouts/Epoxies				
1900™ Epoxy-Modified Grout and Mortar Admixture	0	N/A	0	65
EzPoxy™ 100% Solids Epoxy Grout & Mortar	0	N/A	0	65
Ceramic Tile Grout (Sanded)	0	N/A	0	N/A
Ceramic Tile Grout (Unsanded)	0	N/A	0	N/A
Liquid Admixtures				
425 High Strength Mortar and Grout Additive	0	N/A	0	65
447 Flex-A-Lastic Admixture	0	N/A	0	65
Thin Set Mortars				
ReFlex® ProFlex	0	N/A	0	N/A
StoneWall™ High Performance & Non Sag Mortar	0	N/A	0	N/A
Big Tile & Stone™	0	N/A	0	NA
Single Flex® FS	0	N/A	0	N/A
Single Flex®	0	N/A	0	N/A
Hydroment PM	0	N/A	0	N/A
Ditra-Set™	0	N/A	0	N/A
Porcelain-Mate™	0	N/A	0	N/A
Tile-Mate®	0	N/A	0	N/A
Tile-Mate® Floor & Wall	0	N/A	0	N/A
Bostik® Patches and Underlayments	VOC Weight %	NAHB Model Green Home Guideline (based upon CARB VOC levels)	VOC g/L	USGBC LEED- NC/ LEED-H Standard (SCAQMD VOC levels)
		Weight %	g/L	
Self Leveling Underlayments				
SL-150™ Self Leveling Underlayment	0	N/A	0	N/A
Patches				
Fast Patch 102	0	N/A	0	N/A



Bostik Hardwood Products	VOC Weight%	NAHB Model Green Home Guideline (based upon CARB VOC levels)	VOC g/L	USGBC LEED- NC/ LEED-H Standard (SCAQMD VOC levels)
		Weight %	g/L	
Moisture Vapor Protection				
MVP4™ Moisture Vapor Barrier Coating	8.3	N/A	126	250
EMC™ Epoxy Moisture Coating	5.0	N/A	67	250
Adhesives				
Bostik's Best	5.8	15	86	100
TKO™ (New & Improved)	0	15	0	100
BST™	4.6	15	72	100
EFA+ (Elastomeric Flooring Adhesive)	8.0	15	88	100
Chem-Calk®				
Chem-Calk® Products	VOC Weight%	NAHB Model Green Home Guideline (based upon CARB VOC levels)	VOC g/L	USGBC LEED- NC/ LEED-H Standard (SCAQMD VOC levels)
		Weight %	g/L	
Construction Adhesives & Sealants				
Chem-Calk® 900 Architectural Grade Urethane Sealant	3.9	4	48	250
Chem-Calk® 915 Construction Grade Urethane Sealant	3.9	4	53	250
Chem-Calk® 916 Textured Urethane Sealant	3.9	4	53	250
Chem-Calk® GPS1 General Purpose Urethane Sealant	2.4	4	51	250
Chem-Calk® 955-SL Self Leveling Sealant	3.9	4	51	250
Chem-Calk® 2020 Architectural Grade Hybrid Sealant	1.1	4	16	250
Chem-Calk® 2000 Construction Grade Hybrid Sealant	1.4	4	21	250
Chem-Calk® 300 General Purpose Butyl Sealant	17	4	240	250



Bostik HOME® PRODUCTS	VOC	NAHB Model Green Home Guideline (based upon CARB VOC levels)	VOC g/L	USGBC L.E.E.D H System (based upon SCAQMD VOC levels)
Weight %		g/L		
Construction Adhesives & Sealants				
Heavy Duty Construction Adhesive	6.9	15	105	70
Siding ULTRA and Window Sealant	3.9	4	53	250
Siding ULTRAclear Sealant	4.5	4	45	250
Window & Door Sealant	3.9	4	51	250
Roofing & Flashing sealant	3.9	4	21	250
Pour-a-Bull™ Self Leveling Sealant	1.4	4	21	250
Drywall Adhesive	1.7	15	39	50
Concrete & Masonry Sealant	3.9	4	53	250
Fiber Cement Board Sealant	3.9	4	54	250
Painters Caulk	2	15	33	250
Siliconize Acrylic Latex Sealant	2	15	32	250
Urethane Acrylic Latex Sealant	3.5	15	49	250



Bostik, Inc.
211 Boston Street
Middletown, MA 01949

Customer Service:
1-888-592-8558

Technical Service:
1-800-523-6530

Websites:
www.bostik-us.com
www.greenmission.bostik-us.com