

COVERAGE FOR 10.1 FL. OZ. CARTRIDGE (298 mL)

		Width							
		1/8"	1/4"	3/8"	1/2"	5/8"	3/4"	7/8"	1"
Depth	1/8"	99	49	33	24	20	16	14	12
	1/4"		24	20	12	10	8	7	6
	3/8"			11	8	6	5	5	4
	1/2"				6	5	4	3	3

LINEAR FEET PER 10.1 FL. OZ. CARTRIDGE

COVERAGE FOR 28 FL. OZ. CARTRIDGE (857 mL)

		Width							
		1/8"	1/4"	3/8"	1/2"	5/8"	3/4"	7/8"	1"
Depth	1/8"	288	145	95	71	58	48	40	36
	1/4"		71	58	36	29	23	20	17
	3/8"			32	23	17	16	13	11
	1/2"				17	14	11	10	8

LINEAR FEET PER 28 FL. OZ. CARTRIDGE

COVERAGE FOR 20 FL. OZ. SAUSAGE (600 mL)

		Width							
		1/8"	1/4"	3/8"	1/2"	5/8"	3/4"	7/8"	1"
Depth	1/8"	192	97	63	48	39	31	27	12
	1/4"		48	39	24	19	15	14	6
	3/8"			21	15	11	10	9	4
	1/2"				11	10	8	7	3

LINEAR FEET PER 20 FL. OZ. SAUSAGE

COVERAGE CHART FOR 1.5 GALLON PAIL (5.67 L)

		Width							
		1/8"	1/4"	3/8"	1/2"	5/8"	3/4"	7/8"	1"
Depth	1/8"	1848	924	615	462	369	308	264	231
	1/4"		412	308	231	185	153	132	116
	3/8"			204	153	123	102	87	77
	1/2"				116	92	77	66	57

LINEAR FEET PER 1.5 GALLON PAIL

COVERAGE CHART FOR 5 GALLON PAIL (18.9 L)

		Width							
		1/8"	1/4"	3/8"	1/2"	5/8"	3/4"	7/8"	1"
Depth	1/8"	6153	3077	2048	1538	1228	1025	879	769
	1/4"		1372	1026	779	616	510	440	386
	3/8"			679	510	410	340	290	256
	1/2"				386	306	256	220	190

LINEAR FEET PER 5 GALLON PAIL

PRIMER COVERAGE RECOMMENDATIONS

For one quart of primer, coverage is as follows:

1 unit	5 gallon pail
5 units	1.5 gallon unit
7 gallons	1 gallon unit

NOTE: All values are approximations and can vary due to joint dimension variations, porosity, and texture of substrates. Yield per cartridge is approximate due to variables beyond Bostik's control such as irregular joint configuration and installation technique.

**TABLE 3: CHEM-CALK® 915
ASTM C-794 ADHESION-IN-PEEL
TO COMMON CONSTRUCTION SURFACES***

Surface	Failure Type – %
Mill Finished Aluminum**	Adhesive – 100
Anodized Aluminum	Cohesive – 100
Steel**	Adhesive – 100
Galvanized Steel	Cohesive – 100
Stainless Steel**	Adhesive – 100
Fiberglass	Cohesive – 100
ABS**	Adhesive – 100
Rigid PVC**	Adhesive – 100
Plywood***	Cohesive – 100
Concrete***	Cohesive – 100
Brick	Cohesive – 100
Granite	Cohesive – 100
Marble**	Adhesive – 100
Limestone***	Cohesive – 100

* Values given above are not intended to be used in specification preparation.

** With primer, value is >25, Cohesive – 100.

***Peel values are reduced when unprimed samples are water-immersed.