



OUR ALUMINUM HINGE ROLL-UP MATS HAVE ALL ALUMINUM RAILS. UNLIKE MATS WITH HIDDEN VINYL UNDER-CHANNELS OR VINYL RAILS, ALUMINUM RAIL MATS ARE SUITABLE FOR COMMERCIAL APPLICATIONS. THEY MAINTAIN THEIR INTEGRITY IN ALL WEATHER SO THE TREADS STAY IN THE RAILS

DETAIL NOTES:

- 1-TREAD RAILS MUST RUN PERPENDICULAR TO TRAFFIC DIRECTION.
- 2-MAT DIMENSIONS ALLOW FOR CLEARANCE BETWEEN MAT SECTIONS AND FRAME IN THE WIDTH DIMENSION ONLY.
- 3-TRIM THE FILLER TO ENSURE A TIGHT FIT IN THE TRAFFIC DIMENSION

SPECIFICATIONS:

MATDESIGN MODEL M-600RS HAS OUR 600 DENIER TUFTED POLYPROPYLENE RUGGED SCRUB TREADS HAVE PRIMARY AND SECONDARY BACKING. RAILS ARE MADE WITH 6063-T52 ALLOY RAILS AND ARE $\frac{3}{8}$ " (9.5MM) DEEP AND SPACED 2" (50.8MM) ON CENTER. FRAMES USED WITH THE M-600RS ARE: TYPE F-3 RECESSED; TYPE F-4 SURFACE MOUNT; TYPE F-6 THIN LINE; F-6R THIN LINE CAST IN PLACE FRAMES WHICH ARE MADE OF ALUMINUM. IN ADDITION OUR F-5 SURFACE FRAME IS AVAILABLE IN VINYL.

	<p>Arden Architectural Specialties, Inc. 9300 73rd Avenue North Brooklyn Park, MN 55428</p>	
		<p>JOB REF.</p>
<p>MODEL NO. M-600RS</p>		
<p>RELEASED DATE</p>	<p>1/5/2011</p>	<p>SHEET 1 OF 1</p>