

SPECIFICATIONS:

- (1) DOOR: STEEL, 3/16" DIAMOND PLATE, GRAY PRIMER COAT WITH A H20 LOAD RATING FOR INFREQUENT LOW SPEED TRAFFIC WITH A MAXIMUM DEFLECTION OF L/160
- 2 FRAME: STEEL, 3/16" ANGLE, GRAY PRIMER COAT
- (3) HINGES: TYPE 316 STAINLESS STEEL
- 4 SLAM LATCH: TYPE 316 STAINLESS STEEL WITH INSIDE LEVER HANDLE AND OUTSIDE REMOVABLE 5/16" SQUARE L HANDLE
- (5) COUNTER-BALANCE SPRING: TYPE 17-7 STAINLESS STEEL SPRING ENCLOSED IN A TYPE 316 STAINLESS STEEL TELESCOPING TUBE
- (6) HOLD-OPEN ARM: TYPE 316 STAINLESS STEEL
- (7) **ANCHOR:** 4" CONCRETE ANCHOR STRAPS PROVIDED

8 FLUSH LIFTING HANDLE: TYPE 316 STAINLESS STEEL

FLOOR DOOR SIZE:

" (WIDTH) x " (LENGTH)

CLEAR UNOBSTRUCTED OPENING:

" (WIDTH) x " (LENGTH)

OPENING:

" (WIDTH) x " (LENGTH)

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK DAVIS IS PROHIBITED. THIS IS A GENERIC SHOP DRAWING AND MAY NOT BE AN ACTUAL REPRESENTATION OF THE FINAL PRODUCT.

PROJECT:								
ARCHITECT:								
CONTRACTOR:								
QTY:								
PART#:				BFDEHI	> х	(DAL	
ь				TITLE: Floor Door, Non-Drainable,				
Babcock-Davis				Dbl Dr, 316 SST Hdw,				
9300 73rd Avenue North Brooklyn Park, MN 55428				Steel, Prime Coat, H20, Cast-In Anchors, Slam Latch Removbl L Hdl				
	NAME	DATE	SIZE	DWG. NO.				REV
DRAWN	JE	04/18/11	Α		BFDEH	P_X_D	AL	A

SHEET 1 OF 2

WEIGHT: Varies

2

1

RELEASED DWO 04/18/11

