

SPECIFICATIONS:

(1) DOOR: ALUMINUM, 1/4" SMOOTH PLATE, RECESSED, MILL FINISH WITH A (8) TILE EXTRUSION: ALUMINUM, RECESSED FOR 1/8" LIVE LOAD OF 300 PSF WITH A MAXIMUM DEFLECTION OF L/160

FLOOR COVERING

 $\langle 2 \rangle$ **FRAME:** ALUMINUM, 1/4" EXTRUSION, RECESSED, EPOXY PAINT FINISH ON EXTERIOR SURFACES THAT COME IN CONTACT WITH CONCRETE

(3) HINGES: TYPE 316 STAINLESS STEEL

4 SLAM LATCH: TYPE 316 STAINLESS STEEL WITH INSIDE LEVER HANDLE AND OUTSIDE REMOVABLE 5/16" SQUARE L HANDLE

(5) COUNTER-BALANCE SPRING: TYPE 17-7 STAINLESS STEEL SPRING ENCLOSED IN A TYPE 316 STAINLESS STEEL TELESCOPING TUBE

(6) HOLD-OPEN ARM: TYPE 316 STAINLESS STEEL WITH RED VINYL GRIP **HANDLE**

(7) ANCHOR: 4" CONCRETE ANCHOR STRAPS PROVIDED

FLOOR DOOR SIZE:

" (LENGTH) " (WIDTH) x

CLEAR UNOBSTRUCTED OPENING:

" (WIDTH) x " (LENGTH)

OPENING:

" (WIDTH) x " (LENGTH)

9300 73rd Avenue North Brooklyn Park, MN 55428 DRAWN RELEASED DWO 04/18/11

PROJECT:

ARCHITECT

CONTRACTOR:

QTY:

PART#:

b

Babcock-Davis

BFDRPA DAL Х TITLE: Floor Door, Recessed Series, Dbl Dr, 316 SST Hdw, Alum, Mill, Pedestrian, Cast-In Anchors, Slam Latch Removbl L Hdl

DATE SIZE DWG. NO. REV NAME BFDRPA X DAL Α Α 04/18/11 SHEET 1 OF 2 WEIGHT: Varies

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK DAVIS IS PROHIBITED. THIS IS A GENERIC SHOP DRAWING AND MAY NOT BE AN ACTUAL REPRESENTATION OF THE FINAL PRODUCT.

