

SINGLE COVER SPECIFICATIONS

COVER: .090 ALUMINUM (11 GA)
 COVER IS STIFFENED TO WITHSTAND A LIVE LOAD OF 40 PSF WITH A MAX DEFLECTION OF 1/150 OF THE SPAN. COVER WITHSTANDS A MAX. WIND UPLIFT OF 20 PSF. MAX DEGREE OF OPENING IS 78°
LINER: .040 ALUMINUM
CURB: .090 ALUMINUM

- **COUNTERFLASH:** .090 ALUMINUM WITH EZ TAB FLASHING SYSTEM
- **FINISH:** MILL FINISH
- **HARDWARE:** ZINC PLATED STEEL
- **HINGE:** ZINC PLATED STEEL TAMPER PROOF HINGE ASSEMBLED ON THE INSIDE OF HATCH AS PART OF SPRING ASSEMBLY.
- **LATCH:** ZINC PLATED STEEL 2-POINT LATCH WITH TURN HANDLE

- **SPRING:** STEEL GREASED COMPRESSION SPRING ENCLOSED IN TELESCOPIC TUBES WHICH COUNTER BALANCE THE DOOR
- **MOUNTING FLANGE:** 3.50"
- **INSULATION:** 1" THICK INSULATION IN COVER AND 1" ON CURB PERIMETER

OPTIONS

- OSS - STAINLESS STEEL HARDWARE

CURB OPTIONS

- 1 - SINGLE WALL CURB (AS SHOWN)
- 2 - DOUBLE WALL CURB
- 3 - CURB MOUNT FLANGE
- 4 - DOUBLE WALL NO COUNTERFLASH
- 5 - APRON MOUNT

THIS PRODUCT MAY BE INSTALLED ON EITHER A FLAT OR SLOPING ROOF, WHEN INSTALLED ON A SLOPE, THE HINGE SIDE MUST RUN PARALLEL WITH THE SLOPE. IF THE SLOPE EXCEEDS A 3:12 PITCH, ADVISE FACTORY FOR MODIFICATION.

SIZE

WIDTH: LENGTH:

*HINGE ON LENGTH SIDE
 WIDTH AND LENGTH DIMENSIONS ARE FROM THE INSIDE FACES OF CURB

