



- ① COVER - 3/16 STEEL COVER STIFFENED TO WITHSTAND A LIVE LOAD OF 40 PSF WITH A MAX DEFLECTION OF 1/150 OF THE SPAN. COVER WITHSTANDS A MAX WIND UPLIFT OF 20 PSF.
- ② LINER - 22 GAUGE GALVANIZED STEEL
- ③ CURB - 3/16 STEEL (14 GAUGE GALVANIZED COUNTER FLASH
4. HARDWARE - ZINC PLATED STEEL
- ⑤ LATCH - SINGLE POINT LATCH WITH PROVISION FOR PADLOCK SECURITY

- ⑥ INSULATION - 1" THICK IN COVER AND 1" THICK ON CURB PERIMETER
- ⑦ MOUNTING FLANGE - 3.50 INCHES
- ⑧ HINGE - ZINC PLATED STEEL TAMPER PROOF HINGE CONTAINED WITHIN HATCH AS PART OF SPRING ASSEMBLY
9. SPRING - GREASED HEAVY DUTY COMPRESSION SPRING.
10. FINISH - RED OXIDE POWDER COAT
11. CURB OPENING - 48 X 48 INCHES MEASURE INSIDE CURB TO INSIDE CURB

# BRHSG48X48S1T



TITLE:			Roof Hatch, Security Series, 48x48, Sngl Dr, Galvn Steel, Red Oxide Pwd, Sngl Wall Curb,		
SIZE	DWG. NO.			REV	
B	BRHSG48X48S1T			A	
WEIGHT: 187.10			SHEET 21 OF 22		

