







SECTION A-A

SPECIFICATIONS:

В

- (1) COVER: 14 GAUGE GALVANNEAL COVER STIFFENED TO WITHSTAND A LIVE LOAD OF 40 PSF WITH A MAX DEFLECTION OF 1/150 OF THE SPAN
- (2) LINER: 22 GAUGE GALVANNEALL
- (3) CURB AND COUNTERFLASH W/ EZ TAB: 14 GAUGE GALVANNEAL
- 4 FINISH: COVER- POWDER COAT PAINT, HIGH GLOSS WHITE CURB- POWEDER COAT PAINT, HIGH GLOSS WHITE
- (5) GAS SPRING WITH DAMPER: DESIGNED TO OPEN AGAINST A 10PSF SNOW LOAD IN NOT LESS THAN 2 SECONDS
- (6) HOLD OPEN ARM: LOCK COVER IN FULLY OPEN POSITION ZINC PLATED STEEL
- (7) LATCH: ZINC PLATED ROTARY LATCH ASSEMBLY DESIGNED TO HOLD COVERS CLOSED AGAINST 90 PSF WIND UPLIFT ZINC PLATED STEEL LATCH STRIKERS ON COVERS

- (8) HINGES: ZINC PLATED STEEL WITH STAINLESS STEEL HINGE PINS
- (9) INSULATION: 1" POLYISOCYANURATE IN COVER AND AROUND CURB PERIMETER, R-VALUE 6
- (10) GASKET: ADHESIVE BACKED EPDM RUBBER EXTRUSION
- THERMAL RELEASE MECHANISM: VENT COVERS OPEN THERMALLY BY HEAT AT FUSIBLE LINK TEMPERATURE °F
- (12) MANUAL OPENING: VENT COVERS OPEN WITH INTERNAL AND EXTERNAL MANUAL PULL HANDLE, 1/16" DIA SST CABLE

SMOKE VENT SIZE (WIDTH) X (LENGTH)

EFFECTIVE VENTING AREA 90% SQFT

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.



				02700				
PROJECT:								
ARCHITECT:								
CONTRACTOR:								
QTY:								
PART#:				BSVSW	Х	D11	N	R
Babcock-Davis 9300 73rd Avenue North Brooklyn Park, MN 55428				TITLE: Smoke Vent, SafeMAX Series Galvanneal, Dbl Dr, Single Wall Curb Non-Electrical				
	NAME	DATE	SIZE	DWG. NO.				REV
DRAWN	-	05/04/11	Α		BSVSW_X_D	1N _R		-
RELEASED	DS	05/04/11	WE	IGHT: VARIE	S		SHEET 1	OF 2

2

1



