



MODEL A3E

(SINGLE STAGE RIBBED ABRASIVE BARS)

SPECIFICATIONS:

- ① **BASE:** HEAT TREATED EXTRUDED ALUMINUM ALLOY 6063 T-5
- ② **ABRASIVE:** ALUMINUM OXIDE SILICON CARBIDE GRANULES IN A UV PROTECTED, 2 PART EPOXY, LOCKED INTO EXTRUDED CHANNELS
- 3. **BASE FINISH:** MILL
- 4. **POURED CONCRETE STAIRS:** NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. **CONCRETE FILLED STEEL PAN STAIRS:** NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE

- 6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE, BUFF
- 7. **LENGTH:** 120" MAXIMUM

LENGTH	QTY	COLOR

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.

PROJECT:			
ARCHITECT:			
CONTRACTOR:			
QTY:			
PART#:		BSTSB-A3E	
9300 73rd Avenue North Brooklyn Park, MN 55428		TITLE: V851, Stair Tread, Bar Ribbed Abrasive, Long Nose Angled, Alum Extruded Anchor,	
NAME	DATE	SIZE	DWG. NO.
DRAWN: BMH	3/11/11	A	BSTSB-A3E
RELEASED: PE	3/11/11	WEIGHT: 1.33 LB	SHEET 1 OF 1