



SPECIFICATIONS:

В

- 1 BASE: 319 CAST ALUMINUM
- (2) ABRASIVE: SILICON CARBIDE ABRASIVE, CROSSHATCH PATTERN 1/8" DEEP
- 3. FINISH: SAND CAST
- 4. POURED CONCRETE STAIRS: NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. LENGTH: 6" MINIMUM 6'-0" MAXIMUM

LENGTH ± 1/8	QTY

I	PROJEC	CT:				
ARCHITECT:						
CONTRACTOR:						
	QTY:					
PART#:				BSTCA-C3C		
	9			TITLE:	Stair Tread, Cast Series	
Babcock-Davis•				3	", Cast Aluminum Crosshatch	
9300 73rd Avenue North Brooklyn Park, MN 55428				Shor	Nosing for Concrete, Bolt Anchor	
	NAME	DATE	SIZE	DWG. NO		REV
DRAWN	SJB	3/31/11	Α		BSTCA-C3C	A

WEIGHT: 1.20 LB/FT

SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.

2

1

RELEASED DWO 3/31/11