



SPECIFICATIONS:

- ① **BASE:** 319 CAST ALUMINUM
- ② **ABRASIVE:** SILICON CARBIDE ABRASIVE ,CROSSHATCH PATTERN 1/32" THICK
- 3. **FINISH:** SAND CAST
- 4. **POURED CONCRETE STAIRS:** NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. **LENGTH:** 5'6" MAXIMUM
- 6. **WING ANCHORS:** STANDARD FOR POURED CONCRETE APPLICATIONS

LENGTH	QTY

PROJECT:					
ARCHITECT:					
CONTRACTOR:					
QTY:					
PART#:		BSTCA-P3W			
Babcock-Davis Always right there. 9300 73rd Avenue North Brooklyn Park, MN 55428		TITLE:			
		Stair Tread, Cast Series 3", Cast Aluminum Crosshatch Short Tip Nosing for Concrete, Wing Anchor			
	NAME	DATE	SIZE	DWG. NO.	REV
DRAWN	SJB	3/31/11	A	BSTCA-P3W	A
RELEASED	PE	3/31/11	WEIGHT: 1.20 LB/FT		SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.