

NOTES:

- 1. **PROFILE**: HIGH IMPACT VINYL ACRYLIC EXTRUSION LOCKED IN PLACE, NOMINAL 0.078" (1.98mm) THICK
- 2. CLASS A FIRE RATING, TESTED TO ASTM E84
- 3. RETAINER: CONTINUOUS 6063 T-5 ALUMINUM, NOMINAL 0.060" (1.52mm) THICK
- 4. **EXTRUSION**: PEBBLE GRAIN FINISH WHICH CONTAINS EPA REGISTERED MICRO-CHEK ANTIMICROBIAL AGENT
- 5. MAXIMUM LENGTH: VINYL CORNER GUARDS 20'
- 6. **HARDWARE**: #6 X 1-5/8" DRYWALL SCREWS INCLUDED
- 7. 6063-T5 ALUMINUM COVE BASE INCLUDED, 4" STANDARD HEIGHT
- 8. PARTITION COMPONENTS PROVIDED BY OTHERS. FINISHED LENGTH INCLUDES COVE BASE.

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.

PROJECT:						
ARCHITECT:						
CONTRACTOR:						
Babcock-Davis Babcock-Davis 9300 73rd Avenue North Brooklyn Park, MN 55428				TITLE: 3" CORNER GUARD RECESS MOUNT 135 DEGREE		
	NAME	DATE	SIZE	DWG. NO.		REV
DRAWN	MDS	24APR13	Α		BCGVR3S-D135	A
RELEASED	PGE	01MAY13	WE	IGHT: 1.29 lb	s/ft	SHEET 1 OF 1

2