



SPECIFICATIONS:

- (1) **DOOR:** 316 SST, 3/16" DIAMOND PLATE, MILL FINISH WITH A LIVE LOAD OF 300 PSF WITH A MAXIMUM DEFLECTION OF L/160
- 2 FRAME: 316 SST, 3/16" FORMED, MILL FINISH
- (3) HINGES: TYPE 316 STAINLESS STEEL
- 4 SLAM LATCH: TYPE 316 STAINLESS STEEL WITH INSIDE LEVER HANDLE AND OUTSIDE REMOVABLE 5/16" SQUARE L HANDLE
- (5) COUNTER-BALANCE SPRING: TYPE 17-7 STAINLESS STEEL SPRING ENCLOSED IN A TYPE 316 STAINLESS STEEL TELESCOPING TUBE
- (6) HOLD-OPEN ARM: TYPE 316 STAINLESS STEEL WITH RED VINYL GRIP HANDLE
- (7) ANCHOR: 4" CONCRETE ANCHOR STRAPS PROVIDED

- (8) FLUSH LIFTING HANDLE: TYPE 316 STAINLESS STEEL
- (9) **DRAINAGE COUPLING:** 1-1/2", FOR CONNECTION TO RUN
- 10) FLUSH TYPE PLUG SEAL: TYPE 316 STAINLESS STEEL

FLOOR DOOR SIZE:

" (WIDTH) x " (LENGTH)

CLEAR UNOBSTRUCTED OPENING:

" (WIDTH) x " (LENGTH)

OPENING:

" (WIDTH) x " (LENGTH)

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED. THIS IS A GENERIC SHOP DRAWING AND MAY NOT BE AN ACTUAL REPRESENTATION OF THE FINAL PRODUCT.

PROJECT:								
ARCHITECT:								
CONTRACTOR:								
QTY:								
PART#:				BFDDP	V	X	SAL	
_ b				TITLE: Floor Door, Drainable Series,				
Babcock-Davis•				Sngl Dr, 316 SST Hdw,				
9300 73rd Avenue North Brooklyn Park, MN 55428				SST 316, Mill, Pedestrian, Cast-In Anchors, Slam Latch Removbl L Hdl				
	NAME	DATE	SIZE	DWG. NO.				REV
DRAWN	JPB	7-11-13	Α		BFDD	PV_X_	SAL	A

SHEET 1 OF 2

WEIGHT: Varies

TR 7-11-13

RELEASED

