







SPECIFICATIONS:

В

- (1) COVER: 1/4" ALUMINUM COVER STIFFENED TO WITHSTAND A LIVE LOAD OF 40PSF WITH A MAX DEFLECTION OF 1/150 OF THE SPAN
- (2) LINER: 18 GA ALUM
- (3) CURB AND COUNTERFLASH W/ EZ TAB: 1/4" ALUM
- 4 FINISH: MILL FINISH
- $\langle 5 \rangle$ **Spring/Hinge Assembly**: ZINC PLATED STEEL TAMPER-PROOF HINGE CONTAINED WITHIN SPRING/HINGE ASSEMBLY, TELESCOPIC TUBES CONTAIN COIL STEEL COMPRESSION SPRINGS FOR LIFT **ASSISTANCE**
- 6 HOLD OPEN ARM: LOCKS COVER IN FULLY OPEN POSITION -ZINC PLATED STEEL WITH RED VINYL GRIP HANDLE PULL RELEASE
- $\langle 7 \rangle$ LATCH: SINGLE POINT LATCH SLAM LATCH HOLDS COVER CLOSED AGAINST 20 PSF WIND UPLIFT. INTERNAL AND EXTERNAL TURN HANDLES WITH PADLOCK HASPS

- INSULATION:
- 1" POLYSTYRENE (R4) IN COVER, AND 1" FIBERBOARD (R2.8) IN CURB
- (9) GASKET: ADHESIVE BACKED EPDM RUBBER EXTRUSION
- **SIZING: WIDTH X LENGTH DIMENSIONS ARE MEASURED INSIDE** 10 CURB TO INSIDE CURB WHERE THE WIDTH IS HINGE TO LATCH AND LENGTH IS HINGED SIDE WITH SPRINGS

ROOF HATCH SIZE " (WIDTH) x " (LENGTH) **CLEAR OPENING** " (WIDTH) x " (LENGTH) **ROUGH OPENING** " (WIDTH) x " (LENGTH)

PROJECT:						
ARCHITECT:						
CONTRACTOR:						
QTY:						
PART#:						
Babcock-Davis 9300 73rd Avenue North Brooklyn Park, MN 55428				TITLE: Roof Hatch, Security Series, Sngl Dr, Zinc Hdw, Alum, Mill, Sngl Wall Curb,		
	NAME	DATE	SIZE	DWG. NO.		REV
DRAWN	ELW	10/16/12	Α			Α
RELEASED	-	-	WEIGHT: VARIES SHE			OF 2

2

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROPRIETED.

В

