

MODEL L4.125E


(SINGLE STAGE FULL ABRASIVE)

SPECIFICATIONS:

- ① **BASE:** HEAT TREATED EXTRUDED ALUMINUM
ALLOY 6063 T-5
- ② **ABRASIVE:** ALUMINUM OXIDE SILICON CARBIDE
GRANULES IN A UV PROTECTED, 2 PART EPOXY,
LOCKED INTO EXTRUDED CHANNELS
3. **BASE FINISH:** MILL
4. **POURED CONCRETE STAIRS:** NOSING SHALL
TERMINATE NO MORE THEN 3" FROM END OF
STEPS
5. **CONCRETE FILLED STEEL PAN STAIRS:** NOSING
SHALL BE FULL LENGTH OF STEPS, LESS 1/8"
CLEARANCE

6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW,
GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE, BUFF,
LUMINESCENT
7. **LENGTH:** 12'0" MAXIMUM (STANDARD)
8. UL 1994 LISTED: COMBINED WIDTH OF PHOTO-
LUMINESCENT MATERIAL SHALL NOT BE LESS
THAN 1"

LENGTH	QTY	COLOR

PROJECT:				
ARCHITECT:				
CONTRACTOR:				
QTY:				
PART#:		BSTSF-L4.125E		
 Babcock-Davis <small>Always right there.</small> 9300 73rd Avenue North Brooklyn Park, MN 55428		TITLE:		
		VFAL41, Stair Tread, Full Abrasive, Long Nose, Alum Extruded Anchor,		
NAME	DATE	SIZE	DWG. NO.	REV
DRAWN	BMH	3/14/11	A	BSTSF-L4.125E
RELEASED	PE	3/14/11	WEIGHT: 1.65 LB	SHEET 1 OF 1