

NOTES:

В

- 1. PROFILE: HIGH IMPACT VINYL ACRYLIC EXTRUSION LOCKED IN PLACE, NOMINAL 0.078" (1.98mm) THICK,
- 2. CLASS A FIRE RATING, TESTED TO ASTM E84
- 3. RETAINER: CONTINUOUS 6063 T-5 ALUMINUM RETAINER, NOMINAL 0.060" (1.52mm) THICK
- 4. EXTRUSION: PEBBLE GRAIN FINISH WHICH CONTAINS EPA REGISTERED MICRO-CHEK ANTIMICROBIAL AGENT
- 5. VINYL CRASH RAIL LENGTH: PROVIDED IN 20' CONTINUOUS SECTIONS
- END CAP: #BCRVE5C-ECT, OUTSIDE CORNER: #BCRVE5C-OCT, 135 DEG OUTSIDE CORNER: #BCRVE5C-135OC SPLICE KIT: #BCRVE5C-SK
- 7. FASTENERS AND PARTITION COMPONENTS PROVIDED BY OTHERS.

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.

т	PROJECT:							
'	ARCHITECT:							
	CONTRACTOR:							
.	Babcock-Davis Babcock-Davis 9300 73rd Avenue North Brooklyn Park, MN 55428			TITLE: 5" VINYL CRASH RAIL CRESCENT SHAPE, EXTENDED MOUNT 1-1/2" BRACKET, CONTINUOUS RETAINER				
Ο,								
		NAME		SIZE	DWG. NO.			REV
	DRAWN MDS 04JUN13 A		BCRVE5C-B15			Α		
	RELEASED	PGE	04JUN13	WE	GHT: 0.90 II	os/ft	SHEET 1	OF 1

QUANTITY

COLOR

В

2