

COLOR

QUANTITY

NOTES:

В

- 1. PROFILE: HIGH IMPACT VINYL ACRYLIC EXTRUSION LOCKED IN PLACE, NOMINAL 0.078" (1.98mm) THICK
- 2. CLASS A FIRE RATING, TESTED TO ASTM E84
- 3. RETAINER: CONTINUOUS 6063 T-5 ALUMINUM RETAINER, NOMINAL 0.062" (1.57mm) THICK
- 4. **EXTRUSION**: PEBBLE GRAIN FINISH WHICH CONTAINS EPA REGISTERED MICRO-CHEK ANTIMICROBIAL AGENT
- 5. VINYL CRASH RAIL LENGTH: PROVIDED IN 20' CONTINUOUS SECTIONS
- 6. END CAP: #BCRVS6C-EC, OUTSIDE CORNER: #BCRVS6C-OC, 135 DEG OUTSIDE CORNER: #BCRVS6C-OC135, SPLICE KIT: #BCRVS6C-SK
- FASTENERS AND PARTITION COMPONENTS PROVIDED BY OTHERS.

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.

	PROJECT:						
ARCHITECT:							
CONTRACTOR:							
Babcock-Davis 9300 73rd Avenue North Brooklyn Park, MN 55428					TITLE: 6" VINYL CRASH RAIL SURFACE MOUNT CONTINUOUS RETAINER		
		NAME	DATE	SIZE	DWG. NO.		REV
DR	RAWN	MDS	24APR13	Α		BCRVS6C	A
RE	LEASED	PGE	01MAY13	WE	IGHT: 1.13 lbs/ft		SHEET 1 OF 1