0.078" [1.98mm] GUARD 25.4mm HIGH IMPACT RAIL COVER 2" [50.8mm] X 1/2" [12.7mm] MOUNTING CUSHION \diagdown CONTINUOUS VINYL CUSHION 6" [152.4mm] CONTINUOUS VINYL CUSHION

NOTES:

В

- PROFILE: HIGH IMPACT VINYL ACRYLIC EXTRUSION LOCKED IN PLACE, NOMINAL 0.078" (1.98mm) THICK
- 2. CLASS A FIRE RATING, TESTED TO ASTM E84
- 3. RETAINER: CONTINUOUS 6063 T-5 ALUMINUM RETAINER, NOMINAL 0.062" (1.57mm) THICK
- EXTRUSION: PEBBLE GRAIN FINISH WHICH CONTAINS EPA REGISTERED MICRO-CHEK ANTIMICROBIAL 4. **AGENT**
- 5. VINYL CRASH RAIL LENGTH: PROVIDED IN 20' CONTINUOUS SECTIONS
- END CAP: #BCRVS6C-EC, OUTSIDE CORNER: #BCRVS6C-OC, 135 DEG OUTSIDE CORNER: #BCRVS6C-OC135, 6. SPLICE KIT: #BCRVS6C-SK
- 7. FASTENERS AND PARTITION COMPONENTS PROVIDED BY OTHERS.

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.

PROJECT: ARCHITECT: CONTRACTOR: TITLE: 6" VINYL CRASH RAIL Babcock-Davis

9300 73rd Avenue North
Brooklyn Park, MN 55428 SURFACE MOUNT 1/2" CUSHION, CONTINUOUS RETAINER NAME DATE SIZE DWG. NO. REV BCRVS6C-C05 Α DRAWN MDS 24APR13 A RELEASED PGE 01MAY13 WEIGHT: 1.16 lbs/ft SHEET 1 OF 1

QUANTITY

COLOR

0.062" [1.57mm] CONTINUOUS ALUMINUM RETAINER