

NOTES:

В

- PROFILE: HIGH IMPACT VINYL ACRYLIC EXTRUSION LOCKED IN PLACE, NOMINAL 0.078" (1.98mm) THICK
- 2. CLASS A FIRE RATING, TESTED TO ASTM E84
- 3. RETAINER: 6063 T-5 ALUMINUM RETAINER CLIP, NOMINAL 0.060" (1.52mm) THICK X 2" WIDE
- 4. EXTRUSION: PEBBLE GRAIN FINISH WHICH CONTAINS EPA REGISTERED MICRO-CHEK ANTIMICROBIAL AGENT
- 5. VINYL CRASH RAIL LENGTH: PROVIDED IN 20' CONTINUOUS SECTIONS
- END CAP: #BCRVS7C-ECT, OUTSIDE CORNER: #BCRVS7C-OCT, 135 DEG OUTSIDE CORNER: #BCRVS7C-OC135, SPLICE KIT: #BCRVS7E-SK
- 7. FASTENERS AND PARTITION COMPONENTS PROVIDED BY OTHERS.

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.

			\T.					
	PROJECT:							
т	ARCHITECT:							
•	CONTRACTOR:							
	ь			TITLE: 7" VINYL CRASH RAIL				
5,	Babcock-Davis* 9300 73rd Avenue North Brooklyn Park, MN 55428				CRESCENT SHAPE, SURFACE MOUNT ECONOMY 2" MOUNTING CLIP			
		NAME	DATE	SIZE	DWG. NO.			REV
	DRAWN	/N MDS 04JUN13 A		Α	BCRVS7E			Α
	RELEASED	SED PGE 04JUN13 WE			IGHT: 1.37 lbs/ft		SHEET 1	OF 1