
## **Round Columns**

## **Dimensions & Load Data**



	Actual Diameter		Nominal Diameter		Flutes from Bottom (Fluted column only)	Number of Flutes (Fluted column only)	Standard Cap  Column Extends Through Cap		lonic Cap  Load Bearing Cap		Scamozzi Cap  Load Bearing Cap		Temple Cap  Load Bearing Cap		Corinthian Cap  Load Bearing Cap		Standard Base  Column Extends Through Base		Attic Base  Column Extends Through Base				
																					Standard Lengths (in feet)		Load Lbs .
Round Smooth	Round Fluted	Outside Base	Outside Neck	(approx)			Width	Height	Width	Height	Width	Height	Width	Height	Width	Height	Width	Height	Width	Height	Round Smooth	Round Fluted	
		A	В	C	D		E	F	E	F	E	F	Е	F	E	F	G	Н	G	Н	J	K	
6"	6"	5-5/8"	5"	1/3 of length	9-7/16"	16	7-1/2"	1-5/8"	7-1/2"	3-1/4"	8-1/2"	3-3/4"	8-3/4"	7-3/4"	9-3/4"	8"	8-1/2"	3-3/16"	8"	3-7/16"	8'	8'	8,000
8"	8"	7-5/8"	6-1/2"	1/3 of length	10-5/8"	24	9-1/2"	2-1/2"	8-1/2"	4"	10-1/2"	4-1/4"	10-1/4"	8-1/4"	12-3/4"	9-1/4"	10-1/4"	4-3/8"	10-1/4"	4-1/2"	5'6", 8', 9', 10'	8', 9', 10,	10,000
10"	10"	9-5/8"	8-1/4"	1/3 of length	12-3/4"	24	11-15/16"	3-1/8"	11"	5-1/4"	14-1/2"	5-1/4"	13-3/4"	11"	15-1/2"	12-1/4"	12-3/4"	5-1/2"	12-3/4"	5-7/8"	8', 9',10',12'	8'9'10'12'	14,000
12"	12"	11-5/8"	9-11/16"	1/3 of length	14-1/8"	24	14-3/8"	3-5/8"	12-3/4"	5-3/4"	17-1/2"	6-1/4"	15-3/4"	11-3/4"	18-1/4"	14-3/4"	15-1/8"	6-1/8"	15-5/16"	6-13/16"	8', 9',10',12' 14', 16'	8'9'10'12'	18,000
14"	14"	13-5/8"	11-3/8"	1/3 of length	18-1/4"	24	16-3/8"	4-1/16"	16-1/2"	5"	18-3/4"	5-5/8"	21-1/2"	14"	19-3/4"	15-1/8"	18-5/8"	7-1/2"	18-5/8"	9-1/16"	8', 9',10',12' 14', 16'	8'9'10'12'	20,000
16"	16"	15-5/8"	13"	1/3 of length	N/A	N/A	18-1/2"	4-1/2"	17-1/4"	6-3/8"	22"	7-1/2"	23-1/4"	17"	22-1/2"	17-1/8"	21-3/8"	8-5/8"	21-1/8"	10-3/16"	8', 9',10',12' 14', 16', 18' 20'	8'9'10'12'	20,000
18"	N/A	17-1/2"	15"	1/3 of length	N/A	N/A	21-1/4"	5-1/2"	21-1/4"	6-1/2"	24-3/4"	7-1/2"	27"	18-5/8"	25-1/4"	17-3/4"	24-1/8"	9-13/16"	24-1/4"	11-5/8"	8', 9',10',12' 14', 16', 18' 20'	N/A	20,000
20"	N/A	20"	17"	1/3 of length	N/A	N/A	24-1/8"	5-15/16"	25"	9"	28-1/2"	8-1/2"	27-3/4"	21-1/2"	39"	25-1/4"	27"	10-3/4"	27"	12-7/8"	12',14',16',18' 20', 22', 24'	N/A	20,000
22"	N/A	22"	18-1/2"	1/3 of length	N/A	N/A	26-1/2"	6-1/4"	25-1/8"	9-1/2"	NA	NA	NA	NA	41"	28-1/2"	29-3/4"	12-1/8"	29-3/4"	14-1/4"	14',16',18',20' 22', 24'	N/A	20,000
24"	N/A	24"	20"	1/3 of length	N/A	N/A	28-3/4"	6-7/8"	27-3/4"	9-3/4"	32-1/4"	10-5/8"	35-3/4"	23"	42"	28-1/2"	32-1/2"	13-1/4"	32-1/2"	15-11/16"	14',16',18',20' 22', 24'	N/A	20,000
30"	N/A	30"	25"	1/3 of length	N/A	N/A	35-3/4"	8-5/8"	NA	NA	NA	NA	NA	NA	48"	36"	40-1/2"	16-1/2"	40-1/2"	19-1/4"	20',22',24',26' 28', 30'	N/A	20,000
36"	N/A	36"	30"	1/3 of length	N/A	N/A	42-3/4"	10-1/2"	NA	NA	NA	NA	NA	NA	NA	NA	48-3/4"	20-1/8"	48-3/4"	23-1/2"	20',22',24',26' 28', 30'	N/A	20,000

<sup>\*</sup> Round columns should be trimmed only in non-tapered area of column to assure proper fit to base.

Caps are viewed from top.

Bases are viewed from bottom.