



Thermospan™ 125 Insulated Overhead Doors Standard Design Criteria

STANDARD STRUTTING* SCHEDULE

FINISHED DOOR WIDTH	STRUTS
UP TO 16'-2"	NONE REQUIRED
SEE THERMOSPAN™ 150 FOR DOORS EXCEEDING 16'-2" WIDE	

*WAYNE-DALTON'S STANDARD COMMERCIAL PRODUCT SUBMITTED BASED ON DESIGN CRITERIA PROVIDED. MINIMUM WIND LOAD AS REQUIRED BY THE AUTHORITY HAVING JURISDICTION OVER THE GEOGRAPHICAL LOCATION OF DOOR(S) INSTALLATION MAY REQUIRE ADDITIONAL DESIGN CONSIDERATION AND/OR CLEARANCES. CONSULT FACTORY IF SPECIFIC WIND LOAD REQUIREMENTS APPLY.

PANEL & GLAZING SCHEDULE

FINISHED DOOR WIDTH	No. OF PANELS	MAX No. OF 24x6 LITES PER SECTION	MAX No. OF FULL VIEW SECTIONS	
			LIGHT GLAZING **	HEAVY GLAZING ***
UP TO 9'-2"	2	2	No. OF SECTIONS MINUS 1 *	No. OF SECTIONS MINUS 1 *
9'-3" - 12'-2"	3	3		
12'-3" - 14'-2"	4	4		
14'-3" - 16'-2"	4	4		
SEE THERMOSPANTM 150 FOR DOORS EXCEEDING 16'-2" WIDE				

* NOT AVAILABLE IN LOCK SECTION (IF KEYED LOCK REQUIRED) OR IN BOTTOM SECTION.
 ** LIGHT GLAZING = 1/8" GLAZING OR 1/4" ACRYLIC & LEXAN
 *** HEAVY GLAZING = 1/2" GLAZING OR 1/4" GLASS (DOUBLE END STILES REQUIRED)

SECTION HEIGHTS

FINISHED DOOR HEIGHT	SECTION STACK HEIGHT	No. OF 24" SECTIONS	No. OF 20.8" SECTIONS
5' 3"	5' 2.4"	0	3
5' 6"	5' 5.6"	1	2
5' 9"	5' 8.8"	2	1
6' 1"	6' 0"	3	0
7' 0"	6' 11.2"	0	4
7' 3"	7' 2.4"	1	3
7' 6"	7' 5.6"	2	2
7' 9"	7' 8.8"	3	1
8' 1"	8' 0"	4	0
8' 8"	8' 8"	0	5
9' 0"	8' 11.2"	1	4
9' 3"	9' 2.4"	2	3
9' 6"	9' 5.6"	3	2
9' 9"	9' 8.8"	4	1
10' 1"	10' 0"	5	0
10' 5"	10' 4.8"	0	6
10' 8"	10' 8"	1	5
11' 0"	10' 11.2"	2	4
11' 3"	11' 2.4"	3	3
11' 6"	11' 5.6"	4	2
11' 9"	11' 8.8"	5	1
12' 1"	12' 0"	6	0
12' 2"	12' 1.6"	0	7
12' 5"	12' 4.8"	1	6
12' 8"	12' 8"	2	5
13' 0"	12' 11.2"	3	4
13' 3"	13' 2.4"	4	3
13' 6"	13' 5.6"	5	2
13' 9"	13' 8.8"	6	1
14' 1"	14' 0"	7	0
14' 2"	14' 1.6"	1	7
14' 5"	14' 4.8"	2	6
14' 8"	14' 8"	3	5
15' 0"	14' 11.2"	4	4
15' 3"	15' 2.4"	5	3
15' 6"	15' 5.6"	6	2
15' 9"	15' 8.8"	7	1
16' 1"	16' 0"	8	0
SEE THERMOSPAN™ 150 FOR DOORS OVER 16' HIGH			

HIGH CYCLE TORSION ASSEMBLY OPTIONAL UPGRADES

OPTION	DESCRIPTION
10,000 CYCLES	STANDARD MINIMUM CYCLES
25,000 CYCLES	SPRINGS ONLY
50,000 CYCLES (SPRINGS ONLY)	UP TO & INCLUDING 144 SQ. FT (MAY REQUIRE SOLID SHAFT UPGRADE)
100,000 CYCLES (SPRINGS ONLY)	UP TO & INCLUDING 144 SQ. FT (MAY REQUIRE SOLID SHAFT UPGRADE)
50,000 HIGH CYCLE DOOR SYSTEM	50,000 CYCLE SPRINGS END BRACKETS WITH FLANGE BEARINGS PRECISION 10 BALL ROLLERS 11 GAUGE END HINGES CHAIN TENSIONER (JACKSHAFT OPERATOR) SOLID SHAFT (UPGRADE IF APPLICABLE)
100,000 HIGH CYCLE DOOR SYSTEM	100,000 CYCLE SPRINGS END BRACKETS WITH FLANGE BEARINGS PRECISION 10 BALL ROLLERS 11 GAUGE END HINGES CHAIN TENSIONER (JACKSHAFT OPERATOR) SOLID SHAFT (UPGRADE IF APPLICABLE)

SPECIAL APPLICATION PRODUCTS & SERVICES AVAILABLE

ITEM	DESCRIPTION
PASS DOOR	SEE THERMOSPAN™ 200 FOR PASS DOOR
MANUAL CARRY-AWAY MULLION	EXTRUDED ALUMINUM DESIGN 10 FT. HIGH MAXIMUM; 2" TRACK ONLY 30-1/2" HEADROOM REQUIRED (STD. LIFT)
SWING-UP MULLION WITH MANUAL WINCH	EXTRUDED ALUMINUM DESIGN 16 FT. HIGH MAXIMUM DOOR & MULLION OVERLAPS HEADER 4" 2" TRACK - 34-1/2" HEADROOM REQUIRED 3" TRACK - 35-1/2" HEADROOM REQUIRED
OBSTRUCTED OPERATING ZONE	SITE SPECIFIC DESIGN ENGINEERED TRACK SYSTEMS