



General Operating Clearances

Thermospan® 200-20

| Type | Headroom*** | | Sideroom** | | Depth Into Room | Center Line of Springs | |
|-------------------------------|------------------|----------|--------------|----------|---------------------------|-------------------------|---------------------------|
| | 2" Track | 3" Track | 2" Track | 3" Track | 2" & 3" Track | 2" Track | 3" Track |
| Standard Lift Manual 12"R | 13"-17" | NA | 4.5" | 5.5" | Opening Height +18" | Opening Height +12" | NA |
| Standard Lift Manual 15"R | 15"-20" | 16"-21" | | | | Opening Height +13" | Opening Height +14" |
| Standard Lift Motor Oper.12"R | 15"-20" | NA | | | Opening Height +66" | Opening Height +12" | NA |
| Standard Lift Motor Oper.15"R | 15"-20" | 18"-24" | | | | Opening Height +13" | Opening Height +14" |
| High Lift Manual | High Lift +12" | | | | 24" One Side | | Opening Height –Lift +30" |
| High Lift Motor Oper. | | | | | | | |
| Vertical Lift Manual | Door Height +20" | | 4.5" | 5.5" | 18" | Double Door Height +13" | |
| Vertical Lift Motor Oper. | | | 24" One Side | | | | |
| Low Headroom Manual* | 6"-15" | 6"-15" | 6" | 9" | Opening Height +20" to26" | Does Not Apply | |
| Low Headroom Motorl Oper.* | 9"-17" | 9"-17" | | | Opening Height +66" | | |

*Note: Springs must be rear mount to achieve minimum headroom listed. Front mount torsion headroom depends on drum size, and varies over the range listed. See Approval Drawing.

**Note: 8" sideroom required, one side, for doors with chain hoist.

***Note: Headroom for standard lift depends on drum size, and varies over the range listed. See Approval Drawing.

General Operating Clearances

| Type | Headroom | | Sideroom | | Depth Into Room | Center Line of Springs | |
|--------------------------------|---------------------|----------|--------------|----------|----------------------------|----------------------------|----------------|
| | 2" track | 3" track | 2" track | 3" track | 2" & 3" track | 2" track | 3" track |
| Standard Lift Manual 12"R | 13"-17" | NA | 4½" | 5½" | Opening Height +18" | Opening Height +12" | NA |
| Standard Lift Manual 15"R | 15"-20" | 16"-21" | | | Opening Height +13" | Opening Height +14" | |
| Standard Lift Motor Oper. 12"R | 15"-20" | NA | | | Opening Height +66" | Opening Height +12" | NA |
| Standard Lift Motor Oper. 15"R | 15"-20" | 18"-24" | | | Opening Height +13" | Opening Height +14" | |
| High Lift Manual | High Lift +12" | | 24" One Side | | Opening Height – Lift +30" | Opening Height | Opening Height |
| High Lift Motor Oper. | | | | | | +Lift +6½" | +Lift +7½" |
| Vertical Lift Manual | Door Height +20" | | 4½" | 5½" | 18" | Double Door Height +13" | |
| Vertical Lift Motor Oper. | | | 24" One Side | | | | |
| Low Headroom Manual | 6"-15" | 6"-15" | 6" | 9" | Opening Height +20" - 26" | Does Not Apply | |
| Low Headroom Motor Oper. | 9"-17" | 9"-17" | | | Opening Height +66" | | |

Panel/Section Selection Guide

| Door Section and Lite Selection | | | Door Height and Section Selection | |
|---------------------------------|--------------|------------------|-----------------------------------|--------------|
| Door Width | No. Panels | Max. No. Windows | Door Height | No. Sections |
| Up to 92" | 2 | 2 | Up thru 8'1" | 4 |
| 93" to 122" | 3 | 3 | 8'2" thru 10'1" | 5 |
| 123" to 162" | 4 | 4 | 10'2" thru 12'1" | 6 |
| 163" to 192" | 5 | 6 | 12'2" thru 14'1" | 7 |
| 193" to 242" | 6 | 7 | 14'2" thru 16'1" | 8 |
| 243" & up | Call Factory | | 16'2" & up | Call Factory |

NOTES:

1. For low headroom, springs must be rear mount to achieve minimum headroom listed. Front mount torsion headroom depends on drum size, and varies over the range listed. See approval drawings.
2. Side-room of 8" required, one side, for doors with chain hoist.
3. Headroom depends on drum size, and varies over the range listed. See approval drawings.