



# General Operating Clearances

## Model 216

| Type                          | Headroom***      |          | Sideroom**   |          | Depth Into Room            | Center Line of Springs  |                           |                            |                            |
|-------------------------------|------------------|----------|--------------|----------|----------------------------|-------------------------|---------------------------|----------------------------|----------------------------|
|                               | 2" Track         | 3" Track | 2" Track     | 3" Track | 2" & 3" Track              | 2" Track                | 3" Track                  |                            |                            |
| Standard Lift Manual 12"R     | 13"-17"          | NA       | 4.5"         | 5.5"     | Opening Height +18"        | Opening Height +12"     | NA                        |                            |                            |
| Standard Lift Manual 15"R     | 15"-20"          | 16"-21"  |              |          |                            | Opening Height +13"     | Opening Height +14"       |                            |                            |
| Standard Lift Motor Oper.12"R | 15"-20"          | NA       |              |          | Opening Height +66"        | Opening Height +12"     | NA                        |                            |                            |
| Standard Lift Motor Oper.15"R | 15"-20"          | 18"-24"  |              |          |                            | Opening Height +13"     | Opening Height +14"       |                            |                            |
| High Lift Manual              | High Lift +12"   |          |              |          | 24" One Side               |                         | Opening Height –Lift +30" | Opening Height +Lift +6.5" | Opening Height +Lift +7.5" |
| High Lift Motor Oper.         |                  |          |              |          |                            |                         |                           |                            |                            |
| Vertical Lift Manual          | Door Height +20" |          | 4.5"         | 5.5"     | 18"                        | Double Door Height +13" |                           |                            |                            |
| Vertical Lift Motor Oper.     |                  |          | 24" One Side |          |                            |                         |                           |                            |                            |
| Low Headroom Manual*          | 6"-15"           | 6"-15"   | 6"           | 9"       | Opening Height +20" to 26" | Does Not Apply          |                           |                            |                            |
| Low Headroom Manual Oper.*    | 9"-17"           | 9"-17"   |              |          | Opening Height +66"        |                         |                           |                            |                            |

\*Note: Springs must be rear mount to achieve minimum headroom listed. Front mount torsion headroom depends on drum size, and varies over the range listed. See Approval Drawing.

\*\*Note: 8" sideroom required, one side, for doors with chain hoist.

\*\*\*Note: Headroom for standard lift depends on drum size, and varies over the range listed. See Approval Drawing.