

# Closet and Wardrobe Doors

# Marker Door

۲

# **Steel Marker Door with Magnetic Dry Erase Surface**



- Durable 'Dry Erase' finish on stainless steel panel works great with dry erase markers
- Easy to adjust for out-of-square openings
- One piece 1-3/4" deep top track and integral fascia
- Low rise bottom track for minimal floor obstruction
- Adjustable top guides for greater vertical adjustment
- Track: Top and bottom track prefinished to match door
- Colors: Bright White, Vanilla, Architectural Brown, Black, Arctic Silver, Satin Gold, Bright Gold
- Limited lifetime warranty



Shown in Satin Gold, inset shown in Architectural Brown

# **DUNBARTON Door and Entry Systems**

## Marker Door with Magnetic Dry Erase Panels

## MARKER DOOR SPECIFICATIONS

Provide Marker Door sliding wardrobe doors manufactured by Slimfold Corporation, Dothan, AL in the dimensions shown on the drawings and with the following attributes:

### ARRANGEMENT

- a. Sliding doors shall consist of framed prefinished steel panels supported by adjustable bottom rollers and adjustable top guides that travel in a threshold track and top track respectively.
- b. Top track to be prefinished steel with an integral fascia that matches the stile and rail finish.
- c. The bottom track shall be prefinished steel to match door frame and shall not exceed 5/16" (8mm) in height for minimum floor obstruction.
- d. The bottom roller shall be free floating and provide a 1" (25mm) vertical adjustment. Marker Door rollers are factory installed and shall have plain bearing acetal wheels.
- e. The adjustable top guides shall be permanently fixed to the top connectors and fit snugly into the vertical openings in the top track.

#### FRAME

a. The frame shall consist of prefinished roll-formed stiles and rails joined at each corner by positively retained, removable, unhanded, connectors that snap in place and contain preassembled rollers and guides.

## PANELS

a. Dry erase finished, steel panel.

## FINISHES

Bright White, Vanilla, Architectural Brown, Black, Arctic Silver, Satin Gold, Bright Gold

No. Panels	Size	Door Width	Finished Opening Width
2	4'0"	24-1/8"	48"
2	5'0"	30-1/8"	60"
2	6'0"	36-1/8"	72"

Required Finished Opening Height:			
6'8" (80-1/2") (2045mm)			
Finishing Open Width Tolerance +0" / -2"			
(+0mm/-51mm)			



1101 Technology Drive I Dothan, Alabama 36303 800.633.7553 | 334.794.9184 (fax) www.dunbarton.com I sales@dunbarton.com

۲

SF113 Rev. 02.2015