





RESIDENTIAL UPGRADES

Bringing High Scale Quality to Designer Bathrooms

COMMERCIAL PROJECTS

The Choice of Many of the Finest Hotels, Resorts, and Condominium Complexes Around the World



new **EZ-Adjust** system!)



Prima Series Hinge



Special Top Mount Hinge (Compatible only with EZ-Adjust Header System)



Prima Hinges provide extra application

possibilities. Their Top and Bottom Pivot style handles the weight of the door better than

traditional "Side Mount" hinges, as well as allowing

aesthetic enclosure. Prima Hinges can be mounted floor and ceiling, floor and wall, floor and fixed

greater glass exposure, thus making for a more

transom, floor and adjacent panel, or floor and

header for enclosures not reaching the ceiling.

built-in adapter plate that allows use with our

EZ-Adjust Header System (see top left).

CRL's new Special Top Mount Prima Hinge has a



Offset Bracket



L-Bracket Wall Mount



Inline Panel Mount



135° Glassto-Glass Mount









Standard Top and **Rottom Mount**



Fixed Transom Mount



Wall Mount





SPECIFICATIONS

For Glass Thickness: 5/16" (8 mm) to 3/8" (10 mm) Tempered Safety Glass (Not Included)

Construction: Solid Brass Hinge Swings: Full Rotation

Closing Type: Self-Centering When Within 15 Degrees of Closed Position

Glass Fabrication: Cut-Out Required

Finishes: Over 20 Stock Colors (Custom Finishes Also Available)

Includes: Gaskets, Screws, Glass Fabrication Details NOTE: Senior Prima Hinges are Available for 1/2" (12 mm) Thick Glass. Junior Prima Hinges are Available for 1/4" (6 mm) Thick Glass.



ïenna Series Hinge



Wall Mount Full Back Plate



Wall Mount Short Back Plate



Wall Mount Offset Back Plate



Glass-to-Glass



Glass-to-Glass



Glass-to-Glass



Cologne Series Hinge



Wall Mount Full Back Plate




Wall Mount Offset Back Plate




Glass-to-Glass Glass-to-Glass





Glass-to-Glass (For "Mouse-Ears" Cut-Out)



SPECIFICATIONS

For Glass Thickness: 3/8" (10 mm) to 1/2" (12 mm) Tempered Safety Glass (Not Included)

Construction: Solid Brass

Hinge Swings: 90 Degrees Inwards and Outwards Closing Type: Self-Centering When

Within 15 Degrees of Closed Position Glass Fabrication: Cut-Out Required

Finishes: Over 20 Stock Colors (Custom Finishes Also Available) Includes: Gaskets, Screws, Glass

Fabrication Details

CRL Offers Over 20 Varieties of Hinge Series in Over 20 Finishes, to Accommodate 1/4" to 1/2" (6 mm to 12 mm) Thick Glass, and Match Most Any Modern Bathroom Décor. A Full Line of Accessory Items are Also Available.







Geneva Series Hinge







Wall Mount Full Back Plate



Wall Mount Short Back Plate



Wall Mount Offset Back Plate



Glass-to-Glass



Glass-to-Glass



Glass-to-Glass



Pinnacle Series Hinge



Wall Mount Full Back Plate



Wall Mount Short Back Plate



Wall Mount Offset Back Plate



Glass-to-Glass





Glass-to-Glass



Geneva Hinges offer three varieties of Wall Mount Hinges, in addition to three Glass-to-Glass models. Pinnacle Hinges also offer three styles of Wall Mount Hinges, as well as three Glass-to-Glass models. Adjustable models (not pictured here) that feature up to 90 degrees adjustment to accommodate "off angles" are also available. Geneva and Pinnacle Series Hinges contain the same internal mechanism but offer different styles of hinge plates.

SPECIFICATIONS

For Glass Thickness: 3/8" (10 mm) to 1/2" (12 mm) Tempered Safety Glass (Not Included)

Construction: Solid Brass

Hinge Swings: 90 Degrees Inwards and Outwards Closing Type: Self-Centering When Within 15 Degrees of Closed Position

Glass Fabrication: Cut-Out Required

Finishes: Over 20 Stock Colors (Custom Finishes

Also Available)

Includes: Gaskets. Screws. Glass Fabrication Details



Floor-to-Ceiling Mount System

Frameless Vertical Post Systems

- Standard or Custom Kits Allow User to Stabilize Fixed Panels of Glass Not Going to Ceiling
- Excellent Modern Alternative to More Traditional Horizontal Header Systems that Run Wall-to-Wall
- Floor-to-Ceiling Mount and Two-Point Ceiling Mount Systems Available
- Custom Kits Available in Various Finishes and Post Configurations
- Hinges, Fixed Panel Clamps, U-Channels, Door Pulls and Other Accessories Ordered Separately
- Complete System Details at crlaurence.com



Two-Point Ceiling Mount System

Cottage Series Sliding Shower Door Kits

- Designed for 1/4" (6 mm) or 3/8" (10 mm) Glass
- Top Hung Design Allows for Bottom Track and Side Jambs to Remain Uncluttered
- . Up to Six Stock Sizes and Four Stock Finishes
- Custom Units Available

SPECIFICATIONS

Materials: Extrusions (Aluminum), Towel Bar (Brass Tubing), Knob (Solid Brass) For Glass Thickness: 1/4" (6 mm) or 3/8" (10 mm) Tempered Safety Glass (Not Included)

Finishes: Four Stock Colors (Custom Finishes Available) Includes: Aluminum Extrusions, 24" (610 mm) Towel Bar, Knob, Hardware Package and Installation Instructions

Glass Fabrication: Towel Bar - Two 1/2" (12 mm) Diameter Holes, 24" (610 mm) Center-to-Center; Knob - One 1/2" (12 mm) Diameter Hole; Top Hangers - Four 1/2" (12 mm) Diameter Holes (two per glass panel)







Side Jamb



Towel Bar







Revolutionary Cottage 'CK' Series with Clear Jambs for the 'All-Glass' Look, or Traditional 'DK' Series with Metal Jambs

Hydroslide Sliding Shower Door Kits



- Single Sliding Door System for Compact Areas
- For 5/16" or 3/8 (8 or 10 mm) Tempered Glass
- Available in Four Stock Finishes

CRL Hydroslide Sliding Shower Door Kits feature the latest European 'all-glass' look. Kits are available in either 60" (1524 mm) or 84" (2134 mm) widths. Installers can cut the width to size, and height is optional as long as the sliding door glass weighs less than 88 pounds (40 kg). The 180 Degree Wall-to-Wall Installation only requires a 180 Degree Standard Kit for the installation. The 90 Degree Wall-to-Glass Installation requires a 180 Degree Standard Kit plus a 90 Degree Wall-to-Glass Accessory Kit for the installation. Individual or replacement parts can also be ordered. Bottom Glass Attachments, Handles or Knobs must be ordered separately. Custom units are also available.

SPECIFICATIONS

Glass Thickness Range: 5/16" (8 mm) to 3/8" (10 mm) Tempered Safety Glass (Not Included) Materials: Plated or Lacquered Solid Brass Fittings; Anodized Aluminum Sliding Door Track Maximum Door Weight: 88 lbs (40 kg)

Fabrication: Holes Required in Fixed Panel and Door

Includes: Aluminum Threshold for Optional use Under Door, Gaskets, Screws, and Fabrication Information

FOR MORE INFORMATION ON OTHER CRL PRODUCTS SEE SWEET'S SECTIONS:

05 58 00/CRL-8838 COLUMN COVERS 05 73 00/CRL-5341 STRUCTURAL HEAVY **GLASS RAILING** 07 42 00/CRL-8840 **ROOFING AND SIDING** PANFI S 08 42 00/CRL-1676 **ENTRANCES & STOREFRONTS** 08 42 00/CRM-4545 ENTRANCES & **STOREFRONTS** Facilities & Owners 08 44 26.11/CRL-8621

STRUCTURAL GLASS

CURTAIN WALLS

08 56 59/CRL-4964 SERVICE WINDOWS 08 71 00/CRL-3069 DOOR HARDWARE 08 71 00.14/CRL-7154 STACKING PARTITION SYSTEMS 10 71 13/CRI -8843 EXTERIOR SUN CONTROL DEVICES 11 18 00/CRL-6331 **BULLET RESISTANT PROTECTION** 11 46 16/CRL-5592 SNEEZE GUARDS/ PARTITION POSTS

'All-Glass' Restroom Partition Sv

- 'All-Glass' Look Without Post Interruption for 1/2" (12 mm) Thick Glass
- 2" x 3" (51 x 76 mm) Stainless Steel Posts With Concealed Base Fastener
- Posts Mounted Behind Glass to Maximize "Frameless" Appearance
- Built Per Your Specifications Utilizes CRL Shower Door Hardware
- Doors Accommodate Slide-Bolt Latches (Sold Separately)
- Allows Thru-Glass Mounted Optional Fixtures

This 'All-Glass' Restroom Partition System will modernize any commercial or institutional bathroom area with your choice of multiple architectural finishes. Since metal posts do not 'interrupt' the glass panels, a beautiful frameless environment is attained. The 'All-Glass' Restroom Partition System allows field adjustable height with a floating top mount appearance. No field fabrication is required, ensuring easy installation. CRL hardware is utilized for this system that is designed for use with 1/2" (12 mm) thick tempered glass. Customers may incorporate several optional fixtures as needed, such as coat hooks, toilet paper dispensers, toilet seat cover dispensers and sanitary napkin disposal.



CRL Specialty Catalogs - Can be ordered, viewed or downloaded online at crlaurence.com



Architectural AM09



Architectural **AH11**





LP11

Commercial Door



Frameless Shower Door Hardware and Supplies



Hospitality &

HS07



Architectural



Door Controls Accessories



Transaction and Security Hardware

TH10



Glass Bonding

GB10



VISIT THE WORLD of crlaurence.com

- Access to All CRL Products Through CRL's Easy-to-Use A to Z Product Index See all of the CRL Catalogs
- Technical Articles and Product Support Ordering and Shipping Information Help in Using the Site
- CRL Locations with Addresses, Directions, Phone and Fax Numbers
 Direct E-Mail Connections to CRL Departments
- Account Policies and Credit Terms A Calendar of Industry Trade Shows

Visit CRL's "Installation Image Gallery" @ crlaurence.com for more beautiful shower enclosure photos

Technical Sales Department For All Your Project Requirements

C.R. Laurence Company has a Technical Sales Department to assist with design plans and installation questions concerning Frameless Shower Door Hardware. Your job can be made easier with the help of CRL's Technical Sales Representatives who are trained in the newest Hardware Systems, and can offer you detailed diagrams and layout sheets. Ask for Extension 7740.

