

**ECOstone®**  
**Recycled Rubber Flooring**

**Product Specification**

**Performance Attributes**

- Complies with new ASTM Sustainability Assessment
- Single-ply, non-laminated
- Indoor and outdoor
- Outstanding slip-resistance
- Unbelievable durability
- Cushioned resilience
- Stain resistance
- Consistent color (no wear layer)
- Low VOC emissions
- Custom colors
- Logo/graphic inlays
- Easy installation/maintenance

**Colors**



**Product Presentation**

ECOSurfaces recycled rubber flooring: The single-ply rubber surface furnished under this specification shall be ECORE International's: ECOstone as specified.

The material ECOstone is a non-laminated, single-ply surface made from multiple gray tones of reprocessed EPDM (Ethylene-Propylene Diene Monomer) rubber to give a cool gray marble look. The color shall be (specify: color number and name).

**Physical Properties**

ECOstone Rubber Rolls		
Width:	48"	
Thickness:	4mm (5/32")	standard
	6mm (1/4")	special
Weight:	4mm	1.1lbs/sq.ft.
	6mm	1.7lbs/sq.ft.
Length:	200 sq/ft (50 l/ft) per roll	
ECOstone Rubber Tiles		
Size:	36" x 36"	
	18" x 18"	

Thickness:	4mm (5/32") 6mm (1/4")	standard special
------------	---------------------------	---------------------

<b>Test</b>	<b>ASTM</b>	<b>Results</b>
Tensile Strength	D412	200 lb/in <sup>2</sup> min
Flexibility	F137	Pass ¼ inch mandrel
Coefficient of Friction	D2047	>0.9
McBurney Indentation	F142, 1 min	0.1120 inches
Thermal Conductivity	C518	0.406 Btu-in/hr-ft <sup>2</sup> -°F
Static Load Limit	F970, 400 lbs	<0.005 in
Chemical Resistance	F925	no change
Impact Insulation Class	E492	49
Sound Transmission Coefficient	E413	51
Noise Reduction Coefficient	C423	0.10 sabine/ft <sup>2</sup>
Sustainability	E2129-01	data collected