

BURKTURF

Recycled Rubber Flooring

90% post-consumer recycled content

LEED™ points-eligible

Interior or exterior use

Ramps, entries, concourses

Moisture-prone areas

Durable

Slip-resistant

Spike and skate resistant

Tile or rolls

Easy maintenance

10-year wear warranty



Properties

| | |
|------------------------|--|
| <i>Colors</i> | Earthtone, Blue, Cranberry, Green |
| <i>Sizes</i> | Tile: 12" x 12" nominal Roll: 12" x 25 feet nominal |
| <i>Thickness</i> | 5/16" nominal |
| <i>Weight</i> | 2 lbs per sf |
| <i>Carton</i> | 25 sf (25 12" x 12" tiles or one 12" x 25' roll) |
| <i>Slip-Resistance</i> | ASTM D 2047-static coefficient of friction Meets ADA requirements for ramps |
| <i>Hardness</i> | ASTM 2240-not less than 85 Shore A |
| <i>Adhesive</i> | Burke BR-711 required for warranty |
| <i>Fire Test</i> | ASTM D 2859-Pill Test-Passed; char diameter: 0.672 |
| <i>Warranties</i> | Delamination: Lifetime; Limited Wear: 10-years |

Burke
FLOORING

800-447-8442
burkeflooring.com

BURKTURF

Recycled Rubber Flooring

General Specifications

1. BurkTurf is made from recycled tire strips adhered to reinforced scrim backing. It can be used in most interior and exterior applications, but is not recommended for commercial kitchen environments.
2. BurkTurf tiles are 12" x 12" and BurkTurf rolls are 12" x 25'. Both tile and rolls are 5/16" (nominal) thickness.
3. BurkTurf resists deterioration due to exposure to moisture.
4. Colors available include Earthtone, Blue, Cranberry and Green. Exact color or shade may vary.

Adhesive

Use Burke Flooring BR-711 Adhesive, a solvent-free aqueous adhesive that needs to be applied to only one surface, permitting repositioning of BurkTurf during installation. BurkTurf may be installed on any smooth, dry interior or exterior surface. For exterior installations, ensure that newly installed BurkTurf is not be exposed to moisture for 72 to 96 hours to permit proper drying of adhesive.

Maintenance and Cleaning

General Cleaning Power vacuum or sweep as needed to remove loose dirt. BurkTurf retains traffic dirt, protecting interior areas. In heavy-traffic areas, daily vacuuming may be desired. Exterior installations can be cleaned by hosing to remove excessive mud.

Shampoo or Steam Cleaning If surface becomes heavily soiled, scrub with a commercial shampoo machine and vac-

uum dry to restore original finish. For exterior installations, shampoo and rinse with hose.

Removing Foodstuff, Beverages and Stains Mix a strong concentration of detergent with any commercial bleach. Scrub vigorously with a hand brush. Vacuum carpet thoroughly to remove dampness.

Removing Burns If burns are not severe, a coarse wire brush can be used to brush up the nap. Otherwise, remove burned BurkTurf and scrape old adhesive from floor surface. Install replacement BurkTurf by following non-porous installation instructions as listed on BR-711 adhesive container.

Precautions

BurkTurf must not be used in kitchens or in any area exposed to oil, grease, vegetable fats, strong detergents, acids, solvent-based paints or coatings, gasoline, kerosene or similar solvents that can be absorbed into the flooring and cause deterioration of the rubber. Do not allow the cross-sectional face (side) of BurkTurf to remain exposed and do not drag or move objects across it or drop objects onto it that may cause damage. BurkTurf should not be exposed to direct heat. When exposed to direct or indirect sunlight and/or other outdoor elements, discoloration will occur.

Burke
F L O O R I N G

2250 South Tenth Street
San Jose, CA 95112

800-447-8442
burkeflooring.com