

CONTROL OPTIONS

Phantom Screens offers a wide range of control options to suit each customers' individual needs. All accessory products are guaranteed high quality components covered under Phantom Screens warranty.



Single Channel Hand Held Remote - Allows the user to operate one Executive motorized screen independently, or an unlimited number of screens (*within range) simultaneously. This control option comes equipped with a wall mountable bracket, and is available in off white only.



Five Channel Hand Held Remote - Allows the user to operate up to five different Executive motorized screens independently of each other, or an unlimited number of screens (*within range) simultaneously up to five different groupings. This control option comes equipped with a wall mountable bracket and is available in off white only.



Single Channel Decoflex In-Wall Mount Remote - Allows the user to operate one Executive motorized screen independently, or an unlimited number of screens (*within range) simultaneously. This control option is manufactured for mounting inside of a standard plastic decora box, comes with a decora faceplate, and is available in White, Ivory or Black.



Five Channel Decoflex In-Wall Mount Remote - Allows the user to operate up to five different Executive motorized screens independently of each other, or an unlimited number of screens (*within range) simultaneously up to five different groupings. This control option is manufactured for mounting inside of a standard plastic decora box, comes with a decora faceplate, and is available in White, Ivory or Black.



Single Channel Poolside Remote - Allows the user to operate one Executive motorized screen independently, or an unlimited number of screens (*within range) simultaneously. This remote is water resistant and suitable for a pool or water exposed area. This control option comes equipped with a hanger button, and is available in white with an electric blue rubberized trim.



Five Channel Poolside Remote - Allows the user to operate up to five different Executive motorized screens independently of each other, or an unlimited number of screens (*within range) simultaneously up to five different groupings. This remote is water resistant and suitable for a pool or water exposed area. This control option comes equipped with a hanger button, and is available in white with an electric blue rubberized trim.



Two Channel Key Chain Sequencing Remote - Allows the user to operate up to two screens independently of each other, or two different groupings of screens simultaneously. The key chain is a sequencing opener which means that one button does not open-stop-close-stop-open-stop-close etc.



Four Channel Key Chain Sequencing Remote - Allows the user to operate up to four screens independently of each other, or four different groupings of screen simultaneously. The key chain is a sequencing opener which means that one button does not open-stop-close-stop-open-stop-close etc.



Digital Key Pad Remote - Allows the user to operate one Executive motorized screen independently, or an unlimited number of screens (*within range) simultaneously. It is a programmable indoor or outdoor security switch which can be mounted to a wall, similar to those for use with a garage door. It features a personal code number to help prevent unwarranted access to the premises, and the private entry code can be changed by the end user to ensure limited access or protection should a compromise of security occur.



Single Channel Wall Mount Remote - Allows the user to operate one Executive motorized screen independently, or an unlimited number of screens (*within range) simultaneously. This control option is affixed directly to a surface, and is available in off white only.




Timer with Sun Sensor - Allows the user to set a number of pre-set programs, similar to a thermostat, to automatically lower or retract one Executive motorized screen independently, or an unlimited number of Executive motorized screens (*within range) simultaneously at selected times of the day. This unit also comes with an optional sun sensor, which can also be used to lower and retract the screens when the heat of the sun exceeds or falls below the set threshold. This control option is battery operated, can be used for inside mount only, and is available in off white.



Single Channel Dry Contact Interface for Home Automation - Allows the user to operate one Executive motorized screen independently, or an unlimited number of screens (*within range) simultaneously through a home automation system. This control option is mounted to a surface, usually near the unit or motherboard, and is available in light gray only.



16 Channel RS232 Interface - Allows the user to operate up to 16 different Executive motorized screens independently of each other, or an unlimited number of screens (*within range) simultaneously up to 16 different groupings through a home automation system. This control option is mounted to a surface, usually near the motherboard, and is available in off white only.



Wind Sensor - Allows the user to automatically retract one Executive motorized screen independently, or an unlimited number of Executive motorized screens (*within range) simultaneously when winds exceed the set threshold. This control option is mounted in a wind-exposed area and is available in off white only.



Sun/Wind Sensor - Allows the user to automatically lower or retract one Executive motorized screen independently, or an unlimited number of Executive motorized screens (*within range) simultaneously when winds or sun exceed the set threshold. This control option is mounted in a wind/sun-exposed area and is available in off white only.

*requires a Telis Soliris Transmitter



Sunis RTS Wireless Sun Sensor - Allows the user to operate one Executive motorized screen independently, or an unlimited number of screens (*within range) simultaneously through wireless sun control capability. The Sunis is equipped with a solar panel that recharges the batteries contained in the unit. The dimensions of the Sunis is 4" in diameter and 2" in depth and it is round in appearance (similar to the size and shape of a hockey puck).

*requires a Telis Soliris Transmitter



Telis Soliris Transmitter - For use with the Soliris Sun/Wind Sensor and the Sunis wireless sun sensor. This remote allows the user to override a sun sensor so that you can raise and lower your screens even when the sun is shining and the sensor has activated the screens. Must be used with the Sunis and the Soliris.



Manual Crank Handles - Are used to operate the gear of a manually operated Executive. These handles are available in different standard lengths to suit the individual need of the customer.



Roll Control Speed Reducer - Can be used to slow the rate of retraction for a Phantom Door or Serene Window screen.



Door Chime - Can be used to alert occupants as to the entry of an individual through a Phantom Door or Serene Window screen. This unit has three settings, an "alert" chime, "alarm" chime or "off" setting.

** Transmitter range is considered to be up to 70 feet obstructed or 100 feet through open air from the actual unit **

All remote controls for Executive Motorized units can be used in conjunction, up to twelve per motor, and can operate an unlimited number of motors.