


CABLE·RAIL[®] Step-by-Step Installation for Metal Frames

by feeney


TOOL CHECKLIST

- Safety Glasses
- Work Gloves
- Pencil
- Measuring Tape
- Electric Drill
- Drill Bits
- Hammer
- Cable Cutters or Cut-Off disk
- Vise-Grip Pliers
- 7/16" Wrench
- Electric Grinder
- Hacksaw or Electric Reciprocating Saw
- Cable Lacing Needle



Mark drill hole locations on posts.


To minimize cable deflection, space cables no more than 3 inches apart and have a post or vertical spacer at least every 3 feet. Also, straight runs of cable (no turns/dips) should not exceed 70 feet. Runs with corners (2 bends at most) should not exceed 40 feet. See Frame Requirements on back page.



Drill holes in posts. Hole diameter depends on cable size and type of fitting. See chart below.


Cable Size	Threaded Term. Post	Intermediate Posts	Quick-Connect Post
1/8"	5/16"	1/4"	3/8"
3/16"	3/8"	1/4"	9/16"
1/4"	7/16"	5/16"	9/16"

If desired, Quick-Connect[®]SS posts may be through drilled at 5/16" and then counter-bored with the recommended Quick-Connect[®]SS drill to countersink the fitting.





If using Isolation Bushings or Grommets (optional), insert them into their corresponding post holes.

Note: If using Isolation Bushings, call for special drill hole sizes.




Insert the Threaded Terminal through the Terminal end post and attach a flat washer and Snug-Grip[®] Washer-Nut. Spin the nut 2 full turns. Strong resistance will be felt as the Snug-Grip[®] threads engage; so hold the Terminal shaft with pliers.

Use Beveled Washers for stair termination posts with angled holes. Available for Threaded Terminal and Quick-Connect[®]SS fittings.




Lace the free end of the cable through the intermediate posts and Quick-Connect[®]SS end post. Slide-on a flat washer and Quick-Connect[®]SS fitting until they rest against the face of the post.

Use a Lacing Needle if snagging becomes a problem.




Hold the Quick-Connect[®]SS fitting with one hand and pull the cable tight with the other. The fitting automatically locks when you release the cable.




Tighten Snug-Grip[®] Washer-Nuts until you can't flex the cables more than 4 inches apart using your thumb and fingers on one hand. See diagram to the left for tensioning sequence.


Important Note: If using electric or pneumatic tools to tighten the Washer Nuts, spin the nuts very slowly otherwise they will heat-up causing the threads to seize.



Saw off the excess threads as close to the Snug-Grip[®] Washer-Nut as possible. Touch-up with electric grinder. The special Snug-Grip[®] threads prevent the nut from loosening.




Use cable cutters or cut-off disk to trim the excess cable. Grind flush the exposed cable ends with an electric grinder.




Snap on end caps over the exposed Quick-Connect[®]SS fittings and the Snug-Grip[®] Washer-Nuts. You're done.

Enviro-Magic[®] Cleaner can be applied for lasting protection of stainless steel cable and parts.

Recommended cable tensioning sequence



Cables can either terminate or run through corner posts



*Offset drill holes at least 1/2" if you choose to have cables terminating at a single pipe post.

Metal Frame Requirements

Railing frames need to be designed and built strong enough to support the tension of properly installed cables, which is a load in excess of 300 lbs for each cable. Here are some basic guidelines to help you properly prepare your railing frames. These guidelines apply whether you are using 1/8", 3/16" or 1/4" cable.

Minimum sizes for all corner and end posts

All other posts should be sized as required for cap rail support strength or for code




The Basic Frame Design

Spacing From Walls:

Set end posts 3 to 4 inches away from the house/wall face to allow access for attaching cable end fittings.

Cap Rail:

Always include a strong, rigid cap rail that is securely fastened to all posts. Cap size is based on load strength needs and local code requirements. Set railing height per local code.




Maximum Post Spacing:

Space all posts and vertical spacers (see below) a maximum of 3 feet apart to minimize any deflection that may occur if the cables are ever forced apart.

And Some Other Options

Vertical Spacers (OPTIONAL):

Slender spacers may be used instead of some of the larger intermediate posts to achieve a more open railing design. These are non-structural members and are only intended to maintain cable spacing and minimize deflection. Examples are 1" metal tubing or 1/4" flat bar. Attach spacers to the cap rail and either the foot rail, deck surface or joists.



CONSTRUCTION CHECKLIST

- Space cables no more than 3 inches apart
- Space posts/verticals no more than 3 feet apart
- Observe minimum end/corner post sizes shown above
- Securely fasten all posts and cap rails
- Carefully plan all termination and corner posts for proper clearance, positioning, and maximum cable run lengths
- Straight runs of cable (no turns/dips) should not exceed 70 feet; runs with corner bends (2 bends at most) should not exceed 40 feet

IMPORTANT NOTE

For railings we recommend spacing the cables no more than 3 inches apart and placing posts or vertical members no more than 3 feet apart.

Please note that since building codes vary by state, county and city, our recommendations may not comply with code requirements in all areas.

Always consult with your local building department before starting your project.