



**CEILING SYSTEMS**

[ Between us, Ideas become reality.™ ]

Date Installed: \_\_\_\_\_ Armstrong Ceiling Product: \_\_\_\_\_  
 Building: \_\_\_\_\_ Armstrong Grid Product: \_\_\_\_\_  
 Owner: \_\_\_\_\_ Square Footage: \_\_\_\_\_  
 Address: \_\_\_\_\_ Contractor: \_\_\_\_\_  
 City/State/Zip: \_\_\_\_\_ City/State/Zip: \_\_\_\_\_

## HumiGuard™ Plus Ceilings and Armstrong Suspension Systems Fifteen (15) Year Limited Warranty

ARMATUFF, CIRRUS, CLEAN ROOM MYLAR, CLEAN ROOM VL/VL, CROSSGATE, DUNE, DUNE Second Look, FINE FISSURED, FINE FISSURED Fine Look, FINE FISSURED Open Plan, FINE FISSURED Second Look, GEORGIAN, FINE FISSURED School Zone, TUNDRA, ULTIMA, and ULTIMA Vector.

Please read the following terms carefully, as they are affected by the installation conditions. Armstrong does not assume nor does it authorize any person to assume or extend on its behalf any other warranty obligation or liability. This express warranty constitutes the entire obligation of Armstrong World Industries, Inc., and there are no other warranties expressed or implied, including any warranty of merchantability or fitness for any purpose whatsoever. Liability is limited to the above, and Armstrong World Industries, Inc., shall in no event be liable for incidental or consequential damages. This warranty does not extend to acoustical material which suffers damage caused by fire, or the elements, or any form of physical abuse.

Armstrong Commercial Suspension Systems (listed below) and Commercial Ceiling products with HumiGuard Plus performance, when installed together, are warranted to be free from defects in materials or factory workmanship, or sagging and warping as a result thereof, and against the occurrence of 50% red rust as defined by ASTM B117 test procedures, for fifteen (15) years from the date of installation (except for obvious defects in materials or factory workmanship, of which Armstrong must be notified within 30 days of the date of installation). This limited warranty is subject to further conditions outlined below.

All ceiling products shall be installed in accordance with Armstrong specifications in effect at the time of installation for HumiGuard Plus ceilings and PRELUDE XL, PRELUDE ML, PRELUDE XL Fire Guard, SUPRAFINE XL, SUPRAFINE ML, SUPRAFINE XL Fire Guard, PRELUDE PLUS XL Fire Guard, PRELUDE XL 360 Painted, SILHOUETTE XL ¼" and 1/8" reveal, AXIOM™ (all families), PRELUDE Concealed, CONCEALED Z-bar, Co-extruded Aluminum CLEAN ROOM, INTERLUDE™, SONATA™, SERPENTINA™, TRIMLOK®, and AL PRELUDE PLUS and SS PRELUDE PLUS suspension systems.

Installation of the products shall be carried out where the temperature is between 32° F (0° C) and 120° F (49°C). It is not necessary for the area to be enclosed or for HVAC systems to be functioning. However, all wet work (plastering, concrete, etc.) must be complete and dry. Such installations shall not be exposed to Abnormal Conditions, namely: chemical fumes, vibrations, presence of standing water, or moisture coming into direct contact with the ceiling, such as could result from building leaks or condensation. These products cannot be used in exterior applications. Armstrong treats these mineral fiber acoustical ceiling products with a mold-inhibiting or retarding agent. However, if the product is installed in, or subsequent to installation is exposed to, Abnormal Conditions (as referred to above), continued mold-inhibiting performance cannot be assured. The growth of mold is not covered by this warranty nor is it the responsibility of Armstrong. If subject to Abnormal Conditions, the products should be removed immediately and replaced once the conditions of the installation are normal. The ceiling product must not be used to support any other material except fiberglass thermal/sound control insulation installed in the thickness, density and manner according to Armstrong specifications.

Prior to installation, the ceiling product must be kept clean and dry and between 32° F (0° C) and 120° F (49°C) and not subject to any of the Abnormal Conditions set out above. You must notify Armstrong of any product failure covered by this warranty within 30 days of first observation of failure by writing to the following address: Armstrong World Industries, Inc., Post Office Box 3001, Lancaster, Pennsylvania 17604, or call us at 1 877 ARMSTRONG. Subject to confirmation by Armstrong of such product failure, Armstrong will deliver, at Armstrong's expense, F.O.B., to the place of installation, new ceiling panels and/or an installation system, of the same or similar type and grade, in an amount equal to that which is determined to be defective. **Please Note:** Some jurisdictions do not allow exclusion or limitation of incidental or consequential damages or limitations on how long an implied warranty lasts, so the above limitation or exclusion may not apply to you. Reference to Armstrong in this section shall mean, for the United States: Armstrong World Industries Inc., Armstrong Building Products, P.O. Box 3001, Lancaster, PA 17604; and shall mean, for Canada: Armstrong World Industries Canada Ltd., Armstrong Building Products, 6911 Decarie Blvd., Montreal, Quebec H3W 3E5.



For a valid warranty certificate contact your Armstrong Representative at 877 ARMSTRONG (276-7876)