



WORLD CLASS PERFORMANCE SINCE 1930

*The Path to Beautiful Decorative Concrete*



*Kemiko Products conform to LEED guidelines*



◆ Kemiko Stone Tone Stain

◆ Kemiko Stone Tone buff on Wax-Solvent Based

◆ Kemiko Stone Tone buff on Wax II -Water Based

◆ Kemiko Stone Tone Sealer II Low Viscosity Acrylic Urethane

◆ Kemiko Easy Shine Liquid Wax

◆ Kemiko Sta-Natural 0-VOC Waterborne Siloxane Emulsion

◆ Kemiko Neutra Clean Industrial Strength Cleaner

◆ Kemiko (Sta-Crete) SS1202 100% Solids Epoxy

◆ Kemiko (Sta-Crete) SS1600 Water Extended Epoxy Coating

◆ Kemiko (Sta-Crete) SS2700 Waterborne Aliphatic Polyurethane

◆ Kemiko (Sta-Crete) SS3300 100% Solids Polyaspartic

◆ Kemiko (Sta-Crete) SS3500 100% Solids Pigmented Epoxy

◆ Kemiko (Sta-Crete) SS3700 Water Extended High Gloss Epoxy Coating

◆ Kemiko (Sta-Crete) SS3800 Water Extended, Quick Dry, High Gloss Epoxy



[www.kemiko.com](http://www.kemiko.com)

**KEMIKO® DECORATIVE & INDUSTRIAL PRODUCTS**



Since 1930

## KEMIKO Stone Tone Concrete Stain

### Cola Stain

Reddish Brown Resembling Old Leather

### Malay Tan Stain

Buckskin Suede Tone with Carmel Marbling

### Aqua Blue Stain

Soft Blue Patina with Undertones of Green

### Black Stain

Tortoise Shell Black with Brown Marbling

### Golden Wheat Stain

Amber Hued Undertones

### English Red Stain

Terra Cotta with Rust and Soft Brown Hues

### Vintage Umber Stain

Rich Earthy Brown

### Green Lawn Stain

Soft Grey Green Resembling Aged Italian Marble

## KEMIKO Stone Tone Stain

Transforms an ordinary concrete slab into a luxurious floor that resembles marble or glazed stone. When concrete is scored and stained, Kemiko creates the appearance of expensive flooring at a fraction of the cost.

Whether working with a neo-classic, Southwestern, eclectic, or traditional décor, Stone Tone Stain adapts to enhance any setting.

### Description

**KEMIKO Stone Tone Concrete Stain** is an acid base, single component product that provides a decorative, low maintenance floor finish and is 0-VOC. This class product contains special wetting agents, which chemically combine metallic ions with the particles in the concrete to form colored oxides. Kemiko Stone Tone Stain is the perfect choice for interior and exterior projects.

### Applications

**Kemiko Stone Tone Stain** is applied to properly prepared concrete and cement/plaster material that contains sufficient cement material for color reaction. Typical applications include homes, driveways, patios, tilt walls, restaurants, shopping malls, and other interior/exterior applications where quality, cost-effective color enhanced concrete is desired.

## KEMIKO Neutra Clean

### Description

**KEMIKO Neutra Clean** is an industrial strength, high performance water base sodium metasilicate cleaner for the preparation of bare concrete and coated substrates. It has a pleasant citrus odor and does not contain any hazardous solvents.

### Applications

**KEMIKO Neutra Clean** is typically applied to concrete substrates to remove deleterious matter such as grease, grime, soil, wall plaster and other construction related residue. Typical applications include commercial kitchens, grocery stores, restaurants, showroom floors, walkways, and many other interior/exterior surfaces requiring cleaning.

## Kemiko Stone Tone buff on Wax-Solvent Based

### Description

**Kemiko Stone Tone buff on Wax - Solvent Based** is formulated to produce a low sheen finish with high protection and durability. Designed for interior use of Kemiko Stone Tone Stains, pigmented colored concrete, tile or brick.

### Applications

**Kemiko Stone Tone buff on Wax - Solvent Based** is ideal for interior residential and light commercial projects, such as offices, art galleries, and showrooms.

## KEMIKO Stone Tone buff on Wax II - Water Based

### Description

**KEMIKO Stone Tone buff on Wax II - Water Based** is formulated to produce a low sheen finish with good protection and durability. Designed for interior use over Kemiko Stone Tone Stains, pigmented colored concrete, tile, brick, or any masonry surface.

### Applications

**KEMIKO Stone Tone buff on Wax II - Water Based** is ideal for interior residential and light commercial projects such as offices, art galleries, and showrooms.

## KEMIKO Stone Tone Sealer II

### Description

**KEMIKO Stone Tone Sealer II** is a waterborne, water viscosity, single component, superior coalescing acrylic urethane polymer product that offers ultra-low VOC, is user friendly, stain resistant, and cures to a hard resilient finish. Kemiko Stone Tone Sealer II is supplied in clear gloss and clear natural looking flat to satin sheen, and is non-yellowing when subjected to exterior atmospheric exposure.

### Applications

**KEMIKO Stone Tone Sealer II** is applied to properly prepared concrete, plaster, wood, and metals. It is used as a resilient protective finish coat over faux finishes, Kemiko Acid Stains, and other topcoats for added UV resistance, abrasion resistance, and washability. Typical applications include residential and commercial concrete floors, and other floor surfaces requiring additional protection. Kemiko Stone Tone Sealer II is an excellent replacement product for high VOC lacquers, acrylics and varnishes and quickly cures to a hard resilient film with excellent properties.

## KEMIKO Easy Shine mop on Wax

### Description

**Kemiko Easy Shine** is a low-VOC, user-friendly, waterborne acrylic polymer wax for protecting and maintaining sealed concrete floors in gloss or satin.

### Applications

**Kemiko Easy Shine** is a maintenance wax applied over properly cured Stone Tone Sealer II, Kemiko 100% solids and water based epoxies, Kemiko SS2700 Polyurethane and SS3300 Polyaspartic. Applications include grocery stores, restaurants, showroom floors, walkways and many other interior surfaces.





### KEMIKO Sta-Natural Sealer

#### Description

**KEMIKO Sta-Natural Sealer** is a 0-VOC, user friendly, waterborne silane/siloxane emulsion for sealing Kemiko Stone Tone stained concrete and other cementitious substrates. Sta-Natural Sealer is a water viscosity, single component product that is designed to repel water, reduce efflorescence and frost damage, allow substrate to breathe, has very little or no odor, contains no solvents, and preserves stained concrete color. Sta-Natural Sealer is resistant to UV and high alkalinity exposure.

#### Applications

**KEMIKO Sta-Natural Sealer** is applied to properly stained or bare concrete, new and existing stucco finishes, fired clay brick, and many other cementitious mortars. Typical applications include commercial and residential driveways, walkways, pool decks, stamped and stained concrete, new architectural poured-in-place and pre-cast concrete, as well as many other horizontal and vertical above-grade exterior surfaces requiring additional protection. Excellent replacement product for high VOC solvent base water repellents and sealers, with excellent wetting properties.

### Kemiko (Sta-Crete) SS1202 100% Solids Epoxy

#### Description

**Kemiko (Sta-Crete) SS1202** is a 100% solids, low viscosity, 0-VOC, water clear epoxy coating that has excellent chemical resistance, is designed to be used with color quartz and selected aggregate, is user friendly and cures to a bluish free resilient high gloss film. Kemiko (Sta-Crete) SS1202 is USDA acceptable in food processing facilities cures overnight and is available in two speeds.

#### Applications

**Kemiko (Sta-Crete) SS1202** may be applied to properly prepared concrete floors subject to continuous foot traffic, showroom floors, warehouse floors, food & chemical processing facilities, hospitals kitchens, breweries, laboratories, gymnasiums and many other applications that require a high gloss resilient floor finish. The low viscosity mixture allows easy aggregate filling for slurry applications or aggregate broadcast systems for increased compressive strength and high impact service.

### Kemiko (Sta-Crete) SS1600 Water Extended Epoxy Coating

#### Description

**Kemiko (Sta-Crete) SS1600** is a quality abrasion resistant, amine cured, water extended epoxy coating that offers low-VOC, has excellent adhesion, surface tolerance, low odor, and is designed to be used as a thin resilient primer/finish. Kemiko (Sta-Crete) SS1600 has over 20 years successful case history and is USDA acceptable in food processing facilities, cures overnight and is available in various colors.

#### Applications

**Kemiko (Sta-Crete) SS1600** is applied to properly prepared cement and steel substrates subject to abrasion service, warehouse floors, garages, architectural applications, food and chemical processing facilities, hospitals and other applications requiring a cost-effective surface tolerant general maintenance primer/finish.

LOCATION	APPEARANCE PATHS	STEP 1 FLOOR PREPARATION	STEP 2 DECORATION	STEP 3 RESIDUE REMOVAL	STEP 4 PROTECTION COAT	STEP 5 TOP COAT	STEP 6 WAX REMOVAL
INTERIOR	RICH LUSTER PATH	NEUTRA CLEAN	KEMIKO STAIN	NEUTRA CLEAN	STONE TONE WAX (SOLVENT BASE)		
INTERIOR	RICH LUSTER PATH	NEUTRA CLEAN	KEMIKO STAIN	NEUTRA CLEAN	STONE TONE WAX II (WATER BASE)		
INTERIOR	GLOSSY OR MATTE	NEUTRA CLEAN	KEMIKO STAIN	NEUTRA CLEAN	STONE TONE SEALER II	EASY SHINE FINISH	EASY STRIP
** INTERIOR	COMMERCIAL PATH	NEUTRA CLEAN	KEMIKO STAIN	NEUTRA CLEAN	SS1600 EPOXY	EASY SHINE FINISH	EASY STRIP
EXTERIOR	NATURAL FINISH	NEUTRA CLEAN	KEMIKO STAIN	NEUTRA CLEAN	STA NATURAL		
EXTERIOR	GLOSS OR MATTE	NEUTRA CLEAN	KEMIKO STAIN	NEUTRA CLEAN	STONE TONE SEALER II		
** EXTERIOR	COMMERCIAL PATH	NEUTRA CLEAN	KEMIKO STAIN	NEUTRA CLEAN	SS3300 POLYASPARTIC		
** EXTERIOR	COMMERCIAL PATH	NEUTRA CLEAN	KEMIKO STAIN	NEUTRA CLEAN	SS2700 POLYASPARTIC		

\*\* Path to be followed only by professional applicators.

## KEMIKO/Sta-Crete Standard Colors

Light Gray

Diego Blue

Beige

Whisper Gray

Bernard Tan

Navajo White

Gray

Colors are approximations.  
Results may vary.



### **KEMIKO (Sta-Crete) SS2700 Waterborne Aliphatic Polyurethane Sealer**

#### *Description*

**KEMIKO (Sta-Crete) SS2700 Aliphatic Polyurethane** is a waterborne, universal, high solids, two component product that offers 0-VOC, UV resistance, good chemical resistance, excellent abrasion resistance, is user friendly, and cures to a very durable finish. KEMIKO (Sta-Crete) SS2700 is available in standard colors as well as clear. When subjected to UV exposure, KEMIKO (Sta-Crete) SS2700 has a temporary amber cast.

#### *Applications*

**KEMIKO (Sta-Crete) SS2700** may be applied to properly prepared concrete, plaster, wood, FRP, GFRC, and metals. It is utilized as a resilient protective finish coat over KEMIKO water based epoxies for optimum corrosion resistance. Typical applications include hospital walls and floors, commercial concrete floors, facades, steel and concrete storage tank exteriors, steel and concrete bridges, pump equipment, and many other surfaces requiring abrasion resistance, graffiti resistance, color retention, and chemical resistance.

### **KEMIKO (Sta-Crete) SS3300 100% Solids Polyaspartic**

#### *Description*

**KEMIKO (Sta-Crete) SS3300** is a 100% solids two component polyaspartic that exhibits excellent adhesion, UV resistance, abrasion resistance, chemical resistance, is 0-VOC and has rapid setting properties. It may be used as a decorative or industrial environment basecoat and topcoat for exterior concrete and carbon steel substrates. KEMIKO (Sta-Crete) SS3300 is low odor and utilizes the best available 100% solids polyaspartic technology for atmospheric and chemical exposure.

#### *Applications*

**KEMIKO (Sta-Crete) SS3300** is applied to properly prepared and prime coated concrete and steel for use in food processing plants, water treatment facilities, warehouse and showroom floors, airport maintenance facilities, parking deck garages, chemical containment, exterior concrete and steel tanks, pipelines and many other service areas which require a resilient, chemical resistant, quick curing protective coating. It may also be used for incidental food contact applications.

### **KEMIKO (Sta-Crete) SS3500 100% Solids Pigmented Epoxy**

#### *Description*

**KEMIKO (Sta-Crete) SS3500 100% Solids Pigmented Epoxy** is a two component, abrasion resistant epoxy coating that offers 0-VOC, excellent adhesion to steel and concrete, is user friendly and cures to a very hard resilient high-gloss film. It is non-blushing in high humidity, cures overnight and is available in many colors.

#### *Applications*

**KEMIKO (Sta-Crete) SS3500 100% Solids Pigmented Epoxy** may be applied to properly prepared concrete, metals and utilized as a resilient protective coating for chemical containment, abrasion resistance and as a complete 0-VOC exterior coating system when coated with KEMIKO (Sta-Crete) SS2700 Aliphatic Urethane for optimum color and gloss retention. Typical applications include hospital and food processing floors, petrochemical & chemical secondary containment, warehouse flooring, and showroom floors.

### **KEMIKO (Sta-Crete) SS3700 Water Extended High Gloss Epoxy Coating**

#### *Description*

**KEMIKO (Sta-Crete) SS3700** is a high gloss, quick dry amine cured, water extended epoxy coating that offers excellent adhesion, abrasion resistance and low odor. It is designed to be used as a thin resilient primer finish. KEMIKO (Sta-Crete) SS3700 can be applied on concrete walls, steel, wood, and plaster surfaces. It has been used successfully for over 10 years, is USDA acceptable in food processing facilities, is recoatable in 1-2 hours, and is available in various colors, as well as clear.

#### *Applications*

**KEMIKO (Sta-Crete) SS3700** is applied to properly prepared concrete and steel substrates subject to abrasion service, architectural applications, food and chemical processing facilities, hospitals, water and wastewater treatment facilities, and many other applications that require a cost-effective and surface tolerant primer/finish.

### **KEMIKO (Sta-Crete) SS3800 Water Extended Quick Dry High Gloss Epoxy Coating**

#### *Description*

**KEMIKO (Sta-Crete) SS3800** is a high gloss, ultra low VOC, quick dry, water extended epoxy coating that offers excellent adhesion and low odor. It was designed to be used as a thin film resilient primer finish. It is recoatable in 1-2 hours and is available in clear and various colors.

#### *Applications*

**KEMIKO (Sta-Crete) SS3800** may be applied to properly prepared cement and steel substrates subject to abrasion service, architectural applications, food and chemical processing facilities, hospitals, water and wastewater treatment facilities and many other applications that require a cost-effective surface tolerant general maintenance primer/finish.

**Contact us for your nearest Kemiko Stain Dealer**

**Phone: 800-875-4596 • Email: [epmar@quakerchem.com](mailto:epmar@quakerchem.com) • [www.kemiko.com](http://www.kemiko.com) • [www.epmar.com](http://www.epmar.com)**