



Parts

- A) Headrail — Steel
- B) Pinion Rod (Tilt Rod) — Hexagonal
- C) Headrail End Caps (Clear)
- D) Cord Lock
- E) Wand Tilter
- F) Tape Drum (Ladder Drum)
- G) Tape Drum Support (Cradle)
- H) Hidden Installation Bracket
- I) Wand — Clear Hexagonal
- J) Cord Ladder
- K) Lift Cord 1.4mm

- L) Cord Tassels
- M) Bottomrail Plugs
- N) Bottomrail — C Shape
- O) Bottomrail End Caps
- P) Slats
- Q) Hold Down Brackets — Optional

System Features:

- Integrated Headrail with Light Blocking Lip
- Snap-in Hidden Installation Brackets
- Heavy Duty Metal and Plastic Components
- Wand Tilter has a clutch mechanism preventing over-rotation and repairs

Blind Options:

- Mariak Elite Mini-Blind — 1 1/2" x 1" Headrail with 6-Gauge Aluminum Slats
- Mariak Elite Plus Mini-Blind — 1 1/2" x 1" Headrail with 8-Gauge Aluminum Slats

Headrail:

- Polyester baked enamel — color coordinated
- Phosphate treated steel — 1 1/2" x 1" high
- Wall thickness — 0.024" (before paint)



Bottomrail: (Color Coordinated)

- Steel — C shape
- Phosphate treated steel
- Wall thickness 0.024" (before paint)
- Clear plastic end caps

Tilt Controls:



Wand Tilt Option

- The tilt mechanism features a clutch that prevents over-rotation and repairs
- The worm and gear arrangement is entirely enclosed inside an acetal thermoplastic housing

Control Locations: (Restrictions may apply)

- Standard: Tilter — Left / Lift Cords — Right
- Reverse: Tilter — Right / Lift Cords — Left
- Same Left: Tilter — Left / Lift Cords — Left
- Same Right: Tilter — Right / Lift Cords — Right



Lift Control (Cord Lock):

- Snap-in design incorporates a stainless steel wear guard over which cords pass
- Incorporates a "Crash Proof" safety feature that locks the blind automatically upon release of cords

Other Headrail Channel Hardware:

- Headrail components are made of a combination of metal and low friction acetal thermoplastics
- Snap-in design of components allows for quick and easy repair if necessary



Cord Ladder: (Color Coordinated)

- Polyester braided cord ladders are designed to ensure proper control with adequate overlap of slats when in the closed position

Cord Ladder Spacing:

- Maximum spacing between rout holes = 20"
- Options:
 - Builder Ladder: 22.5mm (13.5 Slats/ft.)
 - Contract Ladder: 21.5mm (14.2 Slats/ft.)
 - Classic Ladder: 19.5mm (15.7 Slats/ft.)
 - Privacy Ladder: 18.0mm (16.9 Slats/ft.)
- Privacy Ladder features an offset route hole that provides for increased light blocking.



Lift Cords: (Color Coordinated)

- 1.4mm Polyester braided cords designed for lifting and lowering the blind

Mounting Hardware:

- Hidden installation brackets
- Center supports on blinds wider than 60"
- Extension brackets (when requested)
- Hold down brackets (when requested)

Size Recommendations:

- Minimum Width — 9" Center Tilt (13" Standard Controls)
- Minimum Drop — 9"
- Maximum Width — 142"
- Maximum Drop — 144"

The sizes listed above are merely recommendations. Blinds may be ordered larger if required. Optional 2 or 3 blinds on a single headrail are available as well.

Slats:

- 5000 series magnesium aluminum alloy
 - Includes recycled aluminum materials
 - Nominally 1" wide .0055" ± .0003" thick
 - Prior to coating the thickness of the slat is nominally .0060"