

Parts:

- A) Headrail — Steel
- B) Pinion Rod (Tilt Rod) — Hexagonal
- C) Cord Lock
- D) Wand Tilter
- E) Tape Drum (Ladder Drum)
- F) Tape Drum Support (Cradle)
- G) Installation Bracket
- H) Wand — Clear Hexagonal
- I) Cord Ladder
- J) Lift Cord 1.4mm
- K) Cord Tassels
- L) Bottomrail Plugs

- M) Bottomrail End Caps
- N) Slats
- O) Bottomrail — Rectangular


System Features:

- Color Coordinated Headrail
- Installation Brackets
- Heavy Metal and Plastic Components
- Wand tilter has a clutch mechanism preventing over-rotating and repairs



Blind Options:

- Fauxwood Poly Vinyl Chloride (PVC) 1" Flat
- Basswood 1" Flat



Headrail:


- Polyester baked enamel — color coordinated
- Phosphate treated steel — 1 1/2" x 1" high
- Wall thickness — 0.024" (before paint)



Bottomrail: *(Color Coordinated)*

- Fauxwood Rectangular Bottomrail — Extruded PVC
- Basswood Rectangular Bottomrail — 100% Basswood

Tilt Controls:




Cord Tilt Option

- The tilt mechanism features a clutch that prevents over-rotation and repairs
- The worm and gear arrangement is entirely enclosed inside an acetal thermoplastic housing

Control Locations: *(Restrictions may apply)*

- Standard: Tilter — Left / Lift Cords — Right
- Reverse: Tilter — Right / Lift Cords — Left
- Same Left: Tilter — Left / Lift Cords — Left
- Same Right: Tilter — Right / Lift Cords — Right



Lift Control (Cord Lock):

- Snap-in design incorporates a stainless steel wear guard over which cords pass
- Incorporates "Crash Proof" safety feature that locks the blind automatically upon release of cords

Other Headrail Channel Hardware:

- Headrail components are made of low friction acetal thermoplastics
- Snap-in design of components allows for quick and easy repair if necessary



Cord Ladder: *(Color Coordinated)*

- Polyester braided cord ladders are designed to ensure proper control with adequate overlap of slats when in the closed position

Cord Ladder Spacing:

- Maximum spacing between rout holes:
 - Fauxwood = 11"
 - Basswood = 20"
- Options:
 - Classic Ladder: 19.5mm (15.7 slats/ft.)



Lift Cords: *(Color Coordinated)*

- 1.4mm Polyester braided cords designed for lifting and lowering the blind

Mounting Hardware:

- End Mounted installation brackets
- Center supports on blinds wider than 60"
- Extension brackets (when requested)
- Hold down brackets (when requested)



Size Recommendations:

- Minimum Width — 9"
- Minimum Drop — 9"
- Maximum Width — 96"
- Maximum Drop — 96"

The sizes listed above are merely recommendations. Blinds may be ordered larger if required. Optional 2 or 3 blinds on a single headrail are available as well.

Slats:

- Fauxwood
 - PVC Resin (base material), Methyltin Mercaptide (stabilizer), Calcium Carbonate (filler), Titanium Dioxide (UV inhibitor), Methyl Methacrylate (lubricant), Ethylenebis (lubricant), Octabenzene (UV inhibitor)
 - Lead Free
 - N.F.P.A. 701
- Basswood
 - 100% Basswood