

Parts:

- A) Low Profile Headrail — Steel
- B) Pinion Rod (Tilt Rod) — Square
- C) Pinion Rod Cap
- D) Tape Drum Support (Cradle)
- E) Tape Drum (Ladder Drum)
- F) Cord Lock
- G) Cord Tilter
- H) End Stiffener
- I) Cord Ladder
- J) Lift Cord 1.8mm
- K) Bottomrail — Trapezoid

- L) Cord Tassels
- M) Top Slat Clip
- N) Slats
- O) Bottomrail Plugs
- P) Cord Grommets
- Q) 3-1/4" Royal Valance
- R) Hold Down Brackets
- S) Hold Down Pins
- T) Center Support Brackets
- U) Box Style Installation Brackets

System Features:

- Hidden 1-piece plastic valance clip

Blind (Material) Options:

- Fauxwood — Poly Vinyl Chloride (PVC) 2"
- 500 Hours UV Rated



Headrail:

- Polyester baked enamel — color coordinated
- Phosphate treated steel — 2" wide x 1-1/2" high
- Wall thickness — 0.018" (before paint)

Valance Options: (Color Coordinated)

- 3-1/4" Royal Valance for Fauxwood
- Inside Mount Optional Clip-On Returns — 1-1/4" Outside Measurement Standard
- Outside Mount Optional Clip-On Returns — 3-1/2" Outside Measurement Upon Request
- Hidden 1-part plastic valance clip

Bottomrail: (Color Coordinated)

- Trapezoid shape for tight slat closure

Tilt Controls:




Cord Tilt Option

- Acetal thermoplastic wheel to rotate smoothly and with minimal noise

Control Locations: (Restrictions may apply)

- Standard: Tilter — Left / Lift Cords — Right



Lift Control (Cord Lock):

- Snap-in design incorporates a stainless steel wear guard over which cords pass
- Incorporates "Crash Proof" safety feature that locks the blind automatically upon release of cords

Other Headrail Channel Hardware:

- Headrail *components* are made of low friction acetal Thermoplastics or Polypropylene Plastic
- Snap-in design of components allows for quick and easy repair if necessary



Cord Ladder: (Color Coordinated)

- Polyester braided cord ladders are designed to ensure proper control with adequate overlap of slats when in the closed position
- Options include:
 - Standard
- Maximum spacing between route holes:
 - Fauxwood = 11"



Lift Cords: (Color Coordinated)

- 1.8mm Polyester braided cords designed for lifting and lowering the blind

Mounting Hardware:

- Universal box brackets (color coordinated)
- Center supports on blinds wider than 60"
- Extension brackets (when requested)
- Hold down brackets (when requested)



Size Recommendations:

- Minimum Width — 9"
- Minimum Drop — 9"
- Maximum Width — 96"
- Maximum Drop — 96"

Slats:

- Fauxwood
 - PVC Resin (base material), Methyltin Mercaptide (stabilizer), Calcium Carbonate (filler), Titanium Dioxide (UV inhibitor), Methyl Methacrylate (lubricant), Ethylenebis (lubricant), Octabenzene (UV inhibitor)
 - Lead Free
 - N.F.P.A. 701

1-Year Warranty against Manufacturer Defects