

Parts:

- | | | | |
|----|----------------------|----|--------------------|
| A) | Headrail | J) | Weight |
| B) | Headrail End Cap | K) | Bottomrail |
| C) | Installation Bracket | L) | Bottomrail End Cap |
| D) | Bracket Screw | M) | Cord Lock |
| E) | Cord Guide | N) | Stop Ball |
| F) | Fabric Insert | O) | Pull Cord |
| G) | Cellular Fabric | P) | Tassel |
| H) | Fixed Button | Q) | Tie Down |
| I) | Cord | | |



Headrail: *(Color Coordinated)*

- Material — Aluminum 6063-T5
- Material thickness — 0.050"
- Finish — Powder coat



Headrail End Caps: *(Color Coordinated)*

- Material — PVC



Bottomrail: *(Color Coordinated)*

- Material — Aluminum 6063-T5
- Material thickness 0.045"
- Clear plastic end caps




Bottomrail End Caps: *(Color Coordinated)*

- Material — PVC



Installation Brackets:

- Material — CRS
- Finish — Zinc-plated



Cellular Fabric:

- Material — spun lace, non-woven fabric. 100% polyester.



Cord Lock:

- Snap-on design incorporates a stainless steel wear guard over which cord passes with durable plastic enclosure
- Safety locking mechanism locks the blind automatically upon release of cords.

Control Locations: *(Restrictions May Apply)*

- Standard: Tilter — Left/ Lift Cords — Right
- Reverse: Tilter — Right/ Lift Cords — Left
- Same Left: Tilter — Left/ Lift Cords — Left
- Same Right: Tilter — Right/ Lift Cords — Right

Fixed Button:

- Material — ABS

Weight:

- Material — CRS
- Thickness — 0.125"
- Finish — Zinc-plated



Lift Cords:

- 0.9 mm Polyester braided cords designed for lifting and lowering the blind

Size Recommendations:

- Minimum Width — 9"
- Minimum Drop — 9"
- Maximum Width — 96"
- Maximum Drop — 96"

The sizes listed above are merely recommendations. Blinds may be ordered larger if required. Optional 2 or 3 blinds on a single headrail are available as well.