



# catalog of appliances

For more information on GE appliances, visit [geappliances.com](http://geappliances.com).



imagination at work

# GE Profile™, GE Café™ and GE® side-by-side refrigerators



## PSCS3RGX

GE Profile counter-depth 23.3 cu. ft. refrigerator

- ClimateKeeper™ system
- Integrated dispenser with LED lighting and UltraFlow<sub>100</sub>
- Quick Ice™ setting
- TurboCool™ setting
- Integrated Ice™ system
- In-the-door beverage rack



## CSCP5UGX

GE Café counter-depth 24.6 cu. ft. refrigerator

- Counter-depth configuration
- GE Café stainless steel handles with stainless sides
- ClimateKeeper2™ system
- External controls with actual-temperature display and UltraFlow<sub>100</sub>
- ExpressChill™
- Slide 'n Store™ freezer baskets



## GSH25JSX

GE 25.0 cu. ft. refrigerator

- External temperature controls with child lock and UltraFlow<sub>64</sub>
- Adjustable-humidity crisper drawers
- Adjustable-temperature deli drawer
- Snack drawer
- Adjustable gallon door bins



## GSS23WST

GE 23.1 cu. ft. refrigerator

- External controls with actual-temperature display and UltraFlow<sub>64</sub>
- Integrated shelf support system
- Adjustable-humidity crisper drawer
- Adjustable-temperature deli drawer
- Snack drawer



# GE Profile and GE bottom-freezer refrigerators



## PFSS2MIY

GE Profile 22.2 cu. ft. French-door refrigerator

- Stainless steel doors with top and bottom bevels
- Internal water dispenser with GE water filtration
- ClimateKeeper system
- Factory-installed icemaker with water filtration system
- BrightSpace™ interior with GE Reveal® lighting
- Freshness Center™



## GBC12IAX

GE 11.6 cu. ft. full-door refrigerator

- 24 inches wide
- Upfront electronic temperature controls
- Crisper drawers
- Adjustable glass shelves
- ClearLook™ door bins
- ExpressFreeze
- NeverClean™ condenser
- Deluxe quiet design

# GE top-freezer refrigerators



## GTK18ICX

GE 18.0 cu. ft. refrigerator

- Factory-installed icemaker
- Adjustable glass shelves
- Upfront temperature controls
- Crisper drawers
- Gallon door bins
- Snack drawer
- Wire freezer shelf



## GTS18ICS

GE 18.0 cu. ft. refrigerator

- Factory-installed icemaker
- Adjustable glass shelves
- Upfront temperature controls
- Crisper drawers
- Gallon door bins
- Snack drawer
- Wire freezer shelf



## GE top-freezer refrigerators



Icemaker model  
**GTS18HCS**  
GE 18.2 cu. ft. refrigerator

- Adjustable glass shelves
- Upfront temperature controls
- Factory-installed icemaker
- Clear vegetable/fruit crisper
- Gallon door storage
- Can storage shelf
- NeverClean™ condenser
- Deluxe quiet design



Icemaker model  
**GTH17BBT**  
GE 16.6 cu. ft. refrigerator

- Upfront temperature controls
- Gallon door storage
- Crisper drawers
- Adjustable wire shelves
- NeverClean condenser
- Deluxe quiet design



Icemaker models  
**GTH18DCX**  
GE 18.0 cu. ft. refrigerator

- Upfront temperature controls
- Adjustable shelves
- Factory-installed icemaker
- Crisper drawers
- Spillproof freezer floor
- Gallon door storage
- NeverClean condenser

**GTS18DCP** (not shown)  
GE 18.0 cu. ft. refrigerator  
Similar features and appearance as GTH18DCX, except not ENERGY STAR® qualified.

Non-icemaker models

**GTH18DBX** (not shown)  
GE 18.0 cu. ft. refrigerator  
Similar features and appearance as GTH18DCX, except equipped for optional automatic icemaker.

**GTS18DBP** (not shown)  
GE 18.0 cu. ft. refrigerator  
Similar features and appearance as GTS18DCP, except equipped for optional automatic icemaker; not ENERGY STAR qualified.



Icemaker model  
**GTS18CCS**  
GE 18.2 cu. ft. refrigerator

- Upfront temperature controls
- Factory-installed icemaker
- Gallon door storage
- Can storage door shelf
- Crisper drawers
- Adjustable wire shelves
- NeverClean condenser

Non-icemaker model

**GTS18CBS** (not shown)  
GE 18.2 cu. ft. refrigerator  
Similar features as GTS18CCS, except equipped for optional automatic icemaker.

## GE Profile and GE slide-in electric ranges



**PS968**  
GE Profile 30" CleanDesign™ convection range

- PreciseAir™ convection system
- Convection bake (single- and multi-rack)
- Convection roast
- Self-clean oven
- Self-clean heavy-duty oven racks
- 12"/9"/6" tri-ring element
- Bridge element



**PS900\*\***  
GE Profile 30" CleanDesign electric range

- Self-clean oven
- 6"/9" dual element
- Super-large oven capacity
- TrueTemp™ oven system
- Ribbon heating elements
- Ceramic glass cooktop
- Optional backguard kit (JXS37) and other kits available at additional cost



**JSS28**  
GE 30" electric coil range

- Standard-clean oven
- Super-large oven capacity
- Electronic oven controls



\*ADA compliant based on Uniform Federal Accessibility Standards

\*\*Stainless steel model features a sculptured storage drawer handle. White, bisque and black models feature a recessed storage drawer handle.

# GE® free-standing electric ranges



**JBP66SM**  
GE 30" range

- Self-clean oven
- Super-large 5.3 cu. ft. oven capacity
- TrueTemp™ oven system
- 9"/12" dual element
- Ceramic glass cooktop
- QuickSet IV oven controls
- Big hearth-shaped window



**JB640**  
GE 30" range

- Self-clean oven
- Super-large 5.3 cu. ft. oven capacity
- 12" element
- TrueTemp oven system
- QuickSet III oven controls
- Ceramic glass cooktop
- Big hearth-shaped window



**JBP35**  
GE 30" range

- Self-clean oven
- Super-large 5.3 cu. ft. oven capacity
- TrueTemp oven system
- QuickSet IV oven controls
- Coil heating elements
- Big hearth-shaped window
- Self-clean heavy-duty oven racks and drip bowls



**JBP24DM**  
GE 30" range

- Self-clean oven
- Super-large 5.3 cu. ft. oven capacity
- QuickSet III oven controls
- Coil heating elements
- Big hearth-shaped window
- Dual element bake



**JBS27**  
GE 30" range

- Standard-clean oven
- Extra-large 5.0 cu. ft. oven capacity
- Coil heating elements
- Small hearth-shaped window
- Electronic clock and timer
- Frameless glass oven door



**JBS15**  
GE 30" range



- Standard-clean oven
- Upfront controls
- Super-large oven capacity
- Coil heating elements
- ClearView™ window
- Dual element bake



## GE Profile™ and GE free-standing gas ranges



### PGB900

#### GE Profile 30" gas range

- Self-clean oven
- Super-large 5.0 cu. ft. oven capacity
- Deep-recessed cooktop
- PowerBoil™ 15,000 BTU burner
- Precise Simmer burner
- Cast-iron grates
- QuickSet V oven controls



### JGBP33DEM

#### GE 30" range

- Extra-large, self-clean oven
- TrueTemp oven system
- QuickSet IV oven controls
- Precise Simmer burner
- 13,000 BTU high-output burner
- Cast-iron grates
- Sealed cooktop burners



### JGBP28DEM

#### GE 30" gas range

- Extra-large, self-clean oven
- TrueTemp oven system
- QuickSet III oven controls
- (2) 12,000 BTU high-output burner
- Cast-iron grates
- Precise Simmer burner



### JGBS23

#### GE 30" range

- Extra-large oven capacity
- Standard-clean oven
- Precise Simmer burner
- 12,000 BTU high-output burner
- Deluxe grates
- Big hearth-shaped window



### JGBS07DEM

#### GE 30" range

- Extra-large, standard-clean oven
- All-purpose burners
- Standard grates
- Porcelain oven door
- ClearView window
- Two oven racks



## GE Profile and GE built-in cooktops



### JGP940

#### GE Profile 30" gas-on-glass cooktop

- Gas-on-glass cooktop
- Sealed cooktop burners
- PowerBoil 15,000 BTU burner
- Precise Simmer burner
- Continuous grates
- Dishwasher-safe grates and knobs
- Control lock capability
- Heavy-duty knobs on stainless steel model



### JP346

#### GE 30" electric CleanDesign™ cooktop

- Ceramic-glass cooktop
- Ribbon heating elements
- Melt setting
- 8" PowerBoil element
- Frameless design
- Hot surface indicator light
- Dishwasher-safe knobs



## GE® hoods



### JV348/347

#### GE 30" deluxe hood

- Convertible venting—vented/non-vented
- Vertical and rear exhaust
- Variable three-speed fan control
- Cooktop light
- Removable grease filter
- Round or rectangular ducting



### JN327H

#### GE 30" standard hood

- Non-vented
- Vertical and rear exhaust
- Variable two-speed fan control
- Cooktop light
- Removable grease filter
- Round or rectangular ducting

## GE Profile Advantium® above-the-cooktop oven



### SCA1001/1000

#### GE Profile™ Advantium 120V above-the-cooktop oven

- Speedcook technology—cooks up to 4 times faster than a conventional oven
- 4 ovens in 1 to meet your cooking needs: Speedcook, Traditional oven, Warming and Sensor Microwave
- Optimizes cook time for consistent results
- Saves valuable time by eliminating preheating
- Over 100 preprogrammed recipes
- Allows up to 30 customized recipes to be saved

## GE Profile and GE microwave ovens



### JVM1850/JNM1851\*\*

#### GE Spacemaker® 1.8 cu. ft. sensor oven

- 1.8 cu. ft. capacity, 1100 watts\*\*\*
- CircuWave™ 1100 cooking system
- Sensor cooking controls
- 1-lb. Quick Defrost
- 14-1/4" recessed turntable with On/Off
- Two removable oven racks



### JVM1750DM/SM

#### GE Spacemaker 1.7 cu. ft. sensor oven

- 1.7 cu. ft. capacity, 1000 watts\*\*\*
- Sensor cooking controls
- Auto and Time Defrost
- Turntable On/Off
- Two-speed, 300-CFM venting system
- Removable two position oven rack
- Full-view cooktop lighting



### JVM1740

#### GE Spacemaker 1.7 cu. ft. oven

- 1.7 cu. ft. capacity, 1000 watts\*\*\*
- Convenience cooking controls
- Auto and Time Defrost
- Turntable On/Off
- Two-speed, 300-CFM venting system
- Removable oven rack
- Full-view cooktop lighting



### JVM1540/JNM1541\*\*

#### GE Spacemaker 1.5 cu. ft. oven

- 1.5 cu. ft. capacity, 950 watts\*\*\*
- Convenience cooking controls
- Auto and Time Defrost
- Turntable On/Off
- Two-speed, 300-CFM venting system
- Removable oven rack



Model shown with optional trim kit JX827SMSS

### PEM31

#### GE Profile 1.0 cu. ft. sensor oven

- 1.0 cu. ft. capacity, 800 watts\*\*\*
- Optional built-in trim kit†
- Optional hanging kit††
- Sensor cooking controls
- Auto and Time Defrost
- Turntable On/Off
- Control lockout



Model shown with installed hanging kit JXA019K



\*ADA compliant based on Uniform Accessibility Standards.

\*\*Non-vented model.

\*\*\*IEC-705 Test Procedure. †Optional trim kits available in 27" and 30" configurations sold separately.

††Optional undercabinet mounting kit sold separately.

## GE Profile and GE dishwashers



### PDW7880P

GE Profile built-in dishwasher with front controls

- Four-position adjustable upper rack
- 4 utility shelves with StemSafe™
- 2 sets of fold-down tines in lower rack
- CleanSensor™
- Up to 16-place setting capacity nylon racking
- Countdown display with 1-9-hour Delay Start
- Glasses selection



### GLDA696P

GE stainless interior dishwasher with front controls

- Bright annealed stainless steel interior
- Low-profile installation capable
- 5 wash levels
- 2-digit countdown display with 2/4/8-hour Delay Start
- Electronic controls with 4 cycles/6 options
- Two utility shelves in upper rack with 1 StemSafe
- Nylon racks



### GSD2100R/2101R\*\*

GE built-in dishwasher

- 4-level PowerScrub™ wash system
- Two-stage filtration with ExtraFine™ filter
- 5 cycles/2 options
- Short wash
- HotStart™ option
- Piranha™ hard-food disposer



## GE washers and dryers



### WCVH6800J

GE 4.0 IEC\*\*\* cu. ft. king-size capacity frontload washer

- Dark chrome trim and knob (featured on Vermillion red only)
- HydroHeater™ internal water heater
- Load-sensing adaptive fill
- 5 with sanitize wash/rinse temperatures
- 1100-RPM spin speed
- QuietBalance™ II suspension system



### DCVH680EJ/GJ

GE 7.0 cu. ft. super capacity frontload dryer

- Dark chrome trim and knob (featured on Vermillion red only)
- Sensor Dry Plus™
- 5 custom heat selections
- Multiple dry cycles
- My Cycle
- Cycle countdown display with LED indicators
- Deluxe dryer rack
- Delay start up to 18 hours



### WCRE6270K

GE 4.1 IEC\*\*\* cu. ft. colossal capacity high-efficiency topload washer

- HydroWave with Infusor™ wash system
- RainShower™ rinse system
- 700-RPM spin speed
- Stainless steel basket
- Rotary electronic controls with cycle status lights



### WCSR4170G (not shown)

GE 3.2 cu. ft. super capacity plus washer

- HydroWave™ wash system
- Rotary electromechanical controls
- ExtraAction™ ribbed basket
- 4 wash/spin speed combinations
- 17 wash cycles
- Bleach and fabric softener dispensers
- 4 water levels



### DRSR483EG/GG

GE 7.0 cu. ft. super capacity dryer

- Stainless steel drum
- Auto Dry™
- Wrinkle care extended tumble
- 8 dry cycles
- Variable end-of-cycle signal
- Pairs with WCRE6270K

### DJXR433EG/GG (not shown)

GE 6.0 cu. ft. extra-large capacity dryer

- Auto Dry
- Rotary electromechanical controls
- DuraDrum™ interior
- 4 heat selections
- 3 dry cycles
- Quiet-by-Design™

\*ADA compliant based on Uniform Federal Accessibility Standards  
\*\*Power cord attached

\*\*\*Washes equivalent amount of clothes as a similar cu. ft. agitator machine per IEC 60456 Edition 4.

## GE® unitized washers and dryers



**WSM2700H** Electric  
**WSM2780H** Gas  
 GE full-size 27" unitized  
 washer/dryer

- 2.7 cu. ft. extra-large capacity (washer)
- 5.5 cu. ft. extra-large capacity (dryer)
- 1 wash/spin speed combination
- 3 wash cycles
- 3 wash/rinse temperatures
- 3 water levels
- Electromechanical controls



**WSM2420D** Electric  
**WSM2480D** Gas  
 GE 24" unitized  
 washer/dryer

- 1.5 cu. ft. large capacity (washer)
- 3.4 cu. ft. large capacity (dryer)
- 2 wash/spin speed combinations
- 3 wash cycles
- 3 wash/rinse temperatures
- 3 water levels
- Electromechanical controls

## GE portable/stationary and commercial washers and dryers



**WSP1500J**  
 GE 24" 120V portable  
 topload washer

- 3.1 IEC\* cu. ft. extra-large capacity
- Stainless steel basket
- Electronic one-touch controls with LED readout
- Load sensing
- 14 wash cycles
- 3 wash/rinse temperatures

**WSP1500J**  
 Similar to the WSP1500J, except is a stationary model.



**DSKP333EC**  
 GE 120V  
 portable dryer

- 3.6 cu. ft. capacity
- 3 dry cycles
- 3 heat selections
- DuraDrum™ interior
- Quiet-by-Design™



**WNRD2050G**  
 GE non-coin  
 commercial washer

- 3.5 cu. ft. super capacity
- Stainless steel basket
- Electronic one-touch controls with LED readout
- 5 wash cycles
- 3 wash/spin speed combinations
- 3 wash/rinse temperatures
- Deluxe quiet

**DNCD450EG** Electric  
**DNCD450GG** Gas  
 GE non-coin  
 commercial dryer

- 7.0 cu. ft. super capacity
- Auto Dry™
- Electronic one-touch controls with LED readout
- Delicate (low heat) cycle
- DuraDrum interior
- 4 heat selections
- 5 dry cycles
- Hush quiet



## GE Profile™ counter-depth side-by-side refrigerator

	GE Profile
	PSCS3RGX PSCF3RGX
<b>Capacity</b>	
Total (cu. ft.)	23.3
Fresh food (cu. ft.)	14.75
Freezer (cu. ft.)	8.59
Shelf area (sq. ft.)	18.9
<b>Fresh food features</b>	
ClimateKeeper™ system	●
Multi-flow air system	●
Electronic sensors	●
Actual-temperature display	●
External controls	●
TurboCool™ setting	●
GE water filtration system	MSWF
UltraFlow dispenser	100
<b>Features</b>	
Crushed ice, cubes, water	●
Integrated design	●
Light	LED
Child lock and door alarm	●
Quick Ice™ feature	●
Water filter indicator light	●
Cabinet shelves	3 adj. glass
Slide-out, spillproof	2
QuickSpace™ shelf	●
Integrated shelf support system	●
Snugger™ clips	2
Freshness Center™ (3-stack drawer system)	●
Top drawer	Adj. temp.
Middle drawer	Adj. humidity
Bottom drawer	Sealed
ClearLook™ door bins	4 (3 adj.)
In-the-door beverage storage	Wire beverage rack
BrightSpace™ interior lighting	GE Reveal®
Quiet design	Premium
<b>Freezer features</b>	
Factory-installed icemaker	Integrated Ice™
Wire slide-out baskets	3
Wire cabinet shelves	3
Wire tilt-out door bin(s)	2 adj.
Door bin	1
BrightSpace interior lighting	GE Reveal
<b>Exterior</b>	
Color(s) available*	SS
Counter-depth configuration	No panel required
Door handles*	Sculptured stainless steel CM sculptured
Exterior design	Rounded doors High-gloss rounded doors
Textured steel door and case	Case only (gray)
Adjustable rollers	All
<b>Weights &amp; Dimensions</b>	
Height to top of hinge (in.)	69-5/8
Height to top of case (in.)	68-3/4
Case depth without door (in.)	23-7/8
Case depth less door handle (in.)	27-1/8
Case depth with door handle (in.)	29-5/8
Depth w/fresh food door open 90° (in.)	46
Width (in.)	35-3/4
Width w/door open 90° w/door handle (in.)	41-3/8
Air clearances	Each side (in.) 1/8 Top (in.) 1 Back (in.) 1/2
Approx. shipping wt. (lbs.)	360
Power/Rating	120V, 60Hz, 15Amps

\*Color(s) available: SS = Stainless steel, WW = White, CC = Bisque, BB = Black, CM = Color-Matched.

†If installed against a wall, allow clearance of 14" on freezer side to remove bin. Clearance required to remove fresh food full-size pan without disassembling is 18-5/8".

ALL MODELS AVAILABLE IN U.S. AND CANADA.

## GE Café™ counter-depth side-by-side refrigerator

	GE Café
	CSCPSUGX
<b>Counter-depth</b>	
Capacity	●
Total (cu. ft.)	24.6
Fresh food (cu. ft.)	15.3
Freezer (cu. ft.)	9.3
Shelf area (sq. ft.)	20.7
<b>Fresh food features</b>	
ClimateKeeper system	ClimateKeeper2
Multi-flow air system	●
Electronic sensors	●
Actual-temperature display	●
External controls	●
TurboCool setting	●
GE water filtration system	MSWF
<b>Features</b>	
Crushed ice, cubes, water	●
UltraFlow <sub>100</sub> dispenser	●
Light	●
Child lock and door alarm	●
Quick Ice feature	●
Water filter indicator light	●
Cabinet shelves	3 glass
Adjustable	3
Slide-out, spillproof	2
QuickSpace shelf	●
Integrated shelf support system	●
Snugger clips	2
Freshness Center (3-stack drawer system)	●
Top drawer	Adj. temp.
Middle drawer	Adj. humidity
Bottom drawer	ExpressChill™
ClearLook door bins	5 (4 adj.; 2 w/gallon storage)
In-the-door beverage storage	Wire beverage rack
BrightSpace interior lighting	GE Reveal
Quiet design	Premium
<b>Freezer features</b>	
FrostGuard™ technology	●
Integrated Ice system	●
Wire slide-out baskets	3 (2 full-extension)
Wire cabinet shelves	3
Wire tilt-out door bin(s)	2 adj.
Door bin	1
BrightSpace interior lighting	GE Reveal
<b>Exterior</b>	
Color(s) available*	SS
Door handles	GE Café stainless
Exterior design	Stainless
Textured steel case	Top only
Stainless steel side panels	●
Adjustable rollers	Front
<b>Weights &amp; Dimensions</b>	
Height to top of hinge (in.)	72-1/8
Height to top of case (in.)	71-5/8
Case depth without door (in.)†	23-7/8
Case depth less door handle (in.)†	27-1/8
Case depth with door handle (in.)†	29-3/4
Depth w/fresh food door open 90° (in.)†	46
Width (in.)	36
Width w/door open 90° w/door handle (in.)	41-5/8
Air clearances	Each side (in.) 1/8 Top (in.) 1 Back (in.) 1/2
Approximate shipping wt. (lbs.)	424
Power/Rating	120V, 60Hz, 15Amps

\*Color(s) available: SS = Stainless steel

†Water hook-up fits in back air clearance when calculating installation depth.

‡If installed against a wall, allow clearance of 14-1/4" on 25 cu. ft. on freezer side to remove ice bin. To remove fresh food pans, remove door bins. Clearances required to remove fresh food full-size pan without disassembling: 19" on 25 cu. ft. Allow additional space for any necessary leveling adjustments.

ALL MODELS AVAILABLE IN U.S. AND CANADA.

## GE side-by-side refrigerators

	GE "J" Series	GE "W" Series
	GSH25JSX GSL25JFX GSH25JFX	GSS23WST GSS23WGT
<b>ENERGY STAR® qualified</b>		
ADA compliant	●	●
<b>Capacity</b>		
Total (cu. ft.)	25.0	23.2
Fresh food (cu. ft.)	15.46	15.86
Freezer (cu. ft.)	9.56	7.26
Shelf area (sq. ft.)	22.9	20.5
<b>Fresh food features</b>		
Actual-temperature display	●	●
GE water filtration system	MWF	MWF
UltraFlow dispenser	64	64
<b>Features</b>		
Crushed ice, cubes, water	●	●
Light and child lock	●	●
Door alarm	●	●
Water filter indicator light	●	●
Cabinet shelves	3 glass	3 glass
Adjustable	2	3
Slide-out, spillproof	2	3
Integrated shelf support system	●	●
Snugger clips	2	2
Freshness Center	●	●
2-stack drawer system	●	●
Top drawer	Adj. humidity	1 adj. temp.
Bottom drawer	Adj. temp.	1 adj. humidity
Snack drawer	●	●
Door bins	4 (2 adj. with gallon storage)	4 (2 adj. with gallon storage)
Dairy compartment	●	●
Interior lighting	Dual	Dual
Quiet design	Deluxe	Deluxe
<b>Freezer features</b>		
FrostGuard technology	●	●
Factory-installed icemaker and bin	●	●
Wire cabinet shelves	4 (1 adj.)	4 (3 adj.)
Storage basket(s)	1 bin	1 slide-out
Door bins	5 shelves	5 shelves
Interior light	●	●
<b>Appearance</b>		
Color(s) available*	SS CleanSteel™ WW, CC, BB	SS WW, CC, BB
Door handles*	Stainless steel tubular Black CM	Stainless steel tubular CM
Exterior design	Rounded doors	Rounded doors
Textured steel case	Black Black	Black
Stain. steel side panel accessory (opt.)	●	●
Adjustable rollers	Front	Front
<b>Weights &amp; Dimensions</b>		
Height to top of hinge (in.)	69-3/4	69-1/2
Height to top of case (in.)	68-3/4	68-3/4
Case depth without door (in.)†	28	28
Case depth less door handle (in.)†	31-1/4	31-1/4
Case depth with door handle (in.)†	33-5/8	33-5/8
Depth w/fresh food door open 90° (in.)†	49-3/8	50-1/8
Width (in.)	35-3/4	32-3/4
Width w/door open 90° with door handle (in.)	38-1/4	37-3/4
Air clearances	Each side (in.) 1/8 Top (in.) 1 Back (in.) 1	1/8 1 1
Approx. shipping wt. (lbs.)	344	340
Power/Ratings	← 120V, 60Hz, 15Amps →	

\*Color(s) available: SS = Stainless steel, CleanSteel = Stainless appearance, WW = White, CC = Bisque, BB = Black, CM = Color-Matched.

†Water hookups fits in back air clearance when calculating installation depth. If installed against a wall, allow clearance of 10-3/4" on 20 cu. ft. and 22 cu. ft. models; 14-1/4" on 25 cu. ft. models on freezer side to remove bin.

‡Clearances required to remove fresh food full-size pan without disassembling: 13-1/2" on 20 cu. ft.; 15" on 22 cu. ft.; and 19" on 25 cu. ft.

Allow additional space for any necessary leveling adjustments.

ALL MODELS AVAILABLE IN U.S. AND CANADA.

## GE Profile™ bottom-freezer refrigerator

	GE Profile	
	PFS2MIY PFSF2MIY PFSW2MIY	
<b>ENERGY STAR® qualified</b>	●	
Stainless steel model	● / - / ●	
French-door model	●	
<b>Capacity</b>		
Total (cu. ft.)	22.2	
Fresh food (cu. ft.)	15.5	
Freezer (cu. ft.)	6.7	
Shelf area (sq. ft.)	27.7	
<b>Fresh food features</b>		
ClimateKeeper™ system	●	
Door alarm	●	
Internal electronic temperature controls	●	
TurboCool™ setting	●	
Cabinet shelves	4 glass	
Adjustable	4 split	
Slide-out	2	
Spillproof	3	
QuickSpace™ shelf	●	
Internal water dispenser	●	
GE water filtration	MWF	
Water filter indicator light	●	
Freshness Center™	●	
Crisper drawers	2 adj. humidity	
Snack drawer	1 adj. temp	
ClearLook™ adjustable gallon door bins	3	
Fixed door bins	2	
In-the-door beverage storage	ShelfSaver™ beverage rack	
Snuggler™ clips	2	
Dairy compartment	●	
BrightSpace™ interior lighting	GE Reveal®	
Quiet design	Premium	
<b>Freezer features</b>		
Factory-installed icemaker & bin	●	
FrostGuard™ technology	●	
Multi-level Slide 'n Store™ full-extension freezer baskets	2 f/w, 1 split	
BrightSpace interior lighting	GE Reveal®	
<b>Exterior</b>		
Color(s) available*	SS WW, BB SS	
Sculptured door handles	Stainless steel Color-matched	
Exterior design	Contoured w/top & bottom bevels Full-wrap contoured doors w/top & bottom bevels	
Textured steel case	Gray Color-matched Stainless wrapped	
Door	Stainless High-gloss Stainless	
Door stops	●	
Adjustable rollers	Front	
<b>Weights &amp; Dimensions</b>		
Height to top of hinge (in.)	68-1/2	
Height to top of case (in.)	67-3/4	
Case depth without door (in.)†	28-3/4	
Case depth less door handle (in.)†	33	
Case depth with door handle (in.)†	35-1/2	
Depth w/fresh food door open 90° (in.)†	46-5/8	
Width (in.)	32-3/4	
Width w/door open 90° w/door handle (in.)	40-5/8	
Each side (in.)	1/8	
Top (in.)	1	
Air clearances Back (in.)	3/4	
Approximate shipping wt. (lbs.)	315	
Power/Rating	120V, 60Hz, 15Amps	

\*Color(s) available: SS = Stainless steel, WW = White, CC = Bisque, BB = Black.  
†Water hook-up fits in back air clearance when calculating installation depth.

ALL MODELS AVAILABLE IN U.S. AND CANADA.

## GE® bottom-freezer refrigerator

	GE	
	GBC12IAXSS	
Stainless steel model	●	
<b>Capacity</b>		
Total (cu. ft.)	11.6	
Fresh food (cu. ft.)	7.3	
Freezer (cu. ft.)	4.2	
<b>Fresh food features</b>		
Internal electronic temperature controls	●	
Door alarm	●	
Cabinet shelves		
Adjustable	3 glass	
Spillproof	●	
ClearLook door bins	4	
Crisper drawer	●	
Fresh food interior lighting	●	
<b>Freezer features</b>		
ExpressFreeze	●	
Freezer door bins	2	
Freezer storage bins	3	
<b>Exterior</b>		
Color(s) available*	SS	
Door handles	Stainless	
Doors	Stainless	
Textured steel case	Case only (gray)	
Exterior design	Contoured w/ crown doors	
Door stops	●	
Choose left or right door opening	●	
<b>Weights &amp; Dimensions</b>		
Height to top of hinge (in.)	70-7/8	
Height to top of case (in.)	70-7/8	
Case depth without door (in.)	22	
Case depth less door handle (in.)	25-1/4	
Case depth with door handle (in.) E	26-1/2	
Width (in.)	23-1/2	
Width with door open 90° w/door handle (in.)	25	
Each side (in.)	2	
Top (in.)	2	
Air clearances Back (in.)	2	
Approx. shipping wt. (lbs.)	184	
Power/Ratings	120V, 60Hz, 15Amps	

\*Color(s) available: SS = Stainless steel.

ALL MODELS AVAILABLE IN U.S. AND CANADA.

## GE top-freezer refrigerators

	GE "I" Series		GE "D" Series	
	GTK18ICX	GTS18ICS	GTH18DCX GTS18DCP	GTH18DBX GTS18DBP
<b>ENERGY STAR qualified</b>	●		● / -	
ADA compliant	●		●	
<b>Capacity</b>				
Total (cu. ft.)	18.0		18.0	
Fresh food (cu. ft.)	12.93		12.89	
Freezer (cu. ft.)	5.09		5.03	
Shelf area (sq. ft.)	22.6		21.8	
<b>Fresh food features</b>				
Upfront temperature controls	●		●	
Cabinet shelves	3 glass		2 wire, 1 glass	
Adjustable	2 split, 1 f/w		1 f/w, 1 split wire 1 split glass	
Spillproof	●		●	
Crisper drawers	2 clear		2 white	
Snack drawer	Clear		White	
Fixed door bins	2 f/w, 1 w/ gallon storage		2 f/w, 1 w/ gallon storage	
Door shelves	1/2 w/gallon storage		1 split w/gallon, 2 f/w w/gallon	
Dairy compartment	●		●	
Interior lighting	Dual		Single	
Quiet design	Deluxe		Deluxe	
NeverClean™ condenser	●		●	
<b>Freezer features</b>				
Factory-installed icemaker & bin	●		●	
Ice 'N Easy trays	●		1	
Spillproof freezer floor	●		●	
Wire freezer compartment shelves	Step		Step	
Fixed door shelves	2 full-width		2 full-width	
<b>Exterior</b>				
Color(s) available*	CleanSteel™	WW, CC, BB	WW, BB WW, CC, BB	WW, CC, BB
Door handles*	SS	CM	CM	CM
Customer-installed handles	●	●	●	●
Exterior design	Rounded doors	Rounded doors	Rounded doors	Rounded doors
Textured steel door and case	Case only (black)	●	●	●
Reversible doors	●	●	●	●
Choose right or left door opening			●	●
Adjustable rollers	Front	Front	Front	Front
<b>Capacity</b>				
Height to top of hinge (in.)	66-5/8		66-5/8	
Height to top of case (in.)	33-1/8		66-1/8	
Height to mid-freezer (in.)	54		53-15/16	
Case depth without door (in.)	27-1/2		27-1/2	
Case depth less door handle (in.)	32-1/8		30-1/4	
Case depth with door handle (in.)	31		32-1/8	
Depth w/fresh food door open 90° (in.)	58-1/8		58-1/8	
Width (in.)	29-1/2		29-1/2	
Width w/door open 90° w/door handle (in.)	32		32	
Each side (in.)	1/8		1/8	
Top (in.)	1		1	
Air clearances Back (in.)	1		1	
Approx. shipping wt. (lbs.)	228		228	
Power/Ratings	120V, 60Hz, 15Amps			

\*Color(s) available: SS = Stainless steel, CleanSteel = Stainless appearance, WW = White, CC = Bisque, BB = Black, CM = Color-Matched.

ALL MODELS AVAILABLE IN U.S. AND CANADA.

GE top-freezer refrigerators

	GE "C" Series	GE "B" Series
	GTS18CCS GTS18CBS	GTH17B8T
<b>ENERGY STAR qualified</b>		●
<b>Capacity</b>		
Total (cu. ft.)	18.2	16.6
Fresh food (cu. ft.)	13.89	12.54
Freezer (cu. ft.)	4.27	4.10
Shelf area (sq. ft.)	18.9/19.8	19.2
<b>Fresh food features</b>		
Upfront temperature controls	●	●
Cabinet shelves	2 wire	2 wire
Adjustable	2 f/w	2 f/w
Crisper drawers	2	2
Door shelves	3 f/w (2 with gallon storage)	2 f/w with gallon storage
Dairy compartment	●	●
Interior light system	Single	Single
Quiet Design	Deluxe	Deluxe
NeverClean condenser	●	●
<b>Freezer features</b>		
Factory-installed icemaker & bin	● / Opt. (IM4A)	Opt. (IM4A)
Ice 'N Easy trays	- / 1	1
Fixed door shelves	2	2
<b>Exterior</b>		
Color(s) available*	WW, CC, BB	WW, CC, BB
Door handles	CM	CM
Exterior design	Squared doors	Squared doors
Reversible doors	●	●
Choose right or left door opening	●	●
Adjustable rollers	Front	Front
<b>Weights &amp; Dimensions</b>		
Height to top of hinge (in.)	67-3/8	64-3/4
Height to top of case (in.)	66-7/8	64-1/4
Height to mid-freezer (in.)	57	54-3/8
Case depth without door (in.)	26-3/4	25-7/8
Case depth less door handle (in.)	30-1/2	29-1/8
Case depth with door handle (in.)	32-3/8	31
Depth w/fresh food door open 90° (in.)	56-3/8	54-7/8
Width (in.)	28	28
Width w/door open 90° w/door handle (in.)	30-3/4	30-1/2
Air clearances	Each side (in.) 3/4	3/4
Top (in.)	1	1
Back (in.)	1	1
Approx. shipping wt. (lbs.)	178	175
Power/Ratings	120V, 60Hz, 15Amps	

\*Color(s) available: WW = White, CC = Bisque, BB = Black, CM = Color-Matched.

ALL MODELS AVAILABLE IN U.S. AND CANADA.

30" slide-in electric ranges

	GE Profile		GE
	PS968SP PS968TP PS968DP	PS900SP PS900DP	JSS28DN
ADA-compliant	●	●	●
<b>Features</b>			
Capacity (cu. ft.)	4.1	4.4	4.4
Self-clean oven with Delay Clean option	●	●	Standard clean
Light self-clean option	●	●	
Variable cleaning time	●	●	
Automatic self-clean oven door lock	●	●	
Oven racks	3 heavy-duty self-clean	2	2
Oven rack positions	7	7	7
Hidden bake oven interior	●	●	●
TrueTemp™ oven system	●	●	●
Variable broil/Six-pass broil element	●	●	●
Ceramic-glass cooktop	Black True white True bisque Black	Black White Bisque Black	
Overhanging cooktop	●	●	●
12"/9"/6" tri-ring element	1 (3000W)		
6"/9" dual element		1 ribbon (2500W)	
8" heating elements		2 ribbon (2000W)	2 plug-in
7" heating elements	2 ribbon (1800W)		
Bridge element	1 ribbon (800W)		
Total bridge wattage	4400W		
6" heating element	1 ribbon (1500W)	1 ribbon (1500W)	2 plug-in
Warming zone	1 ribbon (120W)		
Infinite heat controls	●	●	●
PreciseAir™ convection system	●	●	●
Convection bake	Multi-/Single-rack		
Convection roast	●		
Auto Recipe™ conversion	●		
QuickSet controls	Glass touch	●	●
Proof mode	●		
Warm mode	●		
Oven meat probe	●		
Temperature display	●	●	●
Delay bake option	●	●	
C° or F° programmable	●	●	
Audible preheat signal	●	●	●
Auto oven shut-off w/override	●	●	●
Control lock capability	●	●	
Electronic clock/kitchen timer	●	●	●
Hot surface indicator lights	4	4	
Heating element "ON" indicator light	●	●	●
Certified Sabbath mode	●	●	●
Interior oven light	●	●	●
Storage drawer	Stainless White Bisque Black	Stainless White Bisque Black	White Black
<b>Appearance</b>			
Color appearance*	SS WW CC BB	SS WW CC BB	WW BB
Frameless glass oven door*	Stainless White Bisque Black	Stainless White Bisque Black	White Black
Oven door with window	Big ClearView™	Big ClearView	Big hearth
Heavy-duty knobs	SS model only		
Dishwasher-safe knobs	●	●	●
Oven door handle	Sculptured stainless Sculptured white Sculptured bisque Sculptured black	Sculptured stainless Sculptured white Sculptured bisque Sculptured black	CM*
Storage drawer handle	Sculptured stainless Sculptured white Sculptured bisque Sculptured black	Sculptured stainless Recessed white Recessed bisque Recessed black	Recessed white Recessed black
Rear filler trim	No	No	No
<b>Weights &amp; Dimensions</b>			
Overall oven interior dimensions (WxHxD in inches)	24 x 16-1/4 x 18-1/8	24 x 17-1/2 x 18-1/4	24 x 17-1/2 x 18-1/4
Approx. shipping wt. (lbs.)	248	181	155
<b>Power/Ratings</b>			
KW rating @	240V 12.4 208V 9.3	11.6 8.7	11.9 8.9
Amps @	240V 40 208V 40	40 40	40 40
Convection wattage	2500		
Broiler/Bake wattage	3600/2700	3600/3400	3300/3410

\*SS = Stainless steel, WW = White with white glass door, CC = Bisque with bisque glass door, BB = Black with black glass door, CM = Color-Matched indicates color of drawer matches range cooktop (either white or bisque)

## 30" free-standing CleanDesign™ electric ranges

	GE®	
	JBP66SM JBP66DM JBP66MN	JB640SP JB640DP JB640MP
<b>Features</b>		
Self-clean oven	●	●
Self-clean latch	●	●
Oven capacity (cu. ft.)	5.3	5.3
Oven racks	2	2
	Pat. black Pat. white Pat. bisque Black Pat. black	Pat. black Pat. white Pat. bisque Pat. black
Ceramic-glass cooktop		
One-piece upswept cooktop	●	●
9 1/2" dual element	1 (3000W)	
12" ribbon heating element		1 (2700W)
8" ribbon heating element	1 (2000W)	1 (2000W)
6" ribbon heating element	2 (1500W)	2 (1500W)
6" warming zone	1 (120W)	
Melt/Simmer	●	●
Infinite heat controls	●	●
TrueTemp™ oven system	●	●
Six-pass power bake element	●	
QuickSet oven controls	QuickSet IV	QuickSet III
Digital temperature display	●	●
Delay bake	●	●
Oven light pad	●	●
Self-clean cool-down time display	●	●
Delay clean option	●	●
Auto oven shut-off	w/override	w/override
Certified Sabbath mode	●	●
Audible preheat signal	●	●
Dual element bake	●	●
Hot surface lights	●	●
Interior oven light	Pad	Pad
Storage drawer	●	●
<b>Appearance</b>		
Color appearance*	SS/BS/WW/ CC/BB	SS/BS/WW/ CC/BB
	Stainless steel CleanSteel™ White Bisque Black	Stainless steel CleanSteel™ White Bisque Black
Frameless glass oven door		
Oven door with window	Big hearth	Big hearth
Designer-style handle	●	●
	Stainless Recessed Recessed Recessed Recessed	Stainless Recessed Recessed Recessed Black
Storage drawer handle		
<b>Weights &amp; Dimensions</b>		
Overall oven interior dimensions (WxHxD in inches)	24-1/8 x 19-1/2 x 19-3/8	
Approx. shipping wt. (lbs.)	175	174
<b>Power/Ratings</b>		
KW rating @ 240V	11.9	10.5
208V	8.9	7.9
240V / 208V	40	40
Broiler/bake wattage	3410/2585	3410/2585

\*SS = Stainless steel with black accents, BS = CleanSteel with black accents, WW = White with white glass door, CC = Bisque with bisque glass door, BB = Black with black glass door, CM = Color-matched indicates color of drawer matches range cooktop (either white or bisque).

All ranges are shipped with cooktop cleaning creme & pad.

## 30" free-standing QuickClean™ electric ranges

	GE			
	JBP35SM JBP35DM	JBP24DM	JBS27SM JBS27DM	JBS15M
ADA-compliant				●
<b>Features</b>				
Oven cleaning	Self-clean	Self-clean	Standard	Standard
Oven capacity (cu. ft.)	5.3	5.3	5.0	5.0
Oven racks	2 heavy-duty	2	2	2
Self-clean drip bowls	●			
Upswept porcelain-enameled cooktop	●	●	●	●
Clean-Well™ cooktop system	●	●	●	
Lift-up cooktop w/dual support rods	●	●	●	●
8" heating elements	2 (6 turns)	2 (5 turns)	2 (5 turns)	1 (5 turns)
6" heating elements	2 (5 turns)	2 (4 turns)	2 (4 turns)	3 (3 turns)
Infinite heat controls	●	●	●	●
Plug-in Calrod® heating elements	●	●	●	●
	Black Grey Black Black	Chrome Black	Black Chrome Chrome Black	Chrome Black
Removable 1-piece drip bowls	●			
Self-clean oven racks	●			
TrueTemp oven system	●			
Six-pass power bake element	●			
Convenience controls	●	●	●	
QuickSet oven controls	QuickSet IV	QuickSet III	QuickSet III	
Digital temperature display	●	●	●	
Delay bake	●	●	●	
Electronic oven controls	●	●	●	
Auto oven shut-off	w/override	w/override		
Delay bake	●	●	●	
Oven light pad	●	●	●	
Start pad	●	●	●	
Delay clean option	●	●	●	
Auto self-clean	●	●	●	
Self-clean cool down time display	●	●	●	
Audible preheat signal	●	●	●	
Certified Sabbath mode	●	●	●	
Clock and minute timer	●	●	●	
Dual element bake	●	●	●	●
Heating element "ON" indicator light	●	●	●	●
Interior oven light	Pad	Pad	Switch	Switch
Preheated oven light	●	●		
	Stainless steel White Bisque Black	White Black	Stainless steel White Black	White Black
Removable full-width storage drawer**				
<b>Appearance</b>				
	SS WW CC BB	WW BB	SS WW BB	WW BB
Color appearance*				
	Stainless steel White Bisque Black	White Black	Stainless steel White Black	Porcelain CM*
Frameless glass oven door*				
Oven door with window	Big hearth	Big hearth	ClearView™	ClearView
Removable oven door	●	●	●	●
Designer-style handle	●	●	●	●
Textured steel side panels	●	●	●	●
<b>Weights &amp; Dimensions</b>				
Overall oven interior dimensions (WxHxD in inches)	24-1/8 x 19-1/2 x 19-3/8	24-1/8 x 19-1/2 x 19-3/8	23-3/4 x 19 x 18-1/2	24 x 18-1/2 x 19
Approx. shipping wt. (lbs.)	173	170	158	157
<b>Power/Ratings</b>				
KW rating @ 240V	12.1	11.7	11.7	10.2
208V	9.1	8.8	8.8	7.7
240V / 208V	40	40	40	40
Broiler/bake wattage	3410/2585	3410/2585	3410/2585	3410/2585

\*WW = White with white door, CC = Bisque with bisque door, BB = Black with black door.

CM = Color-Matched indicates color of oven door or storage drawer matches range cooktop (either white, black or bisque).

\*\*Black, white and bisque models feature recessed drawer handle.

## 30" self-clean gas range

	GE Profile™	
	Sealed burner PGB900SEM PGB900DEM	
<b>Capacity</b>		
Upper oven capacity	Super-large	5.0 cu. ft.
<b>Features</b>		
Oven cleaning	Self-clean	
Deep-recessed cooktop	●	
Cooktop burners	Sealed	
PowerBoil™ burner (Nat.)	(1) 15,000 BTU	
Precise Simmer burner (Nat.)	(1) 5,000 BTU/ 140° Simmer	
High-output burner (Nat.)	(1) 12,000	
All-purpose burners (Nat.)	(1) 9,100 BTU	
Valves (degree of turn)	270	
TrueTemp oven system	●	
QuickSet oven controls	QuickSet V	
Oven control setting	DigiPad	
Auto self-clean	●	
Electronic oven control	●	
Delay Bake	●	
Hi/Low broil	●	
Electronic clock and timer	●	
Automatic oven timer	●	
Audible preheat signal	●	
Oven meat probe	●	
Auto oven shut-off	●	
Certified Sabbath mode	●	
Oven lock-out capability	●	
One-piece upswept cooktop	Porc.-enam.	
	Matte black heavy-cast Grey heavy-cast Taupe heavy-cast Black heavy-cast	
Removable grates	Electronic	
Continuous grates	Dishwasher-safe	
Ignition system	Electronic	
Oven racks	2	
Six embossed rack positions	●	
Scratch-resistant backguard	Stainless steel Porc.-enam.	
Interior oven light	●	
In-oven broiling	●	
<b>Appearance</b>		
Color appearance*	SS/WW/BB	
	Stainless steel White glass Black glass	
Frameless oven door		
Oven door with window	Big ClearView	
Stainless appearance knobs	SS model	
Oven door handle	Sculptured	
<b>Weights &amp; Dimensions</b>		
Overall oven interior dimensions (WxHxD in inches)	24 x 19 x 19	
Approx. shipping wt. (lbs.)	220	
<b>Power/Ratings</b>		
	(1) 15.0/11.0 (1) 11.0/9.1 (1) 5.0/5.0 (1) 9.1/9.1	
Top burners (000's BTUs) Nat/LP		
Oven/broiler burners (000's BTUs) Nat/LP	16.0/16.0 oven 13.5/12.0 broil	
Gas range electrical rating**	120V, 60Hz, 5A	
LP conversion kit (includ.)	●	

\*SS = Stainless steel (with black/metallic accents on select models), WW = White with white glass door, BB = Black with black glass door.

\*\*15A requires a dedicated circuit.

Factory set for Natural Gas. A set of LP orifices is included with each range for LP conversion.



### 30" self-clean gas ranges

	GE	
	Sealed burner models	
	JGBP33SEM JGBP33DEM	JGBP28SEM JGBP28MEM JGBP28DEM
<b>Capacity</b>		
Extra-large oven	4.8 cu. ft.	4.8 cu. ft.
<b>Features</b>		
Oven cleaning	Self-clean	Self-clean
Cooktop burners	Sealed	Sealed
High-output burner	(1) 13,000/ 1,000 BTU	(2) 12,000/ 1,000 BTU
Precise Simmer burner (Nat.)	(1) 5,000/600 BTU	(1) 5,000/600 BTU
All-purpose burners (Nat.)	(2) 9,500/850 BTU	(1) 9,500/850 BTU
Valves (degree of turn)	270	270
TrueTemp oven system	●	●
Electronic controls	●	●
QuickSet oven controls	QuickSet IV	QuickSet III
Delay Bake	●	●
Auto self-clean	●	●
Electronic clock and timer	●	●
Automatic oven timer	●	●
Audible preheat signal	●	●
Auto oven shut-off	●	●
Certified Sabbath mode	●	●
One-piece upswept cooktop	Porc.-enam.	Porc.-enam.
Porcelain-enameled one-piece drip pans	Black Grey Taupe Black	Opt. access.
Removable grates	Black cast-iron Grey cast-iron Taupe cast-iron Black cast-iron	Black cast-iron Grey cast-iron Taupe cast-iron Black cast-iron
Square grates	●	●
Ignition system	Electronic	Electronic
Oven racks	3	2
Six embossed rack positions	●	●
Scratch-resistant backguard	Porc.-enam.	Porc.-enam.
Interior oven light	●	●
Storage drawer	●	●
In-oven broiling	●	●
<b>Appearance</b>		
Color appearance*	SS/WW/CC/BB	SS/BS/WW/BB/
Frameless oven door	Stainless steel White glass Bisque glass Black glass	Stainless steel CleanSteel™ White glass Black glass
Oven door with window	Big hearth	Big hearth
Designer-style handle	●	●
<b>Weights &amp; Dimensions</b>		
Overall oven interior dimen. (WxHxD in inches)	24 x 18-1/2 x 19	
Approx. shipping wt. (lbs.)	210	210
<b>Power/Ratings</b>		
Top burners (000's BTUs) Nat/LP	(1) 13.0/11.0 (1) 5.0/5.0 (2) 9.5/9.5	(2) 12.0/11.0 (1) 9.5/9.5 (1) 5.0/5.0
Oven/broiler burners (000's BTUs) Nat/LP	16.0/16.0 Oven 12.5/12.0 Broil	
Gas range electrical rating	120V, 60Hz, 5A	
LP conversion kit (incl.)	●	●

\*SS = Stainless steel (with black/metallic accents on select models), BS = Bisque with bisque glass door, WW = White with white glass door, CC = Bisque with bisque glass door, BB = Black with black glass door.  
 †A set of LP orifices is included with each range for LP conversion.

### 30" standard-clean gas ranges

	GE®	
	Sealed burner model	Standard burner model
	JGBS23SEM JGBS23DEM	JGBS07DEM
ADA-compliant		●
<b>Capacity</b>		
Oven capacity	Extra-large 4.8 cu. ft.	Extra-large 4.8 cu. ft.
<b>Features</b>		
Oven cleaning	Standard-clean	Standard-clean
Cooktop burners	Sealed	Std./twin
High-output burner	(1) 12,000	
Precise Simmer burner (Nat.)	(1) 5,000 BTU 140° simmer	
All-purpose burners (Nat.)	(2) 9,500	(4) 9,100/850 BTU
Valves (degree of turn)	270	140
Electronic clock and timer	●	●
Electronic oven controls	QuickSet III	
Porcelain-enameled cooktop	One-piece upswept	●
Lift-up cooktop		●
Easy-clean porcelain-enameled subtop		●
One-piece drip pans	Black Grey Taupe Black	Opt. access
Removable square grates	Deluxe porcelain-steel	Grey/Taupe/ Black standard porcelain-steel
Ignition system	Electronic	Electronic
Oven racks	2	2
Embossed rack positions	6	6
One piece broiler pan	●	●
Porcelain-enameled backguard	●	●
Interior oven light	●	●
Broiler drawer	Slide-out	●
<b>Appearance</b>		
Color appearance*	SS, WW, CC, BB	WW, CC, BB
Frameless oven door	Stainless steel White glass Bisque glass Black glass	White/Bisque/ Black porc.-enam.
Oven door with window	Big hearth	ClearView
Designer-style handle	●	●
<b>Weights &amp; Dimensions</b>		
Overall oven interior dimensions (WxHxD in inches)	24 x 18-1/2 x 19	24 x 18-1/2 x 19
Approx. shipping wt. (lbs.)	180	165
<b>Power/Ratings</b>		
Top burners (000's BTUs) Nat/LP	(1) 12.0/11.0 (1) 5.0/5.0 (2) 9.5/9.5	(4) 9.1/8.0
Oven/broiler burners (000's BTUs) Nat/LP	18.0/16.5	
Gas range electrical rating**	120V, 60Hz, 5A	
LP conversion kit (included)	●	●

\*SS = Stainless steel (with black/metallic accents on select models), WW = White with white door, CC = Bisque with bisque door, BB = Black with black door. CM = Color-Matched indicates color of oven door matches cooktop (either white or bisque).

\*\*Electrical rating not applicable to standing pilot models. Factory set for Natural Gas. A set of LP orifices is included with each range for LP conversion.

### 30" built-in gas cooktop

	GE Profile
	JGP940SEK JGP940TEK JGP940KEK JGP940BEK
ADA-compliant	●
<b>Features</b>	
Cooktop burners	4 sealed
PowerBoil burner 000's BTUs	(1) 15.0, 180° simmer
All-purpose burner(s) 000's BTUs	(1) 11.0, (1) 9.1 150° simmer
Precise Simmer burner(s) 000's BTUs	(1) 6.0 140° simmer
Electronic pilotless ignition	●
Cooktop surface	Ceramic glass
Cooktop grates	Matte black deluxe-cast Grey deluxe-cast Taupe deluxe-cast Black deluxe-cast
Continuous grates	●
Dishwasher-safe grates and knobs	●
Control panel	Black True White Bisque Black
Controls	Right side
Control lock capacity	●
<b>Appearance</b>	
Color appearance*	SS WW CC BB
Heavy-duty knobs	SS model only
<b>Weights &amp; Dimensions</b>	
Cooktop width (in inches)	30
Approx. shipping wt. (lbs.)	52
<b>Features</b>	
Gas cooktop electrical rating	120V, 60Hz, 5A
Burners (000's/BTU's): Natural Gas/LP Gas †	(1) 15.0/13.0 (1) 11.0/9.1 (1) 9.1/9.1 (1) 6.0/6.0

\*SS = Stainless Steel, WW = White on white, CC = Bisque on bisque, BB = Black on black.  
 †A set of LP orifices is included with each cooktop for LP conversion. Factory set for natural gas.

## 30" electric CleanDesign™ cooktop

	GE®
	JP346SM JP346WWM JP346CM JP346BM
ADA-compliant	●
<b>Features</b>	
	Pattern_black Pattern_white Pattern_bisque Pattern_black
Ceramic-glass surface	
Number of elements	4 ribbon
12" heating elements	1 ribbon (2700W)
8" heating elements	1 PowerBoil™ (2500W)
6" heating elements	2 ribbon (1200W)
Melt setting	●
Hot surface indicator lights	1
Dishwasher-safe knobs	●
<b>Appearance</b>	
	SS WW CC BB
Color appearance*	
Frameless	SS/WW/CC/BB
<b>Weight &amp; Dimensions</b>	
Cooktop width (in inches)	30
Approx. shipping wt. (lbs.)	37
<b>Power/Ratings</b>	
240V	7.6
208V	5.7
240V	40
208V	30

\*SS = Stainless Steel, WW = White on white, CC = Bisque on bisque, BB = Black on black.

## Hoods

	GE	
	Deluxe	Standard
	JV348L JV347H	JN327H
<b>30" Width</b>		
<b>Features</b>		
Two-speed fan control		●
Three-speed fan control	●	
Vertical exhaust (CFM)	200	
Rear exhaust (CFM)	180	
Damper included (rectangular)	●	
Optional damper accessory (round)	JXDA22	
Sones rating:		
Top exhaust	6.0	
Rear exhaust	7.0	
Removable grease filters	Disposable 1-pc. filter†	Disposable 1-pc. filter†
Filter size (sq. in.)	90	90
Cooktop light(s)*	1	1
3-1/4" x 10" rectangular duct	●	
7" round duct	●	
Non-vented	optional	●
<b>Appearance</b>		
	SS	WW/CC/BB
Color appearance**	WW/CC/BB	WW/CC/BB
<b>Weights &amp; Dimensions</b>		
Approx. shipping wt. (lbs.)	20	19
<b>Power/Ratings</b>		
Current rating amps @ 120V	20	2.5

\*Light bulbs not furnished. Light cover not included on JN327H.

\*\*SS = Stainless steel, WW = White on white, CC = Bisque on bisque, BB = Black on black.

†WB02X10700 charcoal filter is shipped with models JN327 and JV347. WB2X8391 grease filter is shipped with model JV348 and JV347. Replacement grease filters and replacement charcoal filters (WB02X10700) are available for additional cost. Call toll-free 800.626.2002.

## GE Profile Advantium® above-the-cooktop ovens

	GE Profile™
	SCA1001KSS SCA1000HWW SCA1000HBB
<b>Features</b>	
Family-size oven	●
Stainless steel oven interior	●
Cooking modes	Speedcook up to 4 times Traditional oven ● Microwave oven ● Warming ●
Oven controls	Controls Dial & buttons Electronic scrolling display ● Preprogrammed menu items over 100 Help pad ● Demo mode ● Interior oven light ● Beeper sound level control 4 levels Variable scroll speed 5 speeds Custom Recipe Saver 30
Cooking complete reminder	●
Control lockout	●
High-capacity cooktop vent fan	2 speeds
Full-view cooktop lighting	●
Programmable night light	●
Microwave oven features	
Sensor	●
Defrost	●
Microwave power output watts	900
300-CFM vent fan	●
<b>Appearance</b>	
	Stainless steel White Black
Color appearance	
New Profile sculptured handle	●
<b>Weights &amp; Dimensions</b>	
Overall oven Height	8-7/32
interior Width	21-3/32
dimensions (in inches)	
Depth	14-3/32
Overall dimensions (in inches)	
Exterior height (front)	16
Exterior height (rear)	16-13/32
Exterior width	29-7/8
Exterior depth (not including handle)	15-3/8
Approx. shipping weight (lbs.)	95
<b>Power/Ratings</b>	
Input volt/hertz	120V/60Hz
Input amps/watts (max)	15A/1.7KW-total
<b>Accessories</b>	
Cookbook	●
Cooking guide	●
Cooking tray	●
Microwave tray	●
Recirculating charcoal filter kit (opt.)	JX81A
Filler panel kit**	Optional
<b>Warranty</b>	
Limited one-year in-home warranty*	●
Limited five-year magnetron warranty*	●

\*See written warranty for details.

\*\*Available through GE Parts. Call 1-877-959-8688

## GE over-the-range microwave ovens

	GE					
	JNM1851SM* JNM1851DM*	JVM1850SM JVM1850DM	JVM1750SM JVM1750DM	JVM1740SM JVM1740DM	JNM1541SN* JNM1541DN*	JVM1540SN JVM1540LN JVM1540DN
<b>Capacity</b>						
Oven cavity (cu. ft.)	1.8	1.8	1.7	1.7	1.5	1.5
<b>Features</b>						
Watts (IEC-705 test procedure)	1100	1100	1000	1000	950	950
Electronic touch controls	●	●	●	●	●	●
SmartControl system w/ interactive display	●	●	●	●	●	●
Scrolling display	2-line	2-line	1-line	1-line	1-line	1-line
Clock and AM/PM pad	●	●	●	●	●	●
Variable scroll speed	●	●	●	●	●	●
Help pad	●	●	●	●		
Bilingual display (English/Spanish)	●	●				
Sensor controls						
Beverage	●	●	●			
Popcorn	●	●	●			
Potatoes	●	●	●			
Reheat	●	●	●			
Vegetables	●	●	●			
Convenience controls						
Beverage				●	●	●
Potato				●	●	●
Popcorn				●	●	●
Reheat				●	●	●
Vegetables				●		
Cook				●		
Express Cook (1-6 min.)	●	●	●	●	●	●
Instant On controls	●	●	●	●	●	●
Time cook	I & II	I & II	I & II	I & II	I & II	I & II
Add 30 Seconds	●	●	●	●	●	●
Auto/Time Defrost	●/●	●/●	●/●	●/●	●/●	●/●
1-lb. Quick Defrost	●	●	●	●		
Power levels	10	10	10	10	10	10
Delay Start/Reminder	●/●	●/●	●/●	●/●	●/●	●/●
Cooking system	CircuWave™ 1100	CircuWave 1100	CircuWave	CircuWave	Top feed	Top feed
Turntable	Recessed	Recessed	●	●	●	●
Turntable On/Off	●	●	●	●	●	●
Interior lighting	●	●	●	●	●	●
Full-view cooktop lighting	●	●	●	●	●	●
Night light	Programmable	Programmable	Programmable	Programmable	●	●
Timer On/Off	●	●	●	●	●	●
Cooking complete reminder	●	●	●	●	●	●
Control lockout	●	●	●	●	●	●
300-CFM exhaust fan	4-speed with boost	4-speed with boost	2-speed	2-speed	2-speed	2-speed
<b>Appearance</b>						
Color appearance**	SS WW/BB	SS WW/CC/BB	SS WW/CC/BB	SS WW/CC/BB	SS WW/CC/BB	SS CS WW/CC/BB
Case color	Black White/Black	Black White/Bisque/Black	Black White/Bisque/Black	Black White/Bisque/Black	Black White/Bisque/Black	Black Black White/Bisque/Black
<b>Weights &amp; Dimensions</b>						
Overall oven interior dimensions WxHxD (in inches)	21-29/32 x 9-1/2 x 14-19/32	21-29/32 x 9-1/2 x 14-19/32	20-1/4 x 9-1/4 x 14-13/32	20-31/32 x 9-3/8 x 14-3/16	18-13/16 x 9-1/4 x 14-13/32	18-13/16 x 9-1/4 x 14-13/32
Approx. shipping weight (lbs.)	68	68	67	67	67	67
<b>Power/Ratings</b>						
Input Volt/Hertz	120V/60Hz	120V/60Hz	120V/60Hz	120V/60Hz	120V/60Hz	120V/60Hz
Input Amps/Watts (max)	15A/1.58KW	15A/1.58KW	15A/1.58KW	15A/1.6KW	15A/1.58KW	15A/1.58KW
<b>Accessories</b>						
Cooking guide label	●	●	●	●	●	●
Oven rack(s)	1 (2-positions)	1 (2-positions)	1 (2-positions)	1 (1-position)	1 (1-position)	1 (1-position)
Recirculating charcoal filter kit†	JX81B (included)	JX81B (optional)	JX81A (optional)	JX81A (optional)	JX81A (included)	JX81A (optional)
Filler panel kit ††	JX52 (optional)	JX52 (optional)	JX48 (optional)	JX48 (optional)	JX48 (optional)	JX48 (optional)
<b>Warranty</b>						
Limited one-year in-home warranty†††	●	●	●	●	●	●

\*Non-vented model.

\*\*SS = Stainless steel, CS = CleanSteel™, WW = White on white, CC = Bisque on bisque, BB = Black on black.

†Optional for units that are not set as recirculating from the factory.

††JX48WH, JX48BL, JX52WH and JX52BL available through GE Parts starting 12/01/09. Call 1-877-959-8688 to order.

†††See warranty for details.

## Spacemaker II™ microwave oven

	GE Profile™ PEM31SM PEM31DM
ADA compliant†	●
<b>Capacity</b>	
Oven cavity (cu. ft.)	1.0
<b>Features</b>	
Watts (IEC-705 test procedure)	800
Electronic touch controls	●
Scrolling display with Help pad	●
Demo mode	●
Electronic digital display w/clock	●
Sensor controls	●
Popcorn	●
Beverage	●
Reheat	●
Vegetable	●
Potato	●
Chicken/Fish	●
Express Cook	●
Instant On controls	●
Time Cook	I & II
Add 30 Seconds	●
Auto/Time Defrost	●
Power levels	10
Turntable On/Off	●
Kitchen timer/Timer (On/Off)	— / ●
Cooking complete reminder	●
Delay Start	●
Reminder	●
Control lockout	●
<b>Appearance</b>	
Color appearance*	SS WW, CC, BB Black
Case color	White, Bisque, Black Stainless steel
Door color	White, Bisque, Black
<b>Weights &amp; Dimensions</b>	
Approx. shipping weight (lbs.)	40
WxHxD††	16-1/2 x 7-7/16 x 11-1/4
(in inches)	23-25/32 x 11-3/16 x 12-9/32
Exterior	
<b>Power/Ratings</b>	
Input Volt/Hz	120V/60Hz
Electrical input	Watts 1300
@ 120V	Amperage 11.5
<b>Accessories</b>	
Cooking guide label	●
Optional built-in kit	JX827SMSS JX827DMWW JX827DMBB
Optional hanging kit	JXA019K**
Right-angle plug	●
<b>Warranty</b>	
Limited one-year in-home warranty††	●
Limited five-year magnetron warranty††	●

\*SS = Stainless steel, WW = White on white, CC = Bisque on bisque, BB = Black on black.

\*\*JXA019K is available at additional cost.

†Model must be in built-in configuration to be ADA compliant.

††See written warranty for details.

†††Exterior dimensions: height includes feet, depth does not include handle.

## GE Profile built-in dishwashers

	GE Profile PDW7880PSS PDW7800PWW PDW7800PCC PDW7800PBB
<b>2009 ENERGY STAR®</b>	●
Energy Factor (EF)*	0.68
Maximum gallons per cycle**	5.1
Kilowatt hrs/yr	321
<b>Features</b>	
Wash system	PermaTuf®
Place settings	Up to 16
Front appearance	Contour door
Wash arms	Six-level wash
Wash arms	3 direct-feed
Wash levels	6-towerless
Water filtration	3-stage, w/ExtraFine™ filter
Dual pumps and motors	●
Hard-foed disposer	Piranha™
Sensor	CleanSensor™
Automatic temperature control	●
Rinse aid dispenser	w/indicator & adjust.
Electronic controls	●
Cycle status indicators	Countdown display w/6 status lights
Selections/Enhancements	7/6
Last cycle memory	●
Audible end-of-cycle signal	●
<b>Selections</b>	
Anti-bacterial (NSF***)	●
Cookware	●
Normal Wash	●
China/Crystal	●
Glasses Cycle	●
SpeedCycle (wash & dry)	●
Rinse Only	●
<b>Enhancements</b>	
Delay Start	1-9-hour
Temp Boost	●
PreWash	●
Heated Dry	●
HotStart™	●
Control lock-out	●
<b>Racking</b>	
Rack finish	White nylon
Adjustable upper rack with CleanTip tines	4-position deep-tiered
Utility shelves	4 sets with 2 multi-position, upper; 2 lower
Fold-down tine flexibility	4 with StemSafe™
Silverware basket	3-pc. w/3 cell covers and ExtraBasket
Solid surface install kit	Included
Latch	Squeeze
<b>Dry</b>	
Calrod heating element	Multi-wattage
<b>Quiet</b>	
Sound insulation package	54 dBA
Door insulation	●
ActiveVent system	●
Tub collar trim	●
<b>Weights &amp; Dimensions</b>	
Height w/legs retracted (in.)	34
Height w/legs removed (in.)	33-13/16
Overall width (in.)	24
Overall depth (in.)	24-3/4†
Approx. shipping weight (lbs.)	90

\*Subject to change.

\*\*Based on DOE test procedure.

\*\*\*Certified by National Sanitation Foundation.

†Add 1/2" for deepest part of contour door.

## GE® tall tub built-in dishwasher

	GE GLDA696PSS GLDA690PWW GLDA690PBB
<b>2009 ENERGY STAR</b>	●
Energy Factor (EF)*	0.74
Maximum gallons per cycle**	5.2
Kilowatt hrs/yr	302
Meets ADA guidelines	●
<b>Features</b>	
Wash system	Towerless
Wash arms	2 w/upper nozzle
Wash levels	5-towerless
Water filtration	3-stage
Dual pumps and motors	●
Manual clean filter	●
Rinse aid dispenser	w/indicator and adjustment
Electronic controls	●
Cycle status indicators	Countdown display with 1 "Clean" light
Cycles/Options	4/6
Last cycle memory	●
<b>Cycles</b>	
Pots & Pans	●
Normal Wash	●
Light wash	●
Rinse Only	●
<b>Options</b>	
Delay Start	2/4/8-hour
Heated Dry	●
HotStart	●
Control lock-out	●
<b>Racking</b>	
Rack finish	Gray nylon
Upper rack	Super
Utility shelves	2 w/1 StemSafe
Silverware basket	Deluxe
Solid surface install kit	Included
Low profile installation	●
Latch	Squeeze
<b>Dry</b>	
Calrod heating element	Multi-wattage
<b>Quiet</b>	
Sound insulation package	56 dBA
Door insulation	●
Mastic	●
<b>Weights &amp; Dimensions</b>	
Height w/legs retracted (in.)	32-11/32
Height w/legs removed (in.)	N/A†
Overall width (in.)	24
Overall depth (in.)	24
Approx. shipping wt. (lbs.)	105

\*Subject to change.

\*\*Based on DOE test procedure.

\*\*\*Certified by National Sanitation Foundation.

†Legs not removable



## GE built-in dishwashers

GE	
	GSD2100RWW GSD2100RCC GSD2100RBB GSD2101RBB† GSD2101RWW†
<b>2009 ENERGY STAR</b>	●
Energy Factor (EF)*	0.66
Maximum gallons per cycle**	5.3
Kilowatt hrs/yr	324
<b>Features</b>	
Tub and door liner	PermaTuf
Wash system	PowerScrub™
Wash levels	4
Water filtration	2-stage
Hard-foed disposer	Piranha
Rinse aid dispenser	●
Control type	Turn-to-start
Cycle status indicator(s)	Dial
Cycles/Options	5/2
<b>Cycles</b>	
Heavy Wash	Dial
Normal Wash	Dial
Light Wash	Dial
Plate Warmer	Dial
Rinse Only	Dial
<b>Options</b>	
Heated Dry	Rocker
HotStart	Dial
<b>Racking</b>	
Upper rack	Standard
Lower rack	Standard
Silverware basket	Deluxe
Solid surface install kit	GPF65
Latch	●
<b>Dry</b>	
Calrod heating element	●
<b>Quiet</b>	
Sound package	TBD
<b>Appearance</b>	
Color panels—door & access	Trimless
<b>Weights &amp; Dim.</b>	
Height w/legs retracted (in.)	34
Height w/legs removed (in.)	33-13/16
Overall width (in.)	24
Overall depth (in.)	25-3/4
Approx. ship. wt. (lbs.)	80

All GE dishwashers are equipped with the following:  
120°F inlet water capacity, convection drying, horizontal mechanism, leveling screws.

\*Subject to change.

\*\*Based on DOE test procedure.

\*\*\*Certified by National Sanitation Foundation.

†GSD2101RWW and GSD2101RBB available with power cord attached.

## GE frontload washer

GE	
	WCVH6800J
<b>Capacity</b>	
Capacity	King-size
Cubic feet	4.0 IEC*
<b>Features</b>	
<b>ENERGY STAR qualified</b>	●
CEE tier rating	3
ADA compliant	●
Wash/rinse temperatures	5 with sanitize
Water levels	Automatic
HydroMotion™ wash	●
HydroHeater™	●
SudsLogic	●
Number of cycles	26
Specialty cycles	Active wear
Detergent dispenser (liquid/powder)	Flow-Thru™ timed
Bleach dispenser	Flow-Thru timed
Fabric softener dispenser	Flow-Thru timed
Pretreat dispenser	●
Control type	Electronic
End-of-cycle signal	Adjustable
Wash/spin speed combinations	6
RPM spin speed	1100
Water temperature system	HydroTemp™
Colors	●
Delicates	●
Easy Care	●
Handwash	●
Whites	●
Optional soil levels	4
2nd rinse	●
Adaptive capabilities	Load size
Cycle countdown	with LED indicators
Cycle status lights	●
Delay start	●
Drain and spin	●
Prewash	●
Speed wash	●
Stain wash	●
Door style	See-thru glass
Noise package	Quiet-by-Design™
Leveling legs	●
Stainless steel wash basket	●
Handle	TrueGrip™
Fill & drain hoses included	●
Pedestal available at additional cost	●
Stacking kit available at additional cost	GEFLSTACK
<b>Appearance</b>	
Colors available**	MV, WW, MS, BB
<b>Weights &amp; Dimensions</b>	
Approx. shipping weight (lbs.)	225
Flexible installation	Undercounter, stacked, side-by-side
<b>Power/Ratings</b>	
Modified Energy Factor (MEF)	2.20
Water Factor (WF)	4.0
Circuit breaker or Time-delay fuse	15 or 20 amps
Volts/Hertz	120V; 60Hz

\*Washes equivalent amount of clothes as a similar cu. ft. agitator machine, per IEC 60456 Edition 4.

\*\*WW = White on white, MV = Vermillion red, MS = Metallic silver, BB = Black.

## GE frontload dryer

GE	
	DCVH680EJ/GJ
<b>Capacity</b>	
Capacity	Super
Cubic feet	7.0
<b>Features</b>	
ADA compliant	●
Moisture sensor	Sensor Dry Plus™
Control type	Rotary-electronic
Cycle countdown	with LED indicators
Cycle status lights	●
Dual thermistors	●
Heat selections	5
Number of cycles	Multiple
Cotton cycle	●
Custom cycle	●
Delicate cycle	●
Easy Care cycle	●
Mixed loads cycle	●
Antibacterial cycle	●
Optional dryness levels—Damp	●
Optional dryness levels—Dry	●
Optional dryness levels—Less dry	●
Optional dryness levels—More dry	●
Timed dry—actual minutes on timer	90
Add Time	●
Dewrinkle	●
Damp dry signal	●
Dryer interior light	●
Dryer rack	Deluxe
End-of-cycle signal	Adjustable
100% front serviceable	●
Door style	See-thru glass
Drum interior	DuraDrum™
Leveling legs	●
Reverse-a-Door	●
Exhaust options (electric/gas)	4/3
Handle	TrueGrip
Pedestal available at additional cost	●
<b>Appearance</b>	
Colors available*	MV, WW, MS, BB
<b>Weights &amp; Dimensions</b>	
Approx. shipping weight (lbs.) E/G	125/130
Flexible installation	Undercounter, stacked, side-by-side
LP conversion kit	WE25X0217

\*WW = White on white, MV = Vermillion red, MS = Metallic silver, BB = Black.

## GE® topload washers

	GE	
	WCRE6270K	WCSR4170G
<b>Capacity</b>		
Capacity cu. ft.	4.1 IEC* Colossal	3.2 Super plus
<b>Energy</b>		
<b>ENERGY STAR® qualified</b>	●	
CEE tier rating	1	
<b>Controls</b>		
Electronic	Rotary	
Electromechanical		●
Status indicators	LED	
HydroWave™	with Infusor™	●
RainShower™ rinse system	●	
Water temp system	PerfectTemp™	
Wash/rinse temps	6	4
Water levels	Variable	4
<b>Wash system</b>		
Wash basket	Stainless steel	ExtrAction™ GentlePower™ agitator
Wash mechanism	Infusor	
Wash/spin combinations	5	4
<b>Drive system</b>		
Maximum spin speed	700 RPM	630 RPM
<b>Dispensers</b>		
Bleach	●	●
Fabric softener	●	●
<b>Wash cycles</b>		
Number of cycles	31	17
<b>Cottons Regular</b>	●	●
Auto soak (30 min.)	●	●
Auto soak (15 min.)	●	●
Extra-heavy soil	●	
Heavy soil	●	●
Medium soil	●	●
Light soil	●	●
Extra-light soil	●	
<b>Easy Care</b>	●	●
Auto soak (15 min.)	●	●
Heavy soil	●	●
Medium soil	●	●
Light soil	●	●
Extra-light soil	●	●
<b>Casuals – Pulsed</b>	●	●
Heavy soil	●	●
Medium soil	●	●
<b>Delicate</b>	●	●
Light soil	●	●
Extra-light soil	●	●
<b>Handwash</b>	●	●
Hang to Dry/Prewash		●
<b>Special cycles</b>		
2nd rinse	●	●
Extended spin	●	
Rinse & spin (Quick rinse)	●	●
Spin only	●	●
Fabric softener	2	
<b>Additional features</b>		
Quiet performance	Quiet-by-Design™	Quiet-by-Design
Color lid instructions	●	●
Fill & drain hoses included	●	●
<b>Appearance</b>		
Backsplash color	Silver	White
Colors available**	WW	WW, CC
<b>Weights &amp; Dimensions</b>		
Approx. ship. weight (lbs.)	155	160
<b>Power/Ratings</b>		
Modified Energy Factor (MEF)	1.94	
Water Factor (WF)	6.5	

\*Washes equivalent amount of clothes as a similar cu. ft. agitator machine per IEC 60456 Edition 4.

\*\*WW = White on white, CC = Bisque on bisque.

## GE topload matching dryers

	GE		
	Electric Gas	DRSR483EG DRSR483GG	DJXR433EG DJXR433GG
<b>Capacity</b>			
Capacity cu. ft.		7.0 Super	6.0 Extra-large
<b>Controls</b>			
Electronic		Rotary	
Electromechanical			●
Heat selections		4	4
<b>Dry system</b>			
Temperature sensor		Thermostat	Thermostat
Dryer drum		Stainless steel	DuraDrum™
Drum baffles		White	White
<b>Signals</b>			
End-of-cycle		●	
<b>Dry cycles</b>			
Number of cycles		8	3
<b>Cycle selections</b>			
Cottons		●	●
Easy care		●	●
<b>Program options</b>			
More dry		●	●
Dry		●	●
Less dry		●	●
Damp dry		●	
<b>Timed dry</b>			
Time control		80 min.	60 min.
<b>Special cycles</b>			
Dewrinkle		●	
Quick Fluff (no heat)		●	
Optional wrinkle care/extended tumble		●	
<b>Additional Features</b>			
Quiet performance		Quiet-by-Design	Quiet-by-Design
Dryer interior light		●	
Reverse-a-Door		●	●
<b>Appearance</b>			
Backsplash color		Silver	White
Colors available*		WW	WW, CC
<b>Weights &amp; Dimensions</b>			
Approx. shipping weight–elec. (lbs.)		119	112
Approx. shipping weight–gas (lbs.)		124	115
LP conversion kit		← WE25X0217 →	

\* WW = White on white, CC = Bisque on bisque.

## GE unitized washers and dryers

Electric Gas Washer Capacity	GE			
	WSM2700H		WSM2420D	
	Washer	Dryer	Washer	Dryer
Capacity (cu. ft.)	2.7 Extra-large	5.5 Extra-large	1.5 Large	3.4 Large
<b>Features</b>				
Wash/spin speed combinations	1		2	
Wash/rinse temperatures	3		3	
Water levels	3		3	
Number of wash cycles	3		3	
Regular	●		●	
Perm. Press	●		●	
Delicates	●		●	
Unbalanced load control	●		●	
Lint filter	●		●	
Fill & drain hoses included	●		●	
<b>Dryer</b>				
<b>Features</b>				
Automatic dry control		●		●
Number of dry cycles		4		4
Auto Regular		●		●
Auto Perm. Press				●
Delicates		●		
Timed		●		●
Air Fluff		●		●
Control location		Mid-band		Mid-band
Exhaust options		Rear		Rear/Sides
<b>Appearance</b>				
Colors available*		WW		WW
<b>Weights &amp; Dimensions</b>				
Dimensions (HxWxD in inches)		75-1/2 x 27 x 30-13/16**		71-3/4 x 23-7/8 x 27-1/4**
Approx. shipping wt. (lbs.)		300		238
LP conversion kit		WE25X10017		WE25X0219

\*WW = White on white

\*\*Depth dimension assumes water hook-up is recessed in the wall.

**Note:** The third prong on the WSM2780D plug configuration is a flat spade type rather than a typical round probe. It requires a matching wall outlet.

## GE portable/stationary washers

Individual washers	GE	
	Portable WSLP1500J	Stationary WLSL1500J
<b>Capacity</b>		
Capacity (cu. ft.)	3.1 IEC* Extra-large	3.1 IEC* Extra-large
<b>Features</b>		
Wash/spin speed combinations	1	1
Wash/rinse temperatures	3	3
Water levels	5	5
Number of cycles	14	14
Cycle countdown	Digital	Digital
Regular		
Colors	●	●
Whites	●	●
Delicates	●	●
Speed Wash	●	●
Custom cycle	●	●
Load sensing	●	●
Automatic cool down	●	●
Fabric softener dispenser	●	●
Automatic detergent dispenser	●	●
Lint filter	1 Removable	1 Removable
Washer lid type	Clear	Clear
Quiet pump	●	●
Easy-roll rollers	●	
Unicouple connector	●	
Basket material	Stainless steel	Stainless steel
Fill & drain hoses included	●	●
<b>Appearance</b>		
Colors available**	WW	WW
<b>Weights &amp; Dimensions</b>		
Circuit requirements	120V, 60 Hertz, 15 or 20 Amps	
Dimensions (HxWxD in inches)**	38 x 23-5/8 x 26	37-1/2† x 23-5/8 x 26
Approx. shipping wt. (lbs.)	116	114

\*Washes equivalent amount of clothes as a similar cu. ft. agitator machine, per IEC 60456 Edition 4.

\*\*Colors available: WW = White on white.

\*\*\*Depth measured from front of control knob.

†With leveling legs extended.

## GE portable dryer

Individual dryer	GE
	DSKP333EC* DSKS333EC
<b>Capacity</b>	
Capacity (cu. ft.)	3.6
<b>Features</b>	
Dry control	Automatic
Heat selections	3 (timer)
Number of dry cycles	3
Auto. Reg.	●
Timed Regular (min.)	150
Air Fluff (min.)	30
Separate start switch	●
Control location	Top
Lint filter	Mid-band
<b>Appearance</b>	
Colors available**	WW
<b>Weight &amp; Dimensions</b>	
Exhaust options***	4 way - rear, bottom, left, right 4 way - rear, top, left, right
Circuit requirements	120V, 60 Hertz, 15 Amps
Power cord	6 feet
Dimensions (HxWxD in inches)	33-1/4 x 23-7/8 x 24-1/2
Wall-mount kit (available at additional cost, applies only to stationary models)	WMK-35
Approx. shipping wt. (lbs.)	108

\*DSKP333EC dryer comes equipped with casters and stationary leveling legs.

\*\*Colors available: WW = White on white.

\*\*\*DSKS333EC is shipped exhausted through the top.

†Rear-mounted outlet on DSKS333EC approved for use with washer/dryer stack rack DSDR24F.

**Circuit requirements:** An individual, properly grounded branch circuit of the proper voltage and frequency as specified on the rating plate, with no other appliances or fixtures in circuit, is required.

## GE commercial washer

Capacity	GE
	WNRD2050G
Capacity (cu. ft.)	3.5 stainless steel
<b>Features</b>	
Motor	2-speed
Wash/spin speed combinations	3
Wash/rinse temperatures	3
Water levels	4
Digital cycle countdown	●
Number of wash cycles	5
White cottons	●
Colored cottons	●
Bright colors	●
Permanent Press	●
Delicate	●
Spin only	●
Bleach dispenser	●
Quiet performance	Deluxe quiet
Lid instructions	●
LED indicators	●
<b>Appearance</b>	
Colors available	White
Braille kit	14-D242
<b>Weights/Dimensions</b>	
Approx. shipping weight (lbs.)	160

## GE commercial dryer

Capacity	GE
	DNCD450EG/GG
Capacity (cu. ft.)	7.0
<b>Features</b>	
Dry cycles	5
Cottons/high heat	●
Mixed loads/high heat	●
Perm. press/medium heat	●
Knits/low heat	●
Delicates/extra low heat	●
Temperatures	4
Air dry	●
Digital cycle countdown	●
Quiet performance	Deluxe quiet
Lockable lint filter	●
LED indicators	●
Door swing	Reverse-a-Door
Drum material	White DuraDrum
<b>Appearance</b>	
Colors available	White
Braille kit	14-D242
<b>Weights &amp; Dimensions</b>	
Approx. shipping wt. (lbs.)	125

# Making builders' lives easier.



- An industry-leading company committed to customer satisfaction.
- GE has the leading position with builders, earning a #1 ranking in appliance preference by *Professional Builder* and *Professional Remodeler* for ten years!\*
- A nationwide network of sales professionals and service technicians wholly dedicated to the builder community.

- 24-hour accessibility through award-winning technology
  - GECustomerNet.com
  - GESelectionCenter.com
  - GEAppliances.com
- GE Answer Center® saves you time by providing answers on product features.

\**Professional Builder* and *Professional Remodeler* brand study, 1998-2006, 2008 (no study in 2007)



## 100 years of innovation and we're just getting started

For more than a century, GE has been committed to producing innovative products that change the way people live. The result of thorough research and rigorous testing, GE appliances are designed for years of dependable performance. Today, the GE tradition of quality and innovation continues.