

RIXSON®
ASSA ABLOY

*Checkmate® Stops & Holders
Compatibility Chart*

Absolute Door Control
for Opening
Protection



ASSA ABLOY, the global leader
in door opening solutions

CLOSER x HOLDER COMPATIBILITY CHART											
Rixson/Checkmate Holders											
Concealed						Surface					
Based on 90 deg. Opng. and for 36" wide doors	#1 & 1ADJ	#2	#5	#6ADJ	#4	#7	#8HD	#9 & 9ADJ	#10	#55	
DOOR CLOSERS											
Corbin Russwin											
DC6200/DC6400 (Reg Arm)	No	No	No	Yes	**Yes	Yes	Yes	No	Yes	No	
DC6210/DC6410 (Par. Arm)	Yes	Yes	Yes	Yes	Yes	No	Yes	No	No	No	
DC6210/DC6410 x A13	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	
DC6210/DC6410 x M83 *	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
DC6220/DC6420 (Top Jamb)	No	Yes	Yes	Yes	No	No	No	No	No	No	
DC6220/DC6420 x drop plate	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	
DC3200	No	No	No	Yes	**Yes	Yes	Yes	No	Yes	No	
DC3210	Yes	Yes	Yes	Yes	Yes	No	Yes	No	No	No	
DC3210 x M83 *	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
DC3220	No	Yes	Yes	Yes	No	No	No	No	No	No	
DC3220 x drop plate	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	
DC8200	No	Yes	Yes	Yes	**Yes	Yes	No	No	No	No	
DC8210 *	Yes	Yes	Yes	Yes	Yes	No	No	No	No	No	
DC8210 x A13	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	
DC8210 x M83 *	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
DC8220	No	Yes	Yes	Yes	No	No	No	No	No	No	
DC8220 x drop plate	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	
DC4600	No	Yes	Yes	Yes	**Yes	Yes	No	No	Yes	No	
DC4610	Yes	Yes	Yes	Yes	Yes	No	No	No	Yes	No	
DC4620	No	Yes	Yes	Yes	No	No	No	No	No	No	
DC4620 x drop plate	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	

NOTES: * Minimum 2 7/16" stop width required to install closer bracket and overhead holder bracket in the same location. Otherwise rabbett application must be used.
 FOR #7 O.H.H/S -(NO) Reg. PA installation = OHH arm will interfere with closer arm.
 (NO) Drop plate installation = Location **MAY HAVE** to be adjusted so that arm of OHH will clear drop plate.

** If SNB's used with #4 OHH/S = NO

FOR SOME PARALLEL ARM INSTALLATIONS: No is listed due to the location of the OHH/S bracket interfering with the PA bracket.

CLOSER x HOLDER COMPATIBILITY CHART

Rixson/Checkmate Holders

	Concealed					Surface					
Based on 90 deg. Opng. and for 36" wide doors	#1 & 1ADJ	#2	#5	#6ADJ		#4	#7	#8HD	#9 & 9ADJ	#10	#55
DOOR CLOSERS											
Dorma											
8900 x AF89 (Reg Arm)	No	No	No	No		**Yes	Yes	No	No	No	No
8900 x AF89P (Par. Arm)	Yes	Yes	Yes	Yes		Yes	No	Yes	No	No	No
8900 x PD	Yes	Yes	Yes	Yes		Yes	*Yes	Yes	*Yes	*Yes	*Yes
8900 x AF89J (Top Jamb)	No	Yes	Yes	Yes		No	No	No	No	No	No
8900 x BP89 drop plate	Yes	Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes
8600 x AF86	No	Yes	Yes	Yes		**Yes	Yes	No	No	No	No
8600 x AF86P	Yes	Yes	Yes	Yes		Yes	No	No	No	No	No
8600 x PD	Yes	Yes	Yes	Yes		Yes	*Yes	*Yes	*Yes	*Yes	*Yes
8600 x AF86J	No	Yes	Yes	Yes		No	No	No	No	No	No
8600 x DP86 drop plate	Yes	Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes
7400 x AR	No	Yes	Yes	Yes		**Yes	Yes	No	No	No	No
7400 x ARP	Yes	Yes	Yes	Yes		Yes	No	No	No	No	No
7400 x PD	Yes	Yes	Yes	Yes		Yes	*Yes	*Yes	*Yes	*Yes	*Yes
7400 x ARJ	No	Yes	Yes	Yes		No	No	No	No	No	No
7400 x DP74 drop plate	Yes	Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes
7300/7200 x AR	No	Yes	Yes	Yes		**Yes	Yes	No	No	No	No
7300/7200 x ARP	Yes	Yes	Yes	Yes		Yes	No	No	No	No	No
7300/7200 x PD	Yes	Yes	Yes	Yes		Yes	*Yes	*Yes	*Yes	*Yes	*Yes
7300/7200 x ARJ	No	Yes	Yes	Yes		No	No	No	No	No	No
7300/7200 x DP73 drop plate	Yes	Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes

NOTES: *Install closer bracket back from face of door to the 1 3/4" dimension indicated on the template in order to install overhead bracket in the same location, minimum 2 7/16" stop width required. Otherwise rabbet application must be used.

FOR #7 OHH/S - (NO) Drop plate installation = Location **MAY HAVE** to be adjusted so that arm of OHH will clear drop plate.

** If SNB'S used with #4 OHH/S = NO

FOR SOME PARALLEL ARM INSTALLATIONS: No is listed due to the location of the OHH/S bracket interfering with the PA bracket.

CLOSER x HOLDER COMPATIBILITY CHART

Rixson/Checkmate Holders

	Concealed					Surface					
	#1 & 1ADJ	#2	#5	#6ADJ		#4	#7	#8HD	#9 & 9ADJ	#10	#55
Based on 90 deg. Opng. and for 36" wide doors											
DOOR CLOSERS											
LCN											
4040 (Reg. Arm)	No	No	No	No		**Yes	Yes	Yes	No	No	No
4040P (Par. Arm)	Yes	Yes	Yes	Yes		Yes	No	Yes	No	No	No
4040P x 62A *	Yes	Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes
4040TJ (Top Jamb)	No	No	No	No		Yes	No	Yes	Yes	Yes	Yes
4040TJ x 18G drop plate	Yes	Yes	Yes	Yes		Yes	No	Yes	Yes	Yes	Yes
4010 (Reg. Arm)	No	No	No	No		**Yes	Yes	No	No	No	No
4110 (Par. Arm)	Yes	Yes	Yes	Yes		Yes	No	No	No	No	No
4110 x 62G*	Yes	Yes	Yes	Yes		Yes	Yes	No	No	No	No
4020 (Top Jamb)	No	No	No	No		Yes	No	Yes	Yes	Yes	Yes
4020 x 18G drop plate	Yes	Yes	Yes	Yes		Yes	No	Yes	Yes	Yes	Yes
1461R (Reg. Arm)	No	Yes	Yes	Yes		**Yes	Yes	No	No	No	No
1461P (Par. Arm)	Yes	Yes	Yes	Yes		Yes	No	No	No	No	No
1461P x 62A *	Yes	Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes
1461TJ (Top Jamb)	No	Yes	Yes	Yes		No	No	No	No	No	No
1461TJ x 18 drop plate	Yes	Yes	Yes	Yes		Yes	No	Yes	Yes	Yes	Yes
1371R (Reg Arm)	No	No	No	No		**Yes	Yes	No	No	No	No
1371P (Par. Arm)	Yes	Yes	Yes	Yes		Yes	No	No	Yes	Yes	Yes
1371TJ (Top Jamb)	No	Yes	Yes	Yes		No	No	Yes	No	Yes	Yes
1371TJ x 18TJ drop plate	Yes	Yes	Yes	Yes		Yes	No	Yes	Yes	Yes	Yes
1070R (Reg. Arm)	No	Yes	Yes	Yes		**Yes	Yes	No	No	No	No
1070P (Par. Arm)	Yes	Yes	Yes	Yes		Yes	No	No	No	Yes	Yes
1070P x 62A *	Yes	Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes
1070TJ (Top Jamb)	No	Yes	Yes	Yes		No	No	No	No	No	No
1070TJ x 18 drop plate	Yes	Yes	Yes	Yes		Yes	No	Yes	No	Yes	Yes

NOTES: * For stop widths up to and including 3 1/4" wide, 62A & 62G shoes are always mounted in the rabbet opposite the door.

FOR #7 O.H.H/S - (NO - 4040 Series only) Reg. PA installation = OHH arm will interfere with closer arm.

** IF SNB's used with #4 OHH/S = NO

FOR SOME PARALLEL ARM INSTALLATIONS: No is listed due to the location of the OHH/S bracket interfering with the PA bracket.

CLOSER x HOLDER COMPATIBILITY CHART

Rixson/Checkmate Holders

	Concealed					Surface					
Based on 90 deg. Opng. and for 36" wide doors	#1 & 1ADJ	#2	#5	#6ADJ		#4	#7	#8HD	#9 & 9ADJ	#10	#55
DOOR CLOSERS											
SARGENT											
281-O (Reg. Arm)	No	Yes	Yes	Yes		**Yes	Yes	No	No	No	No
28 -P9 (Par. Arm)	Yes	Yes	Yes	Yes		Yes	No	No	No	Yes	No
281-P3 *	Yes	Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes
281-O (Top Jamb)	No	Yes	Yes	Yes		No	No	No	No	Yes	Yes
281-OZ x 281B drop plate	Yes	Yes	Yes	Yes		Yes	No	Yes	Yes	Yes	Yes
351-O (Reg. Arm)	No	No	No	No		**Yes	Yes	No	No	No	No
351-P9 (Par. Arm)	Yes	Yes	Yes	Yes		Yes	No	No	No	Yes	No
351-P3 *	Yes	Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes
351-OZ (Top Jamb)	No	Yes	Yes	Yes		Yes	No	Yes	Yes	No	No
351-OZ x 351B drop plate	Yes	Yes	Yes	Yes		Yes	No	Yes	Yes	Yes	Yes
1431-O (Reg. Arm)	No	Yes	Yes	Yes		**Yes	Yes	No	No	No	No
1431-P9 (Par. Arm)	Yes	Yes	Yes	Yes		Yes	No	No	No	Yes	Yes
1431-P3 *	Yes	Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes
1431-OZ (Top Jamb)	No	Yes	Yes	Yes		No	No	Yes	No	No	No
1431-OZ x 1431B drop plate	Yes	Yes	Yes	Yes		Yes	No	Yes	Yes	Yes	Yes
1331-JO(Reg Arm)	No	Yes	Yes	Yes		**Yes	Yes	No	No	No	No
1331-JP9 (Par. Arm)	Yes	Yes	Yes	Yes		Yes	No	No	No	Yes	Yes
1331-JO (Top Jamb)	No	Yes	Yes	Yes		No	No	No	No	Yes	Yes
1331-JO x 1331B drop plate	Yes	Yes	Yes	Yes		Yes	No	Yes	Yes	Yes	Yes

NOTES: *Install closer bracket back from face of door to the 1 1/2" dimension indicated on the template in order to install overhead bracket in the same location, minimum 3/ 1/4" stop width required.

** IF SNB's used with #4 OHH/S = NO

FOR SOME PARALLEL ARM INSTALLATIONS: No is listed due to the location of the OHH/S bracket interfering with the PA bracket.

CLOSER x HOLDER COMPATIBILITY CHART

Rixson/Checkmate Holders

Based on 90 deg. Opng. and for 36" wide doors	Concealed					Surface					
	#1 & 1ADJ	#2	#5	#6ADJ		#4	#7	#8HD	#9 & 9ADJ	#10	#55
DOOR CLOSERS											
NORTON/YALE											
7500/4400 (Reg. Arm)	No	No	No	No		**Yes	Yes	No	No	Yes	No
P7500/4400 (Par. Arm)	Yes	Yes	Yes	Yes		Yes	No	No	No	Yes	No
P7500/4400 x 2018S/290 *	Yes	Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes
J7500/TJ4400 (Top Jamb)	No	Yes	Yes	Yes		No	No	No	No	Yes	Yes
J7500/TJ4400 x 7787/487 x drop plate	Yes	Yes	Yes	Yes		Yes	No	Yes	Yes	Yes	Yes
7700/400 (Reg. Arm)	No	No	No	No		**Yes	Yes	No	No	Yes	No
P7700/400 (Par. Arm)	Yes	Yes	Yes	Yes		Yes	No	No	No	Yes	No
P7700/400 x 2018s/290*	Yes	Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes
J7700/TJ400 (Top Jamb)	No	Yes	Yes	Yes		No	No	No	No	Yes	Yes
J7700/TJ400 x 7787/487 drop plate	Yes	Yes	Yes	Yes		Yes	No	Yes	Yes	Yes	Yes
8000/3000 (Reg. Arm)	No	Yes	Yes	Yes		**Yes	Yes	No	No	Yes	No
P8000/3000 (Par. Arm)	Yes	Yes	Yes	Yes		Yes	No	No	No	Yes	No
P8000/3000 x 2018s/290 *	Yes	Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes
J8000/TJ3000 (Top Jamb)	No	Yes	Yes	Yes		No	No	No	No	No	No
J8000/TJ3000 x 8146/3146 drop plate	Yes	Yes	Yes	Yes		Yes	No	Yes	Yes	Yes	Yes
1600/50BC (Reg Arm)	No	Yes	Yes	Yes		**Yes	Yes	No	No	Yes	No
P1600/50BC (Par. Arm)	Yes	Yes	Yes	Yes		Yes	No	No	No	No	No
P1600/50BC x 2018S/290*	Yes	Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes
J1600/TJ50BC (Top Jamb)	No	Yes	Yes	Yes		No	No	No	No	No	No
J1600/50BC x 1688/214 drop plate	Yes	Yes	Yes	Yes		Yes	No	Yes	Yes	Yes	Yes

NOTES: * Soffit bracket is installed 1 3/4" away from face of door.

FOR #7 O.H.H/S-(NO) Reg. PA installation = OHH arm will interfere with closer arm.

(NO) Drop plate installation = Location **MAY HAVE** to be adjusted so that arm
of OHH will clear drop plate.

** IF SNB'S used with #4 OHH/S = NO

FOR SOME PARRALLEL ARM INSTALLATIONS: No is listed due to the location of the
OHH/S bracket interfering with PA bracket.



RIXSON
9100 West Belmont Avenue
Franklin Park, IL 60131 USA
Tel: 800.457.5670
Fax: 800.221.0489
www.rixson.com

ASSA ABLOY CANADA DSS
160 Four Valley Drive
Vaughan, ON L4K4T9
Telephone: 800.461.3007
Fax: 888.940.2242