

STEEL DOOR FRAMES WITH CASING REQUIRE EXTENDED LIP STRIKES

VERIFY THE LENGTH OF THE STRIKE LIP TO MAKE SURE IT WILL EXTEND PAST THE CASING. THE LIP LENGTH SHOULD BE AT LEAST 1 1/2" LIP TO CENTER. IF EXTENDED LIP STRIKE IS NOT AVAILABLE, ORDER TA-10M CASING FILLER. LIST PRICE OF TA-10M FILLER IS \$30.00

Adams Rite

Model	Frame Prep	Frame Face Cutout Depth	Casing Prep	Housing Dimensions			Fire Rated	Notes
				Height	Width	Depth		
7100	No - Rad. Corners							Rad. Corner Faceplate - Aluminum frames
7101	No - Rad. Corners							Rad. Corner with Radius Faceplate - Aluminum frames
7110	No - Face Plate Too Large							7 15/16" high faceplate
7111	No - Face Plate Too Large							10 1/4" high faceplate
7130	No - Face Plate Too Large							6 7/8" high faceplate
7131	No - Face Plate Too Large							6 7/8" high faceplate - Radius faceplate
7140	Yes - Standard	21/32"	13/32"	3 3/8"	1 1/8"	1 5/8"	No	-01 Suffix for extended lip
7160	No - Rad. Corners			3 3/8"	1 1/8"	1 13/16"		Mechanism deeper than frame face
7170	No			3 3/8"	1 1/8"	1 7/8"		Mechanism deeper than frame face
7240	Yes - Standard	21/32"	13/32"	3 3/8"	1 1/8"	1 5/8"	No	-50 Suffix for extended lip
7270	Yes - Custom	27/32"	21/32"	3 3/8"	1 1/8"	1 13/16"	Yes	3/4" throw latch
7400	No - Rad. Corners							Aluminum Frames
7401	No - Rad. Corners							Aluminum Frames - Radius Faceplate
7410	No - Face Plate Too Large							7 15/16" high faceplate
7411	No - Face Plate Too Large							10 1/4" high faceplate
7430	No - Face Plate Too Large							6 7/8" high faceplate
7431	No - Face Plate Too Large							6 7/8" high faceplate - Radius faceplate
7440	Yes	21/32"	13/32"	3 3/8"	1 13/32"	1 1/16"	No	Lip extension kit - LEK7400-50
74R1	No - Rim Exit device			1 3/4" x 4 1/2" frame cutout				Use TA-12, H.M. shop cut hole in stop
74R2	No - Rim Exit device			1 3/4" x 4 1/2" frame cutout				Use TA-12, H.M. shop cut hole in stop

Rev. 8/11/11

STEEL DOOR FRAMES WITH CASING REQUIRE EXTENDED LIP STRIKES

VERIFY THE LENGTH OF THE STRIKE LIP TO MAKE SURE IT WILL EXTEND PAST THE CASING. THE LIP LENGTH SHOULD BE AT LEAST 1 1/2" LIP TO CENTER. IF EXTENDED LIP STRIKE IS NOT AVAILABLE, ORDER TA-10M CASING FILLER. LIST PRICE OF TA-10M FILLER IS \$30.00

HES

Model	Frame Prep	Frame Face Cutout Depth	Casing Prep	Housing Dimensions			Fire Rated	Notes
				Height	Width	Depth		
1006	No	1 11/16"		3 3/8"	1 3/4"	1 11/16"	Yes	1 11/16" Cut out on frame face
4500	Yes	1"		3 5/8"	1 3/8"	1 3/8"		Must use TA-10A
5000	Yes	11/16"	7/16"	3 3/8"	1 3/8"	1 1/16"	No	
5200	Yes (within 1/32")	27/32"	19/32"	3 3/8"	1 5/16"	1 3/16"	No	3/4" throw latch
5900	See 8000 series (5900 series not available after 2/28/10)							
7000	with 701 faceplate	1 3/16"		3 3/8"	1 3/16"	1 19/32"	No	1 3/16" Cut out on frame face
7500	No	1 1/2"		3 3/8"	1 3/8"	1 11/16"	Yes	1 1/2" Cut out on frame face
8000	Yes	21/32"		3 3/8"	1 3/8"	1 1/16"	No	Must use TA-10A
8300	Yes	21/32"		3 3/8"	1 3/8"	1 1/16"	Yes	Must use TA-10A
9400	No - Rim Exit device							Use TA-12, field cut hole in stop for wiring
9500	No - Rim Exit device							Use TA-12, field cut hole in stop for wiring
9600	No - Rim Exit device							Use TA-12, field cut hole in stop for wiring
RF5010	No	1 11/16"		3 3/8"	1 3/4"	1 11/16"		1" Hole for reader/antenna
RF5210	No	1 13/16"		3 3/8"	1 3/4"	1 13/16"		1" Hole for reader/antenna
RF5910	Replaced by RF8010							
RF8010	Yes	21/32"		3 3/8"	1 3/8"	1 1/16"	No	Must use TA-10A
RF8210	Yes	21/32"		3 3/8"	1 3/8"	1 1/16"	Yes	Must use TA-10A
<i>Vista Series</i>								
V3	Yes	13/16"		3 3/8"	7/8"	1 1/4"		
VS112	Yes	11/16"		3 3/8"	7/8"	1 1/8"		
VS112-75	Yes	13/16"		3 3/8"	7/8"	1 1/4"		3/4" throw latchbolt

FOLGER ADAM

310 Series	1 3/8" x 8" Face Plate	3 3/4" x 2 1/2"		3 3/4"	2 5/16"	2 1/2"		
712 Series		1 1/2"		3 3/8"	1 3/4"	1 5/8"		
732 Series		1 1/2"		3 3/8"	1 3/4"	3 5/8"		3 5/8" depth for solenoid
742 Series		1 1/2"		3 3/8"	1 3/4"	1 5/8"		

STEEL DOOR FRAMES WITH CASING REQUIRE EXTENDED LIP STRIKES

VERIFY THE LENGTH OF THE STRIKE LIP TO MAKE SURE IT WILL EXTEND PAST THE CASING. THE LIP LENGTH SHOULD BE AT LEAST 1 1/2" LIP TO CENTER. IF EXTENDED LIP STRIKE IS NOT AVAILABLE, ORDER TA-10M CASING FILLER. LIST PRICE OF TA-10M FILLER IS \$30.00

ROFU

Model	Frame Prep	Frame Face Cutout Depth	Casing Prep	Framing Modification			Fire Rated	Notes
				Height	Width	Depth		
1401	1 1/4" x 5 7/8" Faceplate	1 1/4"		3 3/8"	13/16"	1 1/2"	No	Latch CL lower - Wood frames
1402	Yes	21/32"	13/32"	3 3/8"	13/16"	1 1/2"	No	
1403	1 1/4" x 6 7/8" Faceplate			3 3/8"	13/16"	1 1/2"	No	
1404	1 7/16" x 7 15/16" Faceplate			3 3/8"	13/16"	1 9/16"	No	
1430	CL Latch not CL strike	3 1/2" x 1 7/16"		3 1/2"	1"	1 1/2"	No	1 7/16" Cut out on frame face
1440	CL Latch not CL strike	3 1/2" x 1 7/16"		3 1/2"	1"	1 1/2"	No	1 7/16" Cut out on frame face
1450		3 1/2" x 1 7/16"		3 1/2"	1"	1 1/2"	No	1 7/16" Cut out on frame face
1460	1 3/8" x 9"	3 3/4" x 1 1/2"		3 3/4"	1"	1 1/2"	No	1 7/16" Cut out on frame face
1470	1 3/8" x 9"	3 3/4" x 2"		3 3/4"	1"	2"	No	2" Cut out on frame face
1501	1 1/4" x 5 7/8" Faceplate	1 3/8" x 5/8"		3 1/2"	13/16"	1 1/4"	No	Faceplate flush with frame face - Centers do not line up
1505	1 1/4" x 5 7/8" Faceplate	1 3/8" x 5/8"		3 1/2"	13/16"	1 1/4"	No	Faceplate flush with frame face - Centers do not line up
1507	Yes - Modify Trine 3234 Prep	5/8"	3/8"	3 3/8"	13/16"	1 1/2"	No	1 1/8" x 2 3/4" Faceplate - Requires enlarged face cutout
1508	1 1/4" x 5 7/8" Faceplate	2 3/8" x 5/8"		3 1/2"	1 1/4"	1 1/2"	No	
1509	1 7/16" x 7 15/16" Faceplate	2 7/8" x 13/16"		3 1/2"	1 1/4"	1 1/2"	No	
1512	Surface mounted - Rim Device							
1701	1 1/4" x 5 7/8" Faceplate	1 7/8" x 1 1/4"		3 1/2"	13/16"	1 1/2"	No	Faceplate flush with frame face - Centers do not line up
1702	Yes	21/32"	13/32"	3 3/8"	13/16"	1 1/2"	No	
1703	1 1/4" x 6 7/8" Faceplate			3 3/8"	13/16"	1 1/2"	No	
1704	1 7/16" x 7 15/16" Faceplate			3 3/8"	13/16"	1 9/16"	No	
1802	Yes	21/32"	13/32"	3 3/8"	13/16"	1 1/2"	No	
1803	1 1/4" x 6 7/8" Faceplate			3 3/8"	13/16"	1 1/2"	No	
1804	1 7/16" x 7 15/16" Faceplate			3 3/8"	13/16"	1 9/16"	No	
1960	Rim Exit Device - surface mount							Use TA-12, field cut hole in stop
2402	Yes	21/32"	13/32"	3 3/8"	13/16"	1 5/16"	No	
3401	1 1/4" x 5 7/8" Faceplate	1 1/4"		3 3/8"	13/16"	1 1/2"	No	Latch CL lower - Wood frames
3402	Yes	21/32"	13/32"	3 3/8"	13/16"	1 1/2"	No	
3403	1 1/4" x 6 7/8" Faceplate			3 3/8"	13/16"	1 1/2"	No	
3404	1 7/16" x 7 15/16" Faceplate			3 3/8"	13/16"	1 9/16"	No	
3430	Centerlines do not line up	3 1/2" x 1 7/16"		3 1/2"		1 1/2"	No	1 7/16" Cut out on frame face
3440	Centerlines do not line up	3 1/2" x 1 7/16"		3 1/2"		1 1/2"	No	1 7/16" Cut out on frame face
3450		3 1/2" x 1 7/16"		3 1/2"		1 1/2"	No	1 7/16" Cut out on frame face
3460	1 3/8" x 9"	3 3/4" x 1 1/2"		3 3/4"	1"	1 1/2"	No	1 7/16" Cut out on frame face
3470	1 3/8" x 9"	3 3/4" x 2"		3 3/4"	1"	2"	No	2" Cut out on frame face
3960	Rim Exit Device - surface mount							Use TA-12, field cut hole in stop

STEEL DOOR FRAMES WITH CASING REQUIRE EXTENDED LIP STRIKES

VERIFY THE LENGTH OF THE STRIKE LIP TO MAKE SURE IT WILL EXTEND PAST THE CASING. THE LIP LENGTH SHOULD BE AT LEAST 1 1/2" LIP TO CENTER. IF EXTENDED LIP STRIKE IS NOT AVAILABLE, ORDER TA-10M CASING FILLER. LIST PRICE OF TA-10M FILLER IS \$30.00

Trine

Model	Frame Prep	Frame Face Cutout Depth	Casing Prep	Framing Modification			Fire Rated	Notes
				Height	Width	Depth		
3234	Yes	5/8"	3/8"	1 11/16"	1 1/32"	1"	No	2 3/4" - Proprietary Tooling
3234W	1 1/8" x 3 3/4"	5/8"		1 11/16"	1 1/32"	1"	No	
3258	1 11/16" x 2 5/8" (Full Lip)	5/8"		1 11/16"	1 1/32"	1"	No	
3458	1 15/16" x 4 5/8"	5/8"		1 11/16"	1 1/32"	1"	No	
3478	Yes	9/16"	5/16"	1 11/16"	1 1/32"	1"	No	Proprietary Tooling
2012	Yes	13/16"	9/16"	1 11/16"	1 1/32"	1"	No	Requires TA-10M
S012	No					1 5/8"	No	Mechanism deeper than frame face
001	1 1/4" x 5 7/8" Faceplate	1 3/8" x 5/8"		3 21/32"	15/16"	1 19/32"	No	
002	1 7/16" x 7 15/16" Faceplate	2 7/8" x 21/32"		3 21/32"	15/16"	1 19/32"	No	
003	1 3/4" x 4 11/16" Faceplate							
004	1 3/8" x 6 1/4" Faceplate							
005	1 3/8" x 3 1/2" Faceplate							
S005	1 3/8" x 3 1/2" Faceplate							
006	3 3/8" x 2 1/8" Faceplate							
007	No	13/16"		1 13/16"	31/32"	2 13/16"	No	Mechanism deeper than frame face
EN-400	No - Frame Face Cut out	1 11/16"		3 1/2"	1 5/8"	1 11/16"		
EN-430	No - Frame Face Cut out	1"		3 3/8"	1 5/8"	1 3/4"		Offset centers
EN-435	No - Frame Face Cut out	1"		3 3/8"	1 5/8"	1 3/4"		Offset centers
EN-800	Special notch in stop	1/2" x 3 3/8"		3 1/2"	1 3/4"	1 3/8"		Rim Exit Device - cut out in stop, stop must be 1 3/4" Min. Width
EN-850	Special notch in stop	1/2" x 3 3/8"		3 1/2"	1 3/4"	1 5/8"		Rim Exit Device - cut out in stop, stop must be 1 3/4" Min. Width
EN-900	1 1/4" x 9" Faceplate	1 11/16"		3 1/2"	1 5/8"	1 11/16"		
EN-950	1 1/4" x 9" Faceplate	1 11/16"		3 1/2"	1 5/8"	1 11/16"		
EN-960	1 1/4" x 9" Faceplate	2"		3 3/4"	1 5/8"	2"		
2001	1 1/4" x 5 7/8" Faceplate	3/4"		3 9/16"	7/8"	1 1/2"		
2002	1 7/16" x 7 15/16" Faceplate	21/32"		2 7/8"	1 1/4"	1 1/2"		
2007	Timely ASA Strike Prep - Modified					1 1/2"	No	Modification required
2009	Timely ASA Strike Prep - Modified					1 1/2"	No	Modification required
2678	1 1/4" x 6 7/8" Faceplate	13/16"		2 9/16"	27/32"	1 1/2"		
4800	Rim Exit Device							Use TA-12, field cut hole in stop

Rev. 8/11/11

STEEL DOOR FRAMES WITH CASING REQUIRE EXTENDED LIP STRIKES

VERIFY THE LENGTH OF THE STRIKE LIP TO MAKE SURE IT WILL EXTEND PAST THE CASING. THE LIP LENGTH SHOULD BE AT LEAST 1 1/2" LIP TO CENTER. IF EXTENDED LIP STRIKE IS NOT AVAILABLE, ORDER TA-10M CASING FILLER. LIST PRICE OF TA-10M FILLER IS \$30.00

RCI (Rutherford Controls)

Model	Frame Prep	Frame Face Cutout Depth	Casing Prep	Framing Modification			Fire Rated	Notes
				Height	Width	Depth		
0162	Surf. Mtd. On stop - Rim E.D.							TA-12
0161	Sur. Mtd. On stop - Rim E.D.							TA-12. field cut hole in stop
F1114	No	1 1/2"		3 3/8"	13/16"	1 5/8"	Yes	Mechanism deeper than frame face
F1119	1 3/8" x 9" Faceplate	1 1/2" x 4 3/8"		4 3/8"	13/16"	1 5/8"	Yes	Mechanism deeper than frame face
2114	No	1 1/2" x 4 3/8"		4 3/8"	13/16"	1 5/8"		Mechanism deeper than frame face
2119	1 3/8" x 9" Faceplate	1 1/2" x 4 3/8"		4 3/8"	13/16"	1 5/8"		Mechanism deeper than frame face
2124	No	1 1/2" x 4 3/8"		4 3/8"	13/16"	1 5/8"		Mechanism deeper than frame face
2134	No	1 1/2" x 4 3/8"		4 3/8"	13/16"	1 5/8"		Mechanism deeper than frame face
2314	No	1 1/2" x 4 3/8"		4 3/8"	13/16"	1 5/8"		Mechanism deeper than frame face
2319	1 3/8" x 9" Faceplate	1 1/2" x 4 3/8"		4 3/8"	13/16"	1 5/8"		Mechanism deeper than frame face
2324	No	1 1/2" x 4 3/8"		4 3/8"	13/16"	1 5/8"		Mechanism deeper than frame face
2334	No	1 1/2" x 4 3/8"		4 3/8"	13/16"	1 5/8"		Mechanism deeper than frame face
4104	No	7/8"		3 3/8"	13/16"	1 1/2"		Mechanism deeper than frame face
4114	No	7/8"		3 3/8"	13/16"	1 1/2"		Mechanism deeper than frame face
4119	1 3/8" x 9" Faceplate							
4304	No	7/8"		3 3/8"	13/16"	1 1/2"		Mechanism deeper than frame face
4314	No	7/8"		3 3/8"	13/16"	1 1/2"		Mechanism deeper than frame face
4319	1 3/8" x 9" Faceplate							
F4104	No	7/8"		3 3/8"	13/16"	1 1/2"		29/32" Cut out on frame face
F4114	No	7/8"		3 3/8"	13/16"	1 1/2"		Mechanism deeper than frame face
L6514	Yes	1 1/16"		3 3/8"	1 13/64"	1 1/16"		
S6514	Yes	1 5/32"		3 3/8"	1 13/64"	1 3/16"		
S7514	Yes	7/8"		3 3/8"	13/16"	1 1/2"		

Rev. 8/11/11

STEEL DOOR FRAMES WITH CASING REQUIRE EXTENDED LIP STRIKES

VERIFY THE LENGTH OF THE STRIKE LIP TO MAKE SURE IT WILL EXTEND PAST THE CASING. THE LIP LENGTH SHOULD BE AT LEAST 1 1/2" LIP TO CENTER. IF EXTENDED LIP STRIKE IS NOT AVAILABLE, ORDER TA-10M CASING FILLER. LIST PRICE OF TA-10M FILLER IS \$30.00

Von Duprin

Model	Frame Prep	Frame Face Cutout Depth	Casing Prep	Framing Modification			Fire Rated	Notes
				Height	Width	Depth		
5100	Yes	1 1/16"		3 3/8"	1"	1 11/16"		Mechanism deeper than frame face
6100	Rim E. D. - Stop Mounted							TA-12. field cut hole in stop
6210	No	1 3/16"		3 3/8"		1 7/8"		Mechanism deeper than frame face
6211	No	1 15/32"		3 3/8"		1 7/8"		Mechanism deeper than frame face

SDC (Security Door Controls)

Model	Frame Prep	Frame Face Cutout Depth	Casing Prep	Framing Modification			Fire Rated	Notes
				Height	Width	Depth		
15	No - Frame Face Cut out	7/8"						
25	Yes	11/16"	7/16"	3 3/8"				
45	No - Frame Face Cut out	1 13/64"		3 3/8"	1 3/8"	1 13/64"		
55	No - Frame Face Cut out	1 11/16"		3 3/8"	2 3/8"	1 11/16"		