



# Acoustical Surfaces, Inc.

*Soundproofing, Acoustics, Noise & Vibration Control Specialists*

123 Columbia Court North • Suite 201 • Chaska, MN 55318  
(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: [sales@acousticalsurfaces.com](mailto:sales@acousticalsurfaces.com)  
Visit our Website: [www.acousticalsurfaces.com](http://www.acousticalsurfaces.com)

**We Identify and S.T.O.P. Your Noise Problems**



## QUILTED CURTAIN S.T.O.P.

**Portable Acoustical Enclosures & Screens**

- ✓ **For Unusual Conditions**
- ✓ **Cost Effective**
- ✓ **Water & Chemical Resistant**
- ✓ **Exterior Applications**

**MATERIAL:** Foam or fiberglass core, faced with quilted aluminized fabric.

**PATTERN:** Quilted pattern

**FEATURES:** Effective and durable absorber with mass loaded vinyl barrier option.


**APPLICATIONS:** Effective solution to a wide range of unusual problems. Machinery and work area enclosures. Industrial absorbers, portable screens.

**THICKNESS:** 1" & 2" **SIZES:** 48" - 54" Wide; Lengths up to 25'

**COLOR:** Silver (Other colors available upon request).

**FLAMMABILITY:** ASTM E84, Class A. Flame Spread: 23, Smoke Developed: 30

**INSTALLATION:** Hook and loop fasteners, grommet hangers, curtain support hardware.



**QUILTED CURTAIN S.T.O.P. Sound Absorption Coefficients – C423**

Frequency	125Hz	250Hz	500Hz	1KHz	2KHz	4KHz	NRC
1" Thick w/oBarrier	.12	.47	.85	.84	.64	.62	.70
2" Thick w/oBarrier	.19	.99	.96	.80	.67	.33	.85
1" Thick w/Barrier	.12	.47	.85	.84	.64	.62	.70
2" Thick w/Barrier	.19	.99	.96	.80	.57	.33	.85

**QUILTED CURTAIN S.T.O.P. Sound Transmission Loss - ASTM E90**

Frequency	125Hz	250Hz	500Hz	1KHz	2KHz	4KHz	STC
1" Thick w/Barrier	11	16	24	30	35	35	27
2" Thick w/Barrier	13	20	29	40	50	55	32