



Acoustical Surfaces, Inc.

SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North • Suite 201 • Chaska, MN 55318

(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: sales@acousticalsurfaces.com

Visit our Website: www.acousticalsurfaces.com

We Identify and S.T.O.P. Your Noise Problems

GREEN SERIES™ ADHESIVE

Construction Adhesive

- **High Performance**
- **Nonflammable**
- **Environmentally Friendly**
- **Ultra Low VOC Content**
- **Low Odor**
- **Easy Cleanup with Water**



GreenSeries™ Adhesive is a high performance, non-flammable, environmentally friendly construction adhesive. This product's unique formulation offers Green Builders a high performance, low gassing, latex based construction adhesive without sacrificing strength and performance.

SIZE:

28 fl. oz. (825 mL)

COVERAGE:

1/4" bead extrudes approximately 86 ft.

3/8" bead extrudes approximately 38 ft.

Feature	Benefits
Ultra low VOC content	GREENGUARD approved and meets LEED Requirements
Water-based adhesive	Non-Flammable, environmentally friendly
Bonds to most building materials	Provides a strong, durable bond to multiple surfaces; Bonds well to wet, frozen and treated lumber
Gap filling	Will bridge minor gaps when bonding irregular surfaces; Helps reduce squeaks and sound transmission
Easy cleanup with water (uncured adhesive)	Eliminates the use of harsh cleaning chemicals
Low odor	Great indoor projects - no strong solvent odor

Continued on next page...



Acoustical Surfaces, Inc.

SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North • Suite 201 • Chaska, MN 55318

(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: sales@acousticalsurfaces.com

Visit our Website: www.acousticalsurfaces.com

We Identify and S.T.O.P. Your Noise Problems

TOOLS TYPICALLY REQUIRED:

Utility knife, caulking gun and tool to puncture inner seal of cartridge.

SAFETY PRECAUTIONS:

Wear gloves. Preparation: The temperature of the adhesive, the surfaces and the working area must be above 40°F (4°C) and below 100°F (38°C). For best performance, apply adhesive at 70°F (21°C). Ensure surfaces to be bonded are clean, dry, structurally sound and free of dust, grease, oil, snow, ice, standing water or other contaminants. To increase adhesion, sand glossy surfaces to a dull finish. Pre-fit all materials prior to applying product. Cut off tip of cartridge at a 45° angle to desired bead size. Puncture inside seal of cartridge.

STORAGE AND DISPOSAL DAMAGED BY FREEZING:

Store in a cool, dry location at room temperature. Take unwanted product to an approved household hazardous waste transfer facility. Hardened material may be disposed of with trash.

DISCLAIMER:

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Purchasers should test the products to determine acceptable quality and suitability for their own intended use. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

PRECAUTIONS:

CAUTION! CONTAINS ETHYLENE GLYCOL and Crystalline Silica. Avoid eye contact. Do not take internally. Use with adequate ventilation. **KEEP OUT OF REACH OF CHILDREN.**